



# 8CH 5MP H.264 NVR

#### Features

- 8-channel real time recording up to 5MP
- H.264 dual-stream recording
- Sophisticated event management
- Synchronized 8-ch playback
- 12x video magnification
- DDNS, P2P for Internet connectivity
- Embedded Linux ensuring reliable operations




### Dimensions



## **Specifications**

ModelNW-11008VIDEOCompatibilityWAMA & ONVIF (Profile S) IP camerasInput8Resolution2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576OutputVGA, HDMICompressionH.264Bit Rate16-8000kbpsDisplay1/4/6/8/9AUDIOIPC audio inOutput-CompressionG.711ARECORDING AND PLAYBACK-				
CompatibilityWAMA & ONVIF (Profile S) IP camerasInput8Resolution2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576OutputVGA, HDMICompressionH.264Bit Rate16-8000kbpsDisplay1/4/6/8/9AUDIOIPC audio inOutput-CompressionG.711A				
Input     8       Resolution     2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576       Output     VGA, HDMI       Compression     H.264       Bit Rate     16-8000kbps       Display     1/4/6/8/9       AUDIO     IPC audio in       Output     -       Compression     G.711A				
Resolution     2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, 960x576       Output     VGA, HDMI       Compression     H.264       Bit Rate     16-8000kbps       Display     1/4/6/8/9       AUDIO     IPC audio in       Output     -       Compression     G.711A				
Resolution960x576OutputVGA, HDMICompressionH.264Bit Rate16-8000kbpsDisplay1/4/6/8/9AUDIOIPC audio inOutput-CompressionG.711A				
CompressionH.264Bit Rate16-8000kbpsDisplay1/4/6/8/9AUDIOIPC audio inOutput-CompressionG.711A				
Bit Rate     16-8000kbps       Display     1/4/6/8/9       AUDIO     IPC audio in       Output     -       Compression     G.711A				
Display 1/4/6/8/9   AUDIO   Input IPC audio in   Output -   Compression G.711A				
AUDIO   Input IPC audio in   Output -   Compression G.711A				
Input IPC audio in   Output -   Compression G.711A				
Output -   Compression G.711A				
Compression G.711A				
RECORDING AND PLAYBACK				
Max. Frame Rate 25/30fps				
HDD 1 x 3.5" SATA				
Recording Mode Manual, event driven, schedule				
Simultaneous Playback 8 channels				
Searching Mode Advanced timeline, channel, event, past moment				
Playback Mode Normal, fast FWD/BWD, slow FWD/BWD, 30-sec step, frame- by-frame				
Snapshot JPEG format				
Back-up Network, USB				
EVENT				
Event Type External alarm, video motion detection, video analytic (with intelligent IP cameras)				
Video Analytic Function -				
Video Analytic Channel -				
Action Type Dial-back, relay switch control, email notification, buzzer				
External Alarm Input 2 + IPC alarm in				
Relay Output 1				
COMMUNICATION				
Network RJ-45, 100 base-T				
Protocol TCP/IP, HTTP, DDNS, SMTP (SSL), DHCP, PPPoE, UPNP, NTP, P2P, FTP				
Concurrent Connection 4				
MISCELLANEOUS				
Operating Environment $-10^{\circ}$ C ~ 55 $^{\circ}$ C / 90% relative humidity (no condensation)				
Power Supply DC12V/3A, 10W (excluding HDD)				
Dimension (mm) 300 (W) x 209 (D) x 48 (H)				
Weight 1 kg (excluding HDD)				





#### WAMA Technology Limited

Unit 502, 5/F, Block B, Wing Kut Industrial Building,			
608 Castle Peak Road, Kowloon, Hong Kong.			
Tel : (852) 3703 9260	Email	: info@wamatech.co	
Fax : (852) 3705 0053	Website	: www.wamatech.co	