

AF5010

10x AHD Mini Speed Dome Camera



Specifications



Features

- 1/3" 2MP Sony CMOS Sensor
- 10x Optical Zoom
- Resolution: 1080p
- 128 presets, 4scans, 4tours,
 4patterns
- OSD menu
- COC, Pelco-P/D

Dimension

Unit: mm



11005		AFF040
MODEL		AF5010
VIDEO	IMAGE SENSOR	1/3" 2MP Sony CMOS Sensor
	RESOLUTION	1080p
	MINIMUM ILLUMINATION	Color: 0.5lux, BW: 0.1lux
	LENS	10x optical zoom f =5.1mm-51mm
	ANGLE OF VIEW	55.2°(Wide) to 3.2°(Tele)
	S/N RATIO	≥52dB
	VIDEO OUTPUT	1080p AHD / CVBS
Function	OSD MENU	Built-in
	VIDEO SETTING	Sharpness, Brightness, D-WDR, WB, NR, BLC, AGC
	D/N MODE	Manual / Auto
	AF MODE	Auto / keyauto / Manual
	IRIS	Auto
	OPERATION ANGLE	Pan 0°~360° with continuous rotation; tilt 0°~90°
	MANUAL SPEED	Pan: 0.1°~300°/s; Tilt: 0.1°~200°/s
	PRESET	128 Presets
	SCAN	355° programmable, 4 scans
	TOUR	4 tours, and speed & park time of presets can be set.
	PATTERN	4 patterns, and each record time is not less than 180s
	PROTOCOLS	Pelco-P/D / COC(AHD 1080p)
	COMMUNICATION	RS485 (Baud rate 2400 / 4800 / 9600 / 19200bps)
POWER	VOLTAGE	12VDC
	MAX. RATING	5W
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	-10℃~+50℃
MECHANICAL DESIGN	PROTECTION GRADE	Indoor dome, TVS lightning protection, surge protection and voltage transient protection
	WEIGHT	1.3kg

TeleEye Group

Hong Kong China Malaysia Philippines

South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY:

www.TeleEye.com