

- 1/3" 4MP CMOS sensor
- Electric vari-focal  
f=2.8-12mm lens  
Angle of view: 94° ~ 30°
- 30-50m IR illumination range
- H.265 / H.264 compression
- AI Detection:  
Face detection  
Human / Vehicle detection
- IP67 & IK10 ingress protection
- Power over Ethernet
- ONVIF Profile S

## MP4056AE



### 4MP Network IR Electric Vari-Focal Dome with AI Detection



MODEL

MP4056AE

Unit: mm



### Accessories



Junction Box: JB0207



Wall Mount Bracket:  
JB0207 + WM0407

Terms & Conditions 使用細則  
Design and specifications are subject to change without prior notice. Copyright © 2019 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

VIDEO	IMAGE SENSOR	1/3" 4MP CMOS
	RESOLUTION	4MP ( 2560×1440 ), 3MP ( 2304×1296 ), 1080P ( 1920×1080 ), 720P ( 1280×720 ), D1. CIF. 480×240
	FRAME RATE	Up to 25/30fps
	MINIMUM ILLUMINATION	0.005 lux @F1.6, AGC ON; 0 lux with IR
	IR DISTANCE	30~50M
	LENS	f=2.8mm ~ 12mm@F1.4 motorized zoom lens
	ANGLE OF VIEW	94° ~ 30°
	ELECTRONIC SHUTTER	1 / 30 s ~ 1 / 100000 s
	VIDEO SETTINGS	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc
	ANALOG VIDEO OUTPUT	CVBS video output ( BNC × 1)
AUDIO	INPUT	1CH Audio input or 1CH Built-in MIC
	OUTPUT	1CH
CONNECTIVITY	NETWORK INTERFACE	RJ45 × 1, 10M / 100M self-adaption
	NETWORK PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
	CONCURRENT USERS	4
	WEB SERVER	Built-in
COMPRESSION	ONVIF	Profile S
	VIDEO COMPRESSION	H.265 / Enhanced H.264
	VIDEO STREAMING	3 Independent Streams
FUNCTION	AUDIO COMPRESSION	G711A/U
	AI DETECTION	Face detection; Human detection; Vehicle detection
	SMART ALARM	Intrusion detection; Line crossing detection; Video Exception: Motion detection
	ACTION	Snap, Recording, Email
	ALARM INPUT	1CH
EDGE RECORDING	ALARM OUTPUT	1CH
	MICRO SD Card	Max. 128GB
POWER	VOLTAGE	12VDC
	MAX. RATING	<10.5W
	POE	YES, IEEE802.af
OPERATING ENVIRONMENT	AMBIENT TEMPERATURE	30°C ~ 60°C
	RELATIVE HUMIDITY	Less than 95% ( non-condensing )
MECHANICAL DESIGN	WATER PROOF	IP67
	VANDAL RESISTANT	IK10
	DIMENSION	Φ 141 mm x 100.2 mm
	WEIGHT	900g