



CHANGE			
EDITI	MODIFICATION	UPDATE DATE	SIGNATURE

- NOTES:
1. Operation Temperature: -40°C ~ +85°C.
 2. Electrical Characteristics:
 - 2.1 > Rated Current: 125V AC, 1.5A @ 25°C.
 - 2.2 > Contact Resistance: 20mΩ Max.
 - 2.3 > Insulation Resistance: 500MΩ Min, 100V DC/min.
 - 2.4 > Voltage Proof: 1000V AC/1 minute no breakdown.
 3. Mechanical Characteristics:
 - 3.1 > Insertion Force & Withdrawal Force: 20N Max.
 - 3.2 > Durability: 750 cycles Min.
 4. Environmental compliance:
 - 4.1 > the products are compliant with the RoHS, and REACH etc.

1	Modular Plug	Contacts	8PCS	/	<input type="checkbox"/> 2 Prongs <input checked="" type="checkbox"/> 3 Prongs	<input type="checkbox"/> G/F" <input type="checkbox"/> 1u" <input type="checkbox"/> 3u" <input checked="" type="checkbox"/> 6u" <input type="checkbox"/> 15u" <input type="checkbox"/> 30u" <input type="checkbox"/> 50u" <input type="checkbox"/> OTHER	<input checked="" type="checkbox"/> Brass <input type="checkbox"/> Phosphor copper
		Housing	1PCS	20*2551**	CAT6/UTP HOUSING/LONG TYPE/ONE-PIECE/WIRE HOLE ϕ 1.10mm		<input checked="" type="checkbox"/> 94V-2 <input type="checkbox"/> 94V-0
NO.	NAME	QTY	PART NO.	DESCRIPTION		MATERIAL	

Voltaa Global

PRODUCT NO	IVR45U-NB-P1	DESCRIPTION	RJ45 Connectors UTP Cat6 1.1mm No Boot Transparent		SHEET.	1/1			
MATERIAL	/	UNIT	mm	SCALE	1:1	DWG NO	MP23025	EDITI	A/0
DIMENSIONAL TOLERANCE		THIRD ANGLE PROJECTION		DRAWN	LIJING	DATE	2020.08.20		
X. X ±0.2 X. XX ±0.10 X. XXX ±0.05 ANGLE ±2°				CHECK	LAMPE	DATE	2020.08.20		
				APPRO.	LIAOGUOZHONG	DATE	2020.08.20		