# BEYOND SHIPLAP BY NINTH & VINE

# **QUICK START INSTALLATION INSTRUCTIONS**

(see www.ninthandvine.com/pages/tutorials for our full, in depth instructions/tutorials)

### MINIMUM TOOLS

- 1 TAPE MEASURE
- 2 LEVEL
- 3 PENCIL
- **4 DUST MASK**
- **5 EYE PROTECTION**
- 6 CUTTING TOOL:

SPEED SQUARE AND HAND SAW MINIMUM

7 J ROLLER:

IF INSTALLING WITH ADHESIVE TAPE



















## WALL PREPARATION

- Wall surface must be clean, dry, structurally sound, flat, free of significant texture.
- If your wall is heavily textured, the (optional) supplied foam tape may be insufficient.

## **FLEXIBLE INSTALLATION OPTIONS**

(Check your moulding to make sure it is level)

## Peel-and-stick adhesive tape

- The adhesive tape is very strong. Before you remove the protective backing for final installation, be sure to test fit each plank as you go to assure proper fit.
- After test fitting, remove the tape backing and apply to the wall.
  Use popsicle sticks, or nickels to create gaps between planks if desired.
  Use a J roller every few rows to activate the pressure sensitive adhesive tape. This step is very important to assure proper adherence.
- Edges & Corners: we recommend wood or metal square edge moulding trim to finish. Paint or stain trim pieces as desired to match or compliment your planks.

# Other installation options

 See our full tutorials at www.ninthandvine.com/pages/tutorials for other installation options such as using construction adhesive (glue), or finishing nails.

# BEYOND SHIPLAP BY NINTH & VINE

# QUICK START INSTALLATION INSTRUCTIONS

(see www.ninthandvine.com/pages/tutorials for our full, in depth instructions/tutorials)

### **MAKING CUTS**

- Use a measuring tape and speed square to mark the desired length of your board.
- Flexible cutting options: Miter (chop) saw is optimal. If you do not have a miter saw a hand saw will suffice use a speed square or miter box as a guide for a straighter cut.

# **CUTTING PLANKS/PANELS LENGTHWISE**

- Test fit the plank where it will be installed.
- · Using a pencil mark both ends of the plank where it needs to be cut.
- \* Next use a straight edge or chalk line to connect your two marks.
- \* We recommend using a Circular Saw or Table Saw to cut the plank lengthwise.

### **ADVISEMENTS**

- Warning: Wood dust is known to the State of California as a Carcinogen.
  Wear protective equipment while cutting and installing wood products.
- Warning: Wood is flammable.
  Do not install this product near open flame or heat source such as a fireplace or furnace.
- This product is not to be installed as a floor.
- This product is not intended for installation in very damp or wet areas.
- This product is made of recycled wood and thereby susceptible to changes in temperature and humidity.
- This product is for interior use only.
- This product may be used for ceiling applications as long as you adhere to local building codes for installation procedures and restrictions.

