

ArmaFinish 99

THE ELASTIC PAINT DESIGNED FOR PROTECTION & COVERING OF ARMAFLEX

- Resistant to weathering and ageing
- Coating remains elastic
- Drip-free paint
- Specially developed for covering Armaflex®
- Protection of Armaflex® insulation materials



ARMAFINISH 99	
UV resistant paint that remains permanently elastic, resistant to weathering and with good ageing resistance.	
Colour	Black, White (RAL 9001) OR GREY (RAL 7037)
Material type	Non-drip
Material special info	Normal consumption: 0.55 Litres per M ² when two coats applied (corresponds to a dry film thickness of 0.26mm)
Applications	Protection of ArmaFlex insulation materials when installed outdoors and for marking purposes when used indoors.
Assembly	ArmaFlex insulation (except HT/ArmaFlex & ArmaFlex Ultima, see product data sheets) installed outdoors, should be covered with two coats. Application temperature: +10 °C to +30 °C, Drying time: 2 hours (+20 °C), Max relative humidity: 80%. It's necessary to allow 2 hours between each coat and the second coat must be applied within 7 days. The paint may be applied with a brush or roller and tools cleaned with water or ArmaFlex cleaner.
Remarks	Unprotected ArmaFlex must not be exposed to weathering for more than 3 days and ArmaFinish 99 paint should be applied as soon as possible. The protective coating should be inspected at regular intervals. After 2 years at the latest a further two coats should be applied.

TECHNICAL DATA

Technical features	
Storage & shelf life	12 months in unopened container. Once open keep container tightly closed in a cool, well ventilated place and protect from frost.
Explosion limits	None
Recycling	Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. For details see relevant Safety Data Sheet. Cans must be emptied prior to recycling. Cans containing adhesive must be recycled into new product.

ARMAFINISH 99 PAINT



Code	Description	Pices/carton
FINISH/BK-2.5	Protective paint for ArmaFlex, black, 2.5 Litres	4
FINISH/WH-2.5	Protective paint for ArmaFlex, White, 2.5 Litres	4
FINISH/GY-2.5	Protective paint for ArmaFlex, grey, 2.5 Litres	4