

# Knauf Joint Cement Premium

## Data Sheet



**Knauf Joint Cement Premium is a lightweight air drying compound for bedding tapes and finishing joints by hand or machine application. Knauf Joint Cement Premium produces an exceptional finish with minimal sanding effort.**

### Knauf Application

- Interior applications only
- For jointing of gypsum boards
  - For bedding joint tapes and finishing joints by hand or machine application

### Physical Characteristics

Bag Size	Bags per pallet	Material No.	Approx. Coverage
kg			m <sup>2</sup> per bag
20	42	622337	80 (for two coats of finish)

### Storage and Handling

Store dry. Protect against frost, high temperatures and exposure to direct sunlight. Recommended for use within 12 months of manufacture.

### Compliance

Bedding filler for interior use acc. to BS EN 13963: 2014

### Performance Data

In compliance with BS EN 13963: 2014, the product is subject to initial type testing and continuous factory product control and bears the CE marking.

### Technical Data

- Reaction to fire: A2
- Flexural Strength: NPD

### Product Features

- 12 months shelf life
- Air drying
- Up to 24 hours drying time (depending on conditions)

### Application/Installation

#### Mixing:

Sprinkle the powder into a suitable clean mixing container with clean, cold tap water.

Allow to stand for 30 minutes.

#### Bedding and Finishing joint tape:

Apply Knauf Joint Cement Premium to the recess formed by the plasterboard tapers. Apply Knauf Joint Tape, submerging the tape into the compound with a taping knife or trowel.

When dry apply second coat.

If sanding is required, at least 120 grit sandpaper is recommended.

#### Suitability:

Suitable for use on all plasterboards manufactured to BS EN 520:2004.

Use in accordance with British Standard Code of Practice BS 8212:1995 and BS 8000: Part 8:1994 workmanship.

#### Cleaning:

Clean containers and tools with water immediately after use.

## Related products

Knauf Joint Cement Premium should be used in conjunction with the following products:

Knauf Fill and Finish 30 Premium  
Material no: 5kg: 622326  
Material no: 10kg: 622329




Knauf Fill & Finish 60 Premium  
Material no: 5kg: 622331  
Material no: 10kg: 622332



Knauf Joint Filler Premium  
Material no: 10kg 622340  
Material no: 20kg 622342



Knauf Joint Tape  
Material no: 258337



Knauf Fibre Tape  
Material no: 493679



## Health & Safety

May irritate eyes or sensitive skin.

Dust may irritate respiratory system.

- Protective gloves, glasses and face mask is recommended.
- Avoid prolonged contact with skin, wash off immediately with water.
- Avoid inhaling – minimise dust, ventilate area, move person to fresh air.
- Avoid ingestion – wash mouth out immediately and drink plenty of water.
- Should any symptoms persist or allergic reaction occur, seek medical advice

Refer to the product MSDS and also the Knauf Guidance for Safe Material Management document:

MSDS: [www.knauf.co.uk/product-data-sheets](http://www.knauf.co.uk/product-data-sheets)

Safe Material Management: [www.knauf.co.uk/literature](http://www.knauf.co.uk/literature)

Sustainability Credentials

Please view Product Sustainability Credentials Sheet:

[www.knauf.co.uk/product-data-sheets](http://www.knauf.co.uk/product-data-sheets)

## Customer Service

UK Tel: 0800 521 050  
Eire Tel.: 01 4620739  
Email: [cservice@knauf.co.uk](mailto:cservice@knauf.co.uk)

## Technical Service

UK Tel.: 0800 030 4135  
Eire Tel.: 01 4620739  
E-mail: [technical@knauf.co.uk](mailto:technical@knauf.co.uk)

## Literature

UK Tel: 03700 613 700  
Eire Tel.: +44 3700 613 700

## Website

[www.knauf.co.uk](http://www.knauf.co.uk)  
[www.knauf.ie](http://www.knauf.ie)

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24



# KNAUF