

## MATERIAL SAFETY DATA SHEET

E-Z VM&P NAPHTHA

**EMERGENCY CONTACT:** FOR CHEMICAL EMERGENCY - SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT,  
CALL CHEMTREC AT 1-(800)-424-9300, DAY OR NIGHT.

<u>INDEX</u>	<u>HMIS</u>	<u>NFPA</u>
4 - Severe	Health 1	Health 1
3 - Serious	Flammability 3	Flammability 3
2 - Moderate	Physical Hazard 0	Reactivity 0
1 - Slight		
0 - Insignificant		

### Section 2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT(S)</u>	<u>CAS Number</u>	<u>% (by weight)</u>
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	98.0 - 100.0

### Section 3. HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS:

##### EYE:

May cause mild eye irritation. Symptoms include stinging, tearing and redness.

##### SKIN:

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

##### SWALLOWING:

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

##### INHALATION:

Breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits (See Section 8).

##### SYMPTOMS OF EXPOSURE:

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), irregular heartbeat.

##### TARGET ORGAN EFFECTS:

Exposure to this material (or a component) has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans.

##### DEVELOPMENTAL INFORMATION:

Based on the available information, risk to the fetus from maternal exposure to this material cannot be assessed.

**CANCER INFORMATION:**

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program or the Occupational Safety and Health Administration.

**OTHER HEALTH EFFECTS:**

No Data

**PRIMARY ROUTE(S) OF ENTRY:**

Inhalation, skin absorption, skin contact, eye contact, ingestion

---

**Section 4. FIRST AID MEASURES**

---

**EYES:**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**SKIN:**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**SWALLOWING:**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**INHALATION:**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

**NOTE TO PHYSICIANS:**

Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 3 - Swallowing) when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma - like conditions). Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

---

**Section 5. FIRE FIGHTING MEASURES**

---

**FLASH POINT:**

50.0 F (10.0 C) TCC

**EXPLOSIVE LIMIT:**

(for product) Lower .9% Upper 7.0%

**AUTOIGNITION TEMPERATURE:**

450.0 F (232.2 C)

**HAZARDOUS PRODUCTS OF COMBUSTION:**

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**FIRE AND EXPLOSION HAZARDS:**

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**EXTINGUISHING MEDIA:**

Regular foam (such as AFFF), water fog, carbon dioxide, dry chemical.

**FIRE FIGHTING INSTRUCTIONS:**

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

---

## Section 6. ACCIDENTAL RELEASE MEASURES

---

### SMALL SPILL:

Eliminate all sources of ignition such as flares, flames (including pilot lights) and electrical sparks. Absorb liquid on vermiculite, floor absorbent or other absorbent material. Persons not wearing proper personal protective equipment should be excluded from area of spill.

### LARGE SPILL:

Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If run-off occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

---

## Section 7. HANDLING AND STORAGE

---

### HANDLING:

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Precautions during use: avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. **WARNING.** Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

### STORAGE:

Store in a cool, dry, ventilated area. Keep containers closed when not in use. Do not store near extreme heat, open flame, or sources of ignition.

---

## Section 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other type safety glasses. Consult your safety representative.

### SKIN PROTECTION:

Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

### RESPIRATORY PROTECTIONS:

If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce exposure.

ENGINEERING CONTROLS:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

EXPOSURE GUIDELINES:

COMPONENT

ALIPHATIC PETROLEUM DISTILLATES (64742-89-8)

OSHA VPEL 1350.000 mg/m3 - TWA

OSHA VPEL 300.000 ppm - TWA

OSHA VPEL 1800.000 mg/m3 - STEL

OSHA VPEL 400.000 ppm - STEL

ACGIH TLV 300.000 ppm - TWA

ACGIH TLV 1370.000 mg/m3 - TWA

---

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

---

BOILING POINT: (for product) 240.0 - 285.0 F (115.5 - 140.5 C) @ 760 mmHg

VAPOR PRESSURE: (for product) 10.200 mmHg @ 68.00 F

SPECIFIC VAPOR DENSITY: 3.800 @ AIR=1

SPECIFIC GRAVITY: .743 - .750 @ 60.00 F

LIQUID DENSITY: 6.190 lbs/gal @ 60.00 F .743 kg/l @ 16.00 C

PERCENT VOLATILES: 100.00%

VOLATILE ORGANIC COMPOUNDS (VOC):                   100.00%  
  743.000 g/l  
  6.190 lbs/gal

EVAPORATION RATE: 9.20 (ETHER)

APPEARANCE: Clear, Colorless

STATE: Liquid

PHYSICAL FORM: Neat

COLOR: Clear, Saybolt Color +30

ODOR: Light Hydrocarbon

pH: Not applicable

VISCOSITY: .7 cps @ 25.00 C

MOLECULAR WEIGHT: 120.0

SOLUBILITY IN WATER: Negligible

HEAT VALUE: 20158.000 BTU

BULK DENSITY: .840 lbs/ft3

---

**Section 10. STABILITY AND REACTIVITY**

---

**HAZARDOUS POLYMERIZATION:**

Product will not undergo hazardous polymerization.

**HAZARDOUS DECOMPOSITION:**

May form: carbon dioxide and carbon monoxide, various hydrocarbons.

**CHEMICAL STABILITY:**

Stable.

**INCOMPATIBILITY:**

Avoid contact with: strong oxidizing agents.

---

**Section 11. TOXICOLOGICAL INFORMATION**

---

No Data

---

**Section 12. ECOLOGICAL INFORMATION**

---

No Data

---

**Section 13. DISPOSAL CONSIDERATION**

---

**WASTE MANAGEMENT INFORMATION**

Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

---

**Section 14. TRANSPORT INFORMATION**

---

**DOT INFORMATION - 49 CFR 172.101****DOT DESCRIPTION & [CONTAINER MODE]:**

PETROLEUM DISTILLATES, N.O.S., 3, UN 1268, II [55 Gal Drum/5 Gal Pail/Gallon]

**DOT DESCRIPTION & [CONTAINER MODE]:**

CONSUMER COMMODITY, ORM-D [Quart/Pint]

**NOS COMPONENT:**

NAPHTHA

**RQ (REPORTABLE QUANTITY) - 49 CFR 172.101**

Product Quantity (lbs)

33333

Component

Xylenes (O-, M-, P- Isomers)

**OTHER TRANSPORT INFORMATION**

The Transport Information may vary with the container and mode of shipment.

---

**Section 15. REGULATORY INFORMATION**

---

**US FEDERAL REGULATIONS:**

TSCA (Toxic Substances Control Act) Status

TSCA (UNITED STATES) The intentional ingredients of this product are listed.

CERCLA RQ - 40 CFR 302.4 (a)

None listed

CERCLA RQ - 40 CFR 302.4 (b)

Materials without a "listed" RQ may be reportable as an "unlisted hazardous substance".

See 40 CFR 302.5 (b).

SARA 302 Components - 40 CFR 355 Appendix A

None

Section 311/312 Hazard Class - 40 CFR 370.2

Immediate (X)      Delayed ( )

Fire (X)

Reactive ( )

Sudden Release of Pressure ( )

SARA 313 Components - 40 CFR 372.65

None

OSHA Process Safety Management 29 CFR 1910

None listed

EPA Accidental Release Prevention 40 CFR 68

None listed

INTERNATIONAL REGULATIONS:

INVENTORY STATUS:

AICS (AUSTRALIA) The intentional ingredients of this product are listed.

DSL (CANADA) The intentional ingredients of this product are listed.

ECL (SOUTH KOREA) The intentional ingredients of this product are listed.

EINECS (EUROPE) The intentional ingredients of this product are listed.

ENCS (JAPAN) The intentional ingredients of this product are listed.

IECSC (CHINA) The intentional ingredients of this product are listed.

PICCS (PHILIPPINES) The intentional ingredients of this product are listed.

STATE AND LOCAL REGULATIONS:

CALIFORNIA PROPOSITION 65:

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause cancer.

ETHYL BENZENE

BENZENE

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance(s) known to the state of California to cause reproductive harm.

TOLUENE

BENZENE

NEW JERSEY RTK LABEL INFORMATION:

NAPHTHA, SOLVENT

64742 - 89 - 8

PENNSYLVANIA RTK LABEL INFORMATION:

ALIPHATIC PETROLEUM DISTILLATES

64742 - 89 - 8

E.E. Zimmerman Company/Elroy Turpentine Company believes that the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.