



#### Safety Data Sheet dated 9/10/2012, version 6

#### 1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

Trade name: RU5BLACK-X

Product type and use: For electroplating industry

Company:

LEGOR GROUP S.p.A. Via del Lavoro, 1 36050 Bressanvido (VI)

Italy

Emergency telephone number of the company and/or of an authorised advisory centre:

LEGOR GROUP S.p.A.

tel. +39 0444 467911 fax +39 0444 660677

Centro Antiveleni Ospedale di Niguarda "Ca Grande" Piazza Ospedale Maggiore 3 20162 Milano

Telephone: +39 (0) 2/66 10 10 29 Telefax: +39 (0) 2/64 44 27 68

Italiano (French, English)

(24-hour-service)

#### 2. HAZARDS IDENTIFICATION

No specific hazards are encountered under normal product use.

The product is harmful following acute exposure to it and poses a serious health threat if ingested. If brought into contact with the eyes, the product causes considerable irritation which can last for over 24 hours.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

1.6 % ammonium chloride

Index number: 017-014-00-8, CAS: 12125-02-9, EC: 235-186-4

Xn,Xi; R22-36

1.35 % sulphamidic acid; sulphamic acid; sulfamic acid

Index number: 016-026-00-0, CAS: 5329-14-6, EC: 226-218-8

Xi; R36/38-52/53

0.98 % pyridine

Index number: 613-002-00-7, CAS: 110-86-1, EC: 203-809-9

F,Xn; R11-20/21/22

### 4. FIRST AID MEASURES

In case of skin contact:

AP032-130/6 Page n. 1 of 5

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

In case of eyes contact:

Wash immediately and thoroughly with running water, keeping eyelids raised, for at least 10 minutes. Following this, protect the eyes with sterile gauze or a clean, dry, handkerchief. OBTAIN A MEDICAL EXAMINATION.

In case of Ingestion:

Induce vomiting. SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.

A suspension of activated charcoal in water, or liquid paraffin may be administered.

In case of Inhalation:

Ventilate the premises. The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area. Should the patient feel unwell, OBTAIN MEDICAL ATTENTION.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Water.

Extinguishers not to be used:

None in particular.

Risks arising from combustion:

Avoid inhaling the fumes.

Protective equipment:

Use protection for the respiratory tract.

#### **6. ACCIDENTAL RELEASE MEASURES**

Measures for personal safety:

Use gloves and protective clothing.

Environmental measures:

Limit leakages with earth or sand.

If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

Cleaning methods:

If the product is in a liquid form, stop it from entering the drainage system.

Recover the product for re-use if possible, or for elimination. The product might, where appropriate, be absorbed by inert material.

After the product has been recovered, rinse the area and materials involved with water.

### 7. HANDLING AND STORAGE

Handling precautions:

Avoid contact and inhalation of the vapours. See, too, paragraph 8 below.

Do not eat or drink while working.

Incompatible materials:

None in particular.

Storage conditions:

Instructions as regards storage premises:

Adequately ventilated premises.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Precautionary measures:

Give adequate ventilation to the premises where the product is stored and/or handled.

Respiratory protection:

Not needed for normal use.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Eye protection:

Use close fitting safety goggles and/or visor conforming to BS 2092 GRADE 1).

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Exposure limit(s) (ACGIH):

ammonium chloride

TLV TWA: 4,57 ppm - 10 mg/m3 TLV STEL: 9,14 ppm - 20 mg/m3

pyridine

TLV TWA: 1 ppm, A3 - 3,24 mg/m3, A3 TLV STEL: A3

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and colour: Dark brown liquid

Odour: Odourless

pH: 1
Melting point / freezing point: n/a

Initial boiling point and boiling range: n/a

n/a °C Flash point: Solid/gas flammability: n/a Autoignition temperature: n/a Explosive properties: n/a Oxidizing properties: n/a Vapour pressure: n/a Relative density: n/a Solubility in water: Total Partition c. (n-octanol/H2O): n/a Vapour density: n/a

#### 10. STABILITY AND REACTIVITY

Conditions to avoid:

Stable under normal conditions.

Substances to avoid:

None in particular.

Hazardous decomposition products:

None.

#### 11. TOXICOLOGICAL INFORMATION

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information on main components of the mixture:

No toxicological information is available on the substances. However, refer to Section 3.

AP032-130/6

Page n. 3 of 5

#### 12. ECOLOGICAL INFORMATION

Adopt good working practices, so that the product is not released into the environment.

List of substances dangerous for the environment and corresponding classification:

1.35 % sulphamidic acid; sulphamic acid; sulfamic acid

CAS: 5329-14-6

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 13. DISPOSAL CONSIDERATIONS

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

ADR-UN number:

ADR-Class:

IATA-Class:

IMDG-Class:

Not dangerous

Not dangerous

Not dangerous

Not dangerous

### 15. REGULATORY INFORMATION

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP) (Annex VI), Regulation (CE) n.790/2009.

Symbols:

Xn Harmful

N Dangerous for the environment

R Phrases:

R22 Harmful if swallowed.

R36 Irritating to eyes.

S Phrases:

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Where applicable, refer to the following regulatory provisions:

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents).

#### 16. OTHER INFORMATION

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

ACGIH - Threshold Limit Values - 2004 edition

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

AP032-130/6

This MSDS cancels and replaces any preceding release.