



STEEL GRIP INC.

Qualified Protection to meet your needs.

Steamgard® SLPE Suit

Steamgard LPE is an aluminized suit designed for brief protection against exposure to steam up to 500 psig and 467°F (242°C). When tested at these conditions, results show this suit can provide 2 to 3.5 seconds of protection against first degree burn and 3.5 seconds of protection against second degree burn.

To find out more about the Multithreat Line of Protective Apparel, or to discuss specific applications, simply contact your **Steel Grip representative : 1-800-223-1595.**

Material of Construction:

Shell: 7.0 oz./yd² aluminized *Kevlar* aramid fabric.

Liner: 10.0 oz./yd² *Nomex* aramid fabric

Components:

Body: Coverall or Jacket and Pants

Head: Hood

Hands: Gloves


Feet: Spats or Overboots

Suit Weight:


6.8 lbs.

7.2 lbs.

Steamgard Protective Steam Suit Selection Guide for Pressurized Steam and Condensate



Thermal Performance of Steamgard LPE Suit Against Steam at 500 psig and 467°F (242°C)



Steamgard® is a registered trademark of Dupont for its protective steam suits. Kevlar® and Nomex® are registered trademarks of Dupont for its aramid fibers.



STEEL GRIP INC.

1501 East Voorhees Street
Danville, IL 61832

Tel 1-800-223-1595
Fax 1-800-270-0517