



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - CENTER HINGE ASSEMBLY (FOR DOORS OVER 8'0" HIGH)
- 4 - 1/8" THICK "TUFF PLAS" COLOR FACE PANEL
- 5 - 1/8" THICK SEALED DOUBLE THERMOPANE SAFETY WINDOW (WINDOW SIZE VARIES DEPENDING ON DOOR SIZE) (CONSULT FACTORY)
- 6 - 11 ga. ROLL-FORMED STEEL SIDE FRAME
- 7 - PVC EDGE TRIM C/W GASKET
- 8 - 1 1/2" SQUARE TUBULAR STEEL DOOR FRAME
- 9 - 1 1/2" THICK URETHANE FOAM INSULATION

DOOR OPENING:
 _____ W x _____ H
 DOUBLE SINGLE
 QUANTITY = _____
 COLOR = _____

- OPTIONS**
 (CHECK BOX IF APPLICABLE)
- DOUBLE DUTCH
 - 5/16" THICK HDP SPRING BUMPERS (UP TO 42" HIGH)
 - 1/2" THICK RUBBER KICKPLATES (UP TO 48" HIGH)
 - CHAIN LOCKING COLLAR
 - EXTENSION "U" BRACKETS
 WALL TYPE = _____
 CURBS / OBSTRUCTIONS ?
 YES NO
 - HOLD OPEN DEVICE
 - 90°-135° WIDE ANGLE HINGE
 - DOOR STOP
 - 12" TOP CANE BOLT ASSEMBLY
 - 46" BOTTOM CANE BOLT ASSEMBLY
 - PROTECTIVE BOLLARDS
 24" 36"
 - FOR USE IN REGISTERED ESTABLISHMENT
 - FREEZER APPLICATION FACING
 ALUMINUM GALVANIZED
 STAINLESS

S.S. QUOTE REF. # _____
 CUSTOMER _____
 APPROVED BY: _____
 P/O No.: _____
 DATE: _____



SERIES 4500 - MODEL 4502
 HEAVY DUTY RIGID INSULATED IMPACT DOOR

DATE: MAY 8/01	SCALE: 1:32
DRAWN: GK	DWG NO: L4502-A