



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - 1/8" CLEAR LEXAN FACE PANEL
- 4 - 1 1/2" SQUARE TUBULAR STEEL DOOR FRAME
- 5 - 11 ga. ROLL-FORMED STEEL SIDE FRAME
- 6 - PVC EDGE TRIM C/W GASKET

**DOOR OPENING:**  
 \_\_\_\_\_ W x \_\_\_\_\_ H

DOUBLE     SINGLE  
 QUANTITY = \_\_\_\_\_  
 COLOR = \_\_\_\_\_

**OPTIONS**  
 (CHECK BOX IF APPLICABLE)

- DOUBLE DUTCH

- 1/2" CLEAR LEXAN

SPRING BUMPERS (UP TO 48"H)

- CHAIN LOCKING COLLAR

- EXTENSION "U" BRACKETS  
 WALL TYPE = \_\_\_\_\_  
 CURBS / OBSTRUCTIONS ?  
 YES     NO

- HOLD OPEN DEVICE

- 90°-135° WIDE ANGLE HINGE

- DOOR STOP

- 12" TOP CANE BOLT ASSEMBLY

- 46" BOTTOM CANE BOLT

ASSEMBLY

- PROTECTIVE BOLLARDS  
 24"     36"

- FOR USE IN REG. ESTABLISHMENT

S. S. QUOTE REF. # \_\_\_\_\_

CUSTOMER \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

P/O No.: \_\_\_\_\_

DATE: \_\_\_\_\_

**SUPERSEAL**

SERIES 4500 - MODEL 4504  
 HEAVY DUTY RIGID INSULATED IMPACT DOOR

DATE: FEB.6/01	SCALE: 1:32
DRAWN: GK	DWG NO: L4504-A