



- 1 - TOP HINGE ASSEMBLY
- 2 - BOTTOM HINGE ASSEMBLY
- 3 - 1/8" "TUFF PLAS" COLOR FACE PANEL
- 4 - 1/8" SEALED DOUBLE THERMOPANE WINDOW
- 5 - CHROMED STEEL DOOR FRAME PROFILE
- 6 - PVC EDGE TRIM C/W GASKET
- 7 - BUBBLE GASKET
- 8 - INJECTED INSULATING FOAM

SELECT MODEL:
 4701 4702

DOOR OPENING:
 _____ W _____ H
 DOUBLE SINGLE
 QUANTITY: _____
 COLOR: _____

OPTIONS (CHECK BOX IF APPLICABLE)

5/16" THICK HDP SPRING BUMPERS

CUSTOM WINDOW DESIGN
 _____ W _____ H

9 1/4" JAMB GUARDS
 (NO WIDE ANGLE JAMB GUARDS)

KICK PLATES

1/4" ABS -COLOR: _____

1/2" HDP -COLOR: _____

WIDE ANGLE HINGE

CHAIN LOCKING COLLAR

CANE BOLT

12" TOP 46" BOTTOM

PROTECTIVE BOLLARDS

24" 36"

EXTENSION "U" BRACKET

HOLD OPEN DEVICE

STAINLESS STEEL

DOUBLE DUTCH

S.S. QUOTE REF. # _____

CUSTOMER _____

APPROVED BY: _____

P/O No.: _____

DATE: _____



SERIES 4700-MODELS 4701/4702 SUPER "TUFF" RIGID INSULATED IMPACT DOOR	
DATE: SEP-04-03	SCALE: 1:32
DRAWN: OC	DWG NO: L4700-B
APPROVED: RT	PART NO: 15-0052