

DIRECT OIL FIRED AIR HEATERS

LOW PRESSURE



YOUTUBE VIDEO

Ventilation of the room is necessary to prevent a deficiency in oxygen supply.

B 35
B 70



PATENTED

B 100
B 150



PATENTED

B 300



PATENTED



- ▶ High air flow
- ▶ Optional room thermostat
- ▶ Two oil filters: oil tank filter and suction filter
- ▶ Thermally protected motor
- ▶ Electronic flame control with photocell
- ▶ Stainless steel combustion chamber
- ▶ Trolley included for B 100, B 150 and B 300
- ▶ Oil tank with level indicator
- ▶ Easy to move
- ▶ Easy maintenance

OPTIONAL ACCESSORIES:




Analog thermostat
TH5 with cable
3 m - **4150.109**
10 m - **4150.112**



Digital thermostat
THD with cable
5 m - **4150.106**
10 m - **4150.107**
for CED models



Trolley
B 35, B 70
4103.925



SPECIFICATIONS		B 35	B 70	B 100	B 150	B 300
Heating power	kW	10	20	29	44	44/88
	Btu/h	34.200	68.300	99.300	150.500	150.500-301.000
	kcal/h	8.600	17.200	25.000	37.900	37.900-75.800
Air displacement	m ³ /h	280	400	800	900	900/1.800
Fuel autonomy	h	16	10	16	10	23/12
Thermostat control		analog or digital		analog or digital		analog or digital
Fuel consumption	l/h	0,9	1,9	2,7	4,2	4,2/8,4
Power supply	V	220-240		220-240		220-240
Frequency	Hz	50-60		50-60		50-60
Electric power	kW	0,08	0,18	0,23	0,28	0,28/0,56
Rated current	A	0,35	0,8	1,0	1,2	1,2/2,4
Protection		IP41		IP41		IP41
Tank capacity	l	15	19	44	44	105
Product size (l x w x h)	mm	745 x 300 x 405	745 x 300 x 405	1075 x 600 x 480	1075 x 600 x 480	1240 x 670 x 640
Box size (l x w x h)	mm	810 x 350 x 450	810 x 350 x 450	1110 x 400 x 450	1110 x 400 x 450	1600 x 750 x 900
Net/gross weight	kg	14/16	15/18	25/28	25/28	53/70
Pallet	pcs	15	15	10	10	1
Dual voltage		no		available		no