

FLESSIBILE ESTENSIBILE INOX PER ACQUA

INOX EXTENSIBLE FLEXIBLE WATER CONNECTION

Art.6500

 Flessibile estensibile M.F. **senza** rivestimento

*Extensible flexible connection M.F. **without** coating*


UNI CIG 7129

- Pressione in ingresso max : 10 bar
- Temperatura max : 200 °C
- Soffietto : AISI 304
- Dado : ottone nichelato
- Raccordo : AISI 304
- Guarnizione : EPDM

- *Pressure in : 10 bar*
- *Max temperature : 200 °C*
- *Hose : AISI 304*
- *Nut : Nickel plated brass*
- *Fitting : AISI 304*
- *Gasket : EPDM*

Utilizzo :

 Applicazione sanitaria, serbatoi
boiler, caldaia

Use :
*Sanitary applications, tank
boiler and heater*


Misura	M.F.	L min / L max	s	
1/2"x1/2"		75 / 130	0,2	10
1/2"x1/2"		100 / 200	0,2	10
1/2"x1/2"		200 / 400	0,2	10
1/2"x1/2"		260 / 520	0,2	10
1/2"x1/2"		500 / 1000	0,2	10
1/2"x1/2"		750 / 1500	0,2	10
1/2"x1/2"		1000 / 2000	0,2	10
1/2"x3/4"		75 / 130	0,2	10
1/2"x3/4"		100 / 200	0,2	10
1/2"x3/4"		200 / 400	0,2	10
1/2"x3/4"		260 / 520	0,2	10
3/4"x3/4"		75 / 130	0,2	10
3/4"x3/4"		100 / 200	0,2	10
3/4"x3/4"		200 / 400	0,2	10
3/4"x3/4"		260 / 520	0,2	10
3/4"x3/4"		500 / 1000	0,2	10
3/4"x3/4"		750 / 1500	0,2	10
3/4"x3/4"		1000 / 2000	0,2	10
1"x1"		75 / 130	0,25	10
1"x1"		100 / 200	0,25	10
1"x1"		200 / 400	0,25	10
1"x1"		260 / 520	0,25	10
1"x1"		500 / 1000	0,25	10
1"x1"		750 / 1500	0,25	10
1"x1"		1000 / 2000	0,25	10
1.1/4"x1.1/4"		100 / 200	0,25	10
1.1/4"x1.1/4"		200 / 400	0,25	10
1.1/2"x1.1/2"		200 / 400	0,25	10

Art.6505

 Flessibile estensibile M.F. **con** rivestimento bianco

*Extensible flexible connection M.F. **with** white coating*


UNI CIG 7129

- Pressione in ingresso max : 10 bar
- Temperatura max : 125 °C
- Soffietto : AISI 304

- Dado : ottone nichelato
- Raccordo : AISI 304
- Guarnizione : NBR

- *Pressure in : 10 bar*
- *Max temperature : 125 °C*
- *Hose : AISI 304*

- *Nut : Nickel plated brass*
- *Fitting : AISI 304*
- *Gasket : NBR*

Misura	M.F.	L min / L max	s	
1/2"x1/2"		100 / 200	0,2	10
1/2"x1/2"		200 / 400	0,2	10
1/2"x3/4"		100 / 200	0,2	10
1/2"x3/4"		200 / 400	0,2	10
3/4"x3/4"		100 / 200	0,2	10
3/4"x3/4"		200 / 400	0,2	10
1"x1"		100 / 200	0,25	10
1"x1"		200 / 400	0,25	10

Art.6510

 Flessibile estensibile F.F. **senza** rivestimento

*Extensible flexible connection F.F. **without** coating*


Misura	M.F.	L min / L max	s	
1/2"x1/2"		100 / 200	0,2	10
1/2"x1/2"		200 / 400	0,2	10
1/2"x3/4"		100 / 200	0,2	10
1/2"x3/4"		200 / 400	0,2	10
3/4"x3/4"		100 / 200	0,2	10
3/4"x3/4"		200 / 400	0,2	10
1"x1"		75 / 130	0,25	10
1"x1"		100 / 200	0,25	10
1"x1"		200 / 400	0,25	10