

FLESSIBILE ESTENSIBILE INOX PER ACQUA

INOX EXTENSIBLE FLEXIBLE WATER CONNECTION

Art.6500

Flessibile estensibile M.F. **senza** rivestimento

Extensible flexible connection M.F. **without** coating



UNI CIG 7129

- Pressione in ingresso max : 10 bar
- Temperatura max : 200 °C
- Soffietto : AISI 304
- Dado : ottone nichelato
- Raccordo : AISI 304
- Guarnizione : EPDM

- *Pressure in : 10 bar*
- *Max temperature : 200 °C*
- *Hose : AISI 304*
- *Nut : Nickel plated brass*
- *Fitting : AISI 304*
- *Gasket : EPDM*

Utilizzo :

Applicazione sanitaria, serbatoi boiler, caldaia

Use :

Sanitary applications, tank boiler and heater



Misura M.F.	L min / L max	s	
1/2"x1/2"	75 / 130	0,2	10
1/2"x1/2"	100 / 200	0,2	10
1/2"x1/2"	200 / 400	0,2	10
1/2"x1/2"	260 / 520	0,2	10
1/2"x1/2"	500 / 1000	0,2	10
1/2"x1/2"	750 / 1500	0,2	10
1/2"x1/2"	1000 / 2000	0,2	10
1/2"x3/4"	75 / 130	0,2	10
1/2"x3/4"	100 / 200	0,2	10
1/2"x3/4"	200 / 400	0,2	10
1/2"x3/4"	260 / 520	0,2	10
3/4"x3/4"	75 / 130	0,2	10
3/4"x3/4"	100 / 200	0,2	10
3/4"x3/4"	200 / 400	0,2	10
3/4"x3/4"	260 / 520	0,2	10
3/4"x3/4"	500 / 1000	0,2	10
3/4"x3/4"	750 / 1500	0,2	10
3/4"x3/4"	1000 / 2000	0,2	10
1"x1"	75 / 130	0,25	10
1"x1"	100 / 200	0,25	10
1"x1"	200 / 400	0,25	10
1"x1"	260 / 520	0,25	10
1"x1"	500 / 1000	0,25	10
1"x1"	750 / 1500	0,25	10
1"x1"	1000 / 2000	0,25	10
1.1/4"x1.1/4"	100 / 200	0,25	10
1.1/4"x1.1/4"	200 / 400	0,25	10
1.1/2"x1.1/2"	200 / 400	0,25	10

Art.6505

Flessibile estensibile M.F. **con** rivestimento bianco

Extensible flexible connection M.F. **with** white coating



UNI CIG 7129

- Pressione in ingresso max : 10 bar
- Temperatura max : 125 °C
- Soffietto : AISI 304
- Dado : ottone nichelato
- Raccordo : AISI 304
- Guarnizione : NBR

- *Pressure in : 10 bar*
- *Max temperature : 125 °C*
- *Hose : AISI 304*
- *Nut : Nickel plated brass*
- *Fitting : AISI 304*
- *Gasket : NBR*

Misura M.F.	L min / L max	s	
1/2"x1/2"	100 / 200	0,2	10
1/2"x1/2"	200 / 400	0,2	10
1/2"x3/4"	100 / 200	0,2	10
1/2"x3/4"	200 / 400	0,2	10
3/4"x3/4"	100 / 200	0,2	10
3/4"x3/4"	200 / 400	0,2	10
1"x1"	100 / 200	0,25	10
1"x1"	200 / 400	0,25	10

Art.6510

Flessibile estensibile F.F. **senza** rivestimento

Extensible flexible connection F.F. **without** coating



Misura M.F.	L min / L max	s	
1/2"x1/2"	100 / 200	0,2	10
1/2"x1/2"	200 / 400	0,2	10
1/2"x3/4"	100 / 200	0,2	10
1/2"x3/4"	200 / 400	0,2	10
3/4"x3/4"	100 / 200	0,2	10
3/4"x3/4"	200 / 400	0,2	10
1"x1"	75 / 130	0,25	10
1"x1"	100 / 200	0,25	10
1"x1"	200 / 400	0,25	10