

# Standridge Color

Plastics Innovation - Transforming Ideas Into Reality

ISO Certified Quality System

## Technical Data Sheet



**Code:** 18031 70% WHITE

This is a **Colorant** compound dispersed into a **Linear Low Density Polyethylene** resin and should process without any hesitancy at normal extrusion conditions.

### Carrier Resin

Type: LLDPE  
Melt Flow: 20 g/10 min  
Density: .924 g/cm<sup>3</sup>

### Concentrate / Compound

Pigment/Additive Loading: 70 %  
Melt Flow: 7 g/10 min  
Specific Gravity: 2.05 g/cm<sup>3</sup>  
Heat Stability: 450 F  
Pellets per Gram: 40  
CONEG Compliant: YES  
FDA Approved: YES

\* Specific FDA regulation compliance can be provided upon request

Standridge Color Corporation  
1196 East Hightower Trail  
Social Circle, GA. 30025  
770.464.3362

[sales@standridgecolor.com](mailto:sales@standridgecolor.com)  
[www.standridgecolor.com](http://www.standridgecolor.com)

The information contained herein is believed to be reliable, but no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications or the results to be obtained there from. The information is based on laboratory work with small-scale equipment and does not necessarily indicate end product performance. Because of the variation in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for the application disclosed. Full-scale testing and end product performance are the responsibility of the user. Standridge Color Corporation shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Standridge Color Corporation's direct control. STANDRIDGE COLOR CORPORATION MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.