

## Product Information



<b>Name</b>	Tint Trim Semi Gloss
<b>Description</b>	Our Trim paint is easy to apply and wash, extra hard wearing and doesn't smell — perfect for all your interior and exterior surfaces, including windows, doors and skirting boards.  It's also free from animal by-products or cruelty, and low in air-polluting VOCs.

## Surface Prep

Use our Prep Paint if you are painting over the following—bare plasterboard, masonry, render, cement sheet, brick, MDF, and interior timber. Also use Prep paint on pre-painted surfaces that have marks, high gloss surfaces or a darker colour.

When painting over a high gloss surface we recommend giving it a quick sand and clean to prep the surface before priming. If you have a repaired patched on your wall you can spot prime over these with a brush, feathering out the edges.

## Application

- Don't apply if ambient temperature is under 10°C or above 30°C or if conditions will drop below 10°C during the drying period
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended
- Stir thoroughly before and during application
- Apply 2 coats by brush, roller or spray
- Provide good ventilation during entire process
- Check the colour for accuracy prior to application

## Properties

<b>Gloss</b>	20-25%
<b>Tools</b>	Brush, roller, spray
<b>Clean up</b>	Water
<b>Dry time</b>	Touch dry 20 mins Recoat 2 hours
<b>Coverage</b>	Up to 16m <sup>2</sup> /L for one coat

<b>Sizes</b>	1L, 4L, 10L
<b>Colour</b>	White, Ultra Deep, Dark, Extra Dark
<b>VOC</b>	<36g/L
<b>Volume Solids</b>	40%
<b>Film build at 16 m<sup>2</sup> p/L</b>	Dry 25µ Wet 62µm

**Thinning** Not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of water can be added per litre of paint to ease application under very warm conditions.

**Care and Maintenance** New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.

**Protect our environment** Don't pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

**Warranty** See [tintpaint.com.au](http://tintpaint.com.au) for full warranty statement.

**Safety and First Aid** Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and leak-proof gloves when painting. If swallowed, drink plenty of water and seek medical advice by contacting a doctor or the Poisons Information Centre (Phone 13 11 26). If skin contact occurs, wash skin thoroughly with soap and water.

In case of eye contact, keep eyes open and flush with running water for at least 15 minutes and seek medical advice.