

240V AC VOLTAGE	13W POWER	1200 LUMENS	3CCT CCT	TRIAC DIMMING	60° BEAM	20 IP RATING
RECESS MOUNTING	50 FACE SIZE	3 YEARS WARRANTY	>83 CRI	FLICKER FREE DRIVER		



**Mounting Depth Table for All Surface Trims when used with X15A (13Watt) Modular COB light**

Surface Mount Trim Model	Fixed or Adjustable	IP Rating	Cut Out Size	Face Size	Mounting depth Required
RF1	Fixed	IP44	70-75 mm	90 mm	88 mm
RF2	Fixed	IP44	89-90 mm	100 mm	118 mm
RA3	Adjustable	IP20	90 mm	105 mm	109 mm
RF4	Fixed	IP44	70-75 mm	90 mm	88 mm
RA4	Adjustable	IP44	80 mm	90 mm	126 mm
RF6	Fixed	IP20	89-90 mm	100 mm	112 mm
RA6	Adjustable	IP20	90 mm	105 mm	101 mm
RF7	Fixed	IP44	90 mm	110 mm	81 mm
RF8	Fixed	IP20	70-75 mm	84 mm	101 mm
RA8	Adjustable	IP20	80 mm	89 mm	118 mm
RF11	Fixed	IP20	89-90 mm	110 mm	104 mm
RF12	Fixed	IP20	89-90 mm	100 mm	112 mm
RF22	Fixed	IP20	70-90 mm	120 mm	94 mm
RF36	Fixed	IP20	89-90 mm	100 mm	112 mm
SQ17	Fixed	IP20	75 x 75 mm	85 x 85 mm	104 mm
SQ1	Adjustable	IP20	90 x 90 mm	100 x 100 mm	104 mm
SQ2	Adjustable	IP20	90 x 170 mm	100 x 185 mm	104 mm
SQ3	Adjustable	IP20	90 x 250 mm	100 x 270 mm	104 mm

**Warning: When 90 mm is recommended cut out size, it's very important not to use a 92mm hole saw. In most cases, The trim may not be able to cover a 92mm cut out.**