

240V AC <small>VOLTAGE</small>	18W <small>POWER</small>	1500 <small>LUMENS</small>	NATURAL WHITE <small>COLOUR</small>	4000K <small>CCT</small>		
TRIAC <small>DIMMING</small>	60° <small>BEAM</small>	20 <small>IP RATING</small>	RECESS <small>MOUNTING</small>	50 <small>FACE SIZE</small>	3 YEARS <small>WARRANTY</small>	>83 <small>CR</small>
FLICKER FREE <small>DRIVER</small>						



Mounting Depth Table for All Surface Trims when used with X20A (18Watt) Modular COB light

Surface Mount Trim Model	Fixed or Adjustable	IP Rating	Cut Out Size	Face Size	Mounting depth Required
RF1	Fixed	IP44	70-75 mm	Not suitable	Not suitable
RF2	Fixed	IP44	89-90 mm	100 mm	135 mm
RA3	Adjustable	IP20	90 mm	105 mm	126 mm
RF4	Fixed	IP44	70-75 mm	Not suitable	Not suitable
RA4	Adjustable	IP44	80 mm	90 mm	143 mm
RF6	Fixed	IP20	89-90 mm	100 mm	129 mm
RA6	Adjustable	IP20	90 mm	105 mm	118 mm
RF7	Fixed	IP44	90 mm	110 mm	97 mm
RF8	Fixed	IP20	70-75 mm	Not suitable	Not suitable
RA8	Adjustable	IP20	80 mm	89 mm	136 mm
RF11	Fixed	IP20	89-90 mm	110 mm	121 mm
RF12	Fixed	IP20	89-90 mm	100 mm	129 mm
RF22	Fixed	IP20	70-90 mm	120 mm	111 mm
RF36	Fixed	IP20	89-90 mm	100 mm	129 mm
SQ17	Fixed	IP20	75 x 75 mm	Not suitable	Not suitable
SQ1	Adjustable	IP20	90 x 90 mm	100 x 100 mm	121 mm
SQ2	Adjustable	IP20	90 x 170 mm	100 x 185 mm	121 mm
SQ3	Adjustable	IP20	90 x 250 mm	100 x 270 mm	121 mm

Warning: When 90 mm is recommended cut out size, it's very important not to use a 92mm hole saw. In most cases, The trim may not be able to cover a 92mm cut out.