

240V AC VOLTAGE	9W POWER	800 LUMENS	3CCT CCT	TRIAC DIMMING	60° BEAM	20 IP RATING
RECESS MOUNTING	50 FACE SIZE	3 YEARS WARRANTY	>83 CRI	FLICKER FREE DRIVER		



Mounting Depth Table for All Surface Trims when used with X3A (9Watt) Modular COB light

Surface Mount Trim Model	Fixed or Adjustable	IP Rating	Cut Out Size	Face Size	Mounting depth Required
RF1	Fixed	IP44	70-75 mm	90 mm	79 mm
RF2	Fixed	IP44	89-90 mm	100 mm	109 mm
RA3	Adjustable	IP20	90 mm	105 mm	100 mm
RF4	Fixed	IP44	70-75 mm	90 mm	79 mm
RA4	Adjustable	IP44	80 mm	90 mm	117 mm
RF6	Fixed	IP20	89-90 mm	100 mm	103 mm
RA6	Adjustable	IP20	90 mm	105 mm	92 mm
RF7	Fixed	IP44	90 mm	110 mm	72 mm
RF8	Fixed	IP20	70-75 mm	84 mm	92 mm
RA8	Adjustable	IP20	80 mm	89 mm	110 mm
RF11	Fixed	IP20	89-90 mm	110 mm	95 mm
RF12	Fixed	IP20	89-90 mm	100 mm	103 mm
RF22	Fixed	IP20	70-90 mm	120 mm	85 mm
RF36	Fixed	IP20	89-90 mm	100 mm	103 mm
SQ17	Fixed	IP20	75 x 75 mm	85 x 85 mm	95 mm
SQ1	Adjustable	IP20	90 x 90 mm	100 x 100 mm	95 mm
SQ2	Adjustable	IP20	90 x 170 mm	100 x 185 mm	95 mm
SQ3	Adjustable	IP20	90 x 250 mm	100 x 270 mm	95 mm

Warning: When 90 mm is recommended cut out size, it's very important not to use a 92mm hole saw. In most cases, The trim may not be able to cover a 92mm cut out.