

## APPLICATION GUIDE USING

# BIO WALL PAINT PRIMER (INTERIOR)

This penetrating wall paint primer is used for interior surface and prior to Bio Wall Paint. This can be used on all new surfaces like plasterboard, concrete, fibro-cement, plaster and other absorbent rumbly surfaces.

### Preparation

- Prepare surface in accordance to [AS 2311](#) The painting of buildings.
- Substrate should be dry and cleaned of greasy and dirty contaminants, and should be solid and resistant to pressure.
- Loose particles from crumbly surfaces must be brushed off. Old coats must be removed.

### Application

- Stir thoroughly with a broad flat stirrer before use.
- Apply evenly using a brush, roller or spray.
- Drying time is 2-6 hours, longer in cold and damp condition.
- Do not apply under 12°C.

### Cleaning

- Immediately after use with soapy water.

### Storage

- Keep tightly sealed in a cool and dry place. Keep out of reach of children.

### Paint Disposal

- Do not pour left over paint down the drain.
- Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection.
- Let empty container dry out well and dispose via recycling program.

*Note: The preceding information is given as a general guide only. Some variations may occur or be advisable for particular conditions. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.*

*“Our information is given in good faith and is based on results obtained from experience and tests. However, as the workmanship is beyond our control, all recommendations and suggestions are made without guarantee.”*