

**WEP 15-125 Quick (600476420) Angle grinder**  
**Cardboard box**

Order no. 600476420  
EAN 4007430245632



Representative picture



- Highest service life for extreme applications: robust, powerful angle grinder with greatest power density in its class for quick work progress
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

## Technical values

### Parameters

|                              |               |
|------------------------------|---------------|
| Amps                         | 13.5 AMPS     |
| Grinding wheel Ø             | 5 "           |
| Output power                 | 900 W         |
| No-load speed                | 11000 RPM     |
| Revolutions at rated load    | 11000 RPM     |
| Torque                       | 31 in-lbs     |
| Spindle thread               | 5/8" - 11 UNC |
| Weight (without power cable) | 5.5 lbs       |
| Cable length                 | 8 ft          |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 6 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 3.6 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LWA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Guard  
Inner support flange  
M-Quick flange nut  
Side handle Metabo VibraTech (MVT)