

**GB 18 LTX BL Q I (603827890) Cordless Tappers**  
**18V ; Cardboard box**

Order no. 603827890  
EAN 4007430306203



Representative picture



- High-grade cordless drill/screwdriver with unique, patented thread-tapping function
- Quick and interruption-free drilling and cleaning of threads thanks to automatic change of the direction of rotation
- Quick-change threaded chuck for mounting square and straight shank drills
- Metabo "Quick" System: Quick change of tool holder and bits, ideal for fast and convenient change of applications
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Selectable "impulse" mode for removal of damaged screws and for spot-drilling on smooth surfaces
- Precision Stop: Electronic torque control with increased precision for accurate and intricate working
- Overload protection: protects the motor from overheating
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminum gear housing for optimum heat dissipation and durability
- With handy belt hook and bit holder, can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M Technology: highest power, gentle charging, and 3 year warranty on the battery pack

## Technical values

### Parameters

|                                 |                        |
|---------------------------------|------------------------|
| Battery voltage                 | 18 V                   |
| Maximum torque - soft           | 531 in-lbs             |
| Maximum torque, hard            | 1062 in-lbs            |
| Adjustable torque               | 9 - 177 in-lbs         |
| Thread diameter                 | M8 - M12               |
| Max. capacity in steel          | 1/2 "                  |
| Max. capacity in soft wood      | 2 1/2 "                |
| No-load speed                   | 0 - 500 / 0 - 1850 RPM |
| Chuck capacity                  | 1/32 - 1/2 "           |
| Weight (including battery pack) | 5.5 lbs                |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Drilling in metal            | 3.2 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 78 dB(A) |
| Sound power level (LwA)      | 89 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Quick change tapping chuck M8-M12  
Side Handle  
Belt hook with bit case  
MetaLoc case insert  
without battery pack, without charger