

## WEPF 9-125 (613069420) 5" Flat-Head Angle Grinder Cardboard box

Order no. 613069420 EAN 4007430244628



Representative picture



- Most compact flat-head angle grinder for working at acute angles down to 43°
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Metabo Long-life motor with patented dust protection for long service life
- Constamatic (C)-Full wave electronics: fast work progress by means of almost constant speed under load
- Tool-free adjustable guard; twist-proof
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Electronic overload protection, soft start and restart protection
- Auto-stop carbon brushes to protect the motor



## **Technical values**

## Parameters

| Amps                         | 8 AMPS               |
|------------------------------|----------------------|
| Minimum accessible angle     | 43 °                 |
| Grinding wheel Ø             | 5 "                  |
| Rated input power            | 910 W                |
| Output power                 | 430 W                |
| No-load speed                | 10000 RPM            |
| Revolutions at rated load    | 8200 RPM             |
| Torque                       | 18 in-lbs            |
| Spindle thread               | 5/8" - 11 UNC        |
| Weight (without power cable) | 4.6 lbs              |
| Cable length                 | 13 ft                |
| Vibration                    |                      |
| Surface grinding             | 5 m/s²               |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 88 dB(A)             |
| Sound power level (LwA)      | 99 dB(A)             |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard Inner support flange Nut with two holes Spanner wrench Side Handle 1 Lamellar grinding disc Flexiamant Super Convex (125mm; P60)