

## WEVF 10-125 Quick Inox (613080420) 5" Flat-Head Angle Grinder Cardboard box

Order no. 613080420 EAN 4007430285126



Representative picture



- The most easy-to-handle flat-head angle grinder with speed regulation for perfect processing of stainless steel e.g. stockade fences
- Particularly developed for the removal of weld slag, rust or paint in narrow frame constructions and for working in tight spaces
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Constamatic (VC)-Full wave electronics with thumbwheel for working with materials requiring customized speeds, which remain almost constant under load
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Electronic safety shutdown of the motor reduces kickback if the disc stops unexpectedly- for high user protection
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor



## **Technical values**

## Parameters

| Amps                         | 9.5 AMPS             |
|------------------------------|----------------------|
| Minimum accessible angle     | 43 °                 |
| Grinding wheel Ø             | 5 "                  |
| Rated input power            | 1000 W               |
| Output power                 | 550 W                |
| No-load speed                | 2000 - 7600 RPM      |
| Revolutions at rated load    | 6300 RPM             |
| Torque                       | 31 in-lbs            |
| Spindle thread               | 5/8" - 11 UNC        |
| Weight (without power cable) | 5.1 lbs              |
| Cable length                 | 8 ft                 |
| Vibration                    |                      |
| Surface grinding             | 4.4 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 91 dB(A)             |
| Sound power level (LwA)      | 102 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard Inner support flange Quick adjusting nut Side Handle 1 Lamellar grinding disc Flexiamant Super Convex (125mm; P60)