

# XMT® Racks

**Multipoperator  
Welding Systems** 

## Quick Specs

### Heavy Industrial Applications

Construction  
Fabrication  
Shipbuilding  
Rental fleets

### Processes

**MIG (GMAW)/Pulsed MIG (GMAW-P)**  
Stick (SMAW)  
TIG (GTAW)  
Flux-cored (FCAW)  
Air carbon arc (CAC-A) cutting and gouging

### Rack Capacity

Allows up to six XMT 350 power sources  
Allows up to four XMT 450 power sources

**Empty Rack Weight** 256 lb. (116 kg)



**XMT 350 FieldPro™  
4-Pack Rack**



**XMT 350 FieldPro™  
6-Pack Rack**

**One easy connection** allows up to six inverters to be connected with one primary power drop.

**Meets IP23**, which is more stringent than IP23S or IP23M ratings.

**Protected from the elements**, the electrical junction box is located well under the galvanized roof panel.

**Lifting eyes simplify** transportation using crane or overhead lifting device.

**Liquid-tight strain reliefs** provided on both welding power source and electrical junction box. Strain relief is designed to resist salt water, alcohol, oil, grease and common solvents.

**Rack roof panel and power source shelves are fabricated from galvanized steel** and painted for added protection in harsh environments.

**Rugged steer skids** stand up to the rugged construction environment.

**Lift truck side and end fork pockets** in base to enable loading and worksite repositioning with fork lift.

**Isolated work terminal** provides a convenient connection point for common workpiece construction.

**Easy power source removal from rack** with ability to wire conventional plug for applications remote from rack.



Warranted for three years parts and labor.



**Miller Electric Mfg. LLC**  
An ITW Welding Company  
1635 West Spencer Street  
P.O. Box 1079  
Appleton, WI 54912-1079 USA

**Equipment Sales US and Canada**  
Phone: 866-931-9730  
FAX: 800-637-2315  
International Phone: 920-735-4554  
International FAX: 920-735-4125

**MillerWelds.com**  




## Additional Features

All racks factory-equipped with power sources include work lead connections between the power sources and isolated work terminal.

All racks factory-equipped with power sources include fuses to provide primary power line protection for each inverter power supply on 460 volts. XMT 350 FieldPro Racks include 20-amp fuses, XMT 450 CC/CV ArcReach Racks include 30-amp fuses. (575-volt operation, if applicable, also utilizes the same fuses as 460-volt operation).

Meets NEC requirements when properly installed and utilizing recommended primary circuit protection and proper fuse selection for primary power applied to rack.

Fuses meet requirements of IEC 60529 for IP-20 finger safe rating.

Fuse holders are designed to accommodate fuses for both 300 amps (208–575 V) and 450 amps (380–575 V) inverters in all voltage ranges applicable to power source.

Visual indication window is built into fuses to assist troubleshooting.

Custom build your own system by mix and matching XMT 350 CC/CV, 450 CC/CV, 350 MPa and 450 MPa. Rack holds a maximum of six XMT 350 models or four XMT 450 models.

All racks come equipped with casters that can be bolted to the base of the rack. Two swivel casters and two non-swivel castes. Large 5-inch diameter wheels enable the rack to be moved over grating and driveway gravel.

## XMT® 350 FieldPro™ Rack



XMT 350 FieldPro  
6-Pack Rack shown.

The XMT 350 FieldPro is a standard in the welding industry for multiprocess welding.

The XMT 350 FieldPro is the most versatile package with unbeatable arc performance. It provides CC and CV welding processes, including stick, TIG, MIG, FCAW and air carbon arc cutting and gouging. The XMT 350 FieldPro is commonly used with the Miller® line of ArcReach® SuitCase® feeders to provide a reliable and durable solution for construction.

### Air Carbon Arc Electrode Size

Power Source	Single Power Source
XMT 350 FieldPro	Up to 1/4 in.

## Specifications (Subject to change without notice.)



Rack	Input Power to Rack	Welding Power Source	Rack Capacity	Dimensions	Weight
4-Pack Rack	208–575 V, 50/60 Hz, three-phase, with Auto-Line*	XMT 350 FieldPro or XMT 350 FieldPro Polarity Reversing	4 units	H: 59 in. (1,498 mm) W: 34 in. (863 mm) D: 32 in. (812 mm)	520 lb. (236 kg)
6-Pack Rack			6 units	H: 59.375 in. (1,508 mm) W: 43 in. (1,092 mm) D: 34.375 in. (873 mm)	759 lb. (344 kg)

\*Fuses included for 460- or 575-volt (if applicable) operation. Only for empty rack orders is it required to order the appropriate fuse kit.

## XMT® 450 CC/CV ArcReach® Rack



The XMT 450 CC/CV ArcReach provides additional power for large cored wire and gouging applications.

The XMT 450 CC/CV ArcReach provides the same multiprocess capability as the XMT 350 with the added benefit of a higher output (450 amps at 100 percent duty cycle). The 230/460 V model leaves the factory linked and fused for 460 V operation.

### Air Carbon Arc Electrode Size

Power Source	Single Power Source
XMT 450 CC/CV ArcReach	Up to 5/16 in.

## Specifications (Subject to change without notice.)



Input Power to Rack	Welding Power Source	Rack Capacity	Dimensions	Weight
460 V, 60 Hz, three-phase*	XMT 450 CC/CV ArcReach	4 units	H: 59.375 in. (1,508 mm) W: 43 in. (1,092 mm) D: 34.375 in. (873 mm)	780 lb. (354 kg)

\*Fuses included for 460-volt operation — not compatible with 230-volt operation. Only for empty rack orders is it required to order the appropriate fuse kit.

# Customize Your System with Different XMT® Inverters

XMT 350 CC/CV



XMT 350 MPa



XMT 450 CC/CV



XMT 450 MPa

### Empty XMT Racks

**195466** 208–575 V

Rack holds up to six XMT 350 models or four XMT 450 models (shown above).

**300970** 208–575 V

Rack holds up to four XMT 350 models (not compatible with the XMT 450).

*Note: Order fuse kit separately for appropriate power supply and intended primary voltage (see chart below).*

### XMT 350 CC/CV

**907161** 208–575 V

**907161011** w/auxiliary power

- Rack capacity – 4 or 6 units
- See literature DC/18.93.

### XMT 350 MPa

**907366** 208–575 V

**907366014** w/Tweco® connectors

- Pulsed MIG capability
- Rack capacity – 4 or 6 units
- See literature DC/18.93.

### XMT 450 CC/CV

**907481** 230/460 V

**907482** 575 V w/ArcReach®

- Rack capacity – 4 units
- See literature DC/18.94.

### XMT 450 MPa

**907479** 230/460 V

**907480** 575 V

- MIG pulse capability
- Rack capacity – 4 units
- See literature DC/18.94.

## LINE FUSE SIZE REQUIREMENTS

Product	Input Voltage (3-phase)	Recommended Line Fuse Size (Amps)	Miller Replacement Parts		Bussman	
			Fuse Kit Stock Number		Individual Fuse Stock Number	
			4-Pack Rack	6-Pack Rack		Individual Fuse Stock Number
XMT 350	208 V	45 A	220764	220763	220075	TCF-45
	230 V					
	460 V	20 A	220766*	220765*	220074	TCF-20
	575 V					
XMT 450	460 V	30 A	220767	Incompatible	220768	TCF-30
	575 V					

\*Rack is supplied with 20 A fuses.

# Ordering Information

Equipment and Options	Stock No.	Description	Qty.	Price
<i>Note: These Inverter Racks are not suitable for use with older inverter models.</i>				
<b>XMT® Racks and Options</b>				
<b>XMT 350 FieldPro Racks</b>	<b>907739</b>	4-pack, 208–575 V, fused 460 V, Tweco® connectors		
	<b>907740</b>	6-pack, 208–575 V, fused 460 V, Tweco® connectors		
<b>XMT 350 FieldPro Polarity Reversing Racks</b>	<b>907742</b>	4-pack, 208–575 V, fused 460 V, Tweco® connectors		
	<b>907741</b>	6-pack, 208–575 V, fused 460 V, Tweco® connectors		
<b>XMT 450 CC/CV ArcReach® Rack</b>	<b>907700</b>	4-pack, 230/460 V, fused and linked for 460 V, stud connectors		
<b>Empty XMT Rack</b>	<b>195466</b>	208–575 V. Holds up to six XMT 350 models or four XMT 450 models		
	<b>300970</b>	208–575 V. Holds up to four XMT 350 models (not compatible with XMT 450) <i>Note: Order <b>required</b> fuse kit below for appropriate primary voltage</i>		
Fuses	<b>220764</b>	208/230 V, 45 A, 4-pack fuse kit		
	<b>220763</b>	208/230 V, 45 A, 6-pack fuse kit		
	<b>220075</b>	45 A, individual fuse		
	<b>220766</b>	460/575 V, 20 A, 4-pack fuse kit		
	<b>220765</b>	460/575 V, 20 A, 6-pack fuse kit		
	<b>220074</b>	20 A, individual fuse		
	<b>220767</b>	460/575 V, 30 A, 4-pack fuse kit		
	<b>220768</b>	30 A, individual fuse		
<b>XMT Rack Power Source Options</b>				
XMT 350 CC/CV	<b>907161</b>	208–575 V with Auto-Line™		
	<b>907161011</b>	208–575 V with Auto-Line™ and auxiliary power		
XMT 350 MPa	<b>907366</b>	208–575 V with Auto-Line™		
	<b>907366014</b>	208–575 V with Auto-Line™ and Tweco® connectors		
XMT 450 CC/CV	<b>907481</b>	230/460 V		
XMT 450 CC/CV ArcReach®	<b>907482</b>	575 V		
XMT 450 MPa	<b>907479</b>	230/460 V		
	<b>907480</b>	575 V		
<b>Accessories</b>				
Rack Running Gear	<b>195114</b>	Only required when purchasing racks and power sources separately. Assembled racks come equipped with casters		

Date:

Total Quoted Price:

Distributed by:





# XMT® 350 FieldPro™ Systems

**Multiprocess Welding System** 

## Quick Specs

### Heavy Industrial Applications

Construction  
Shipbuilding  
Power generation plants  
Rental fleets

### Processes

MIG (GMAW)  
Pulsed MIG (GMAW-P)\*  
RMD®\*  
Stick (SMAW)  
TIG (GTAW)  
Flux-cored (FCAW)  
Air carbon arc cutting and gouging (CAC-A)  
Induction heating\*\*

**Input Power** Auto-Line™, 208–575 V  
Requires 3- or 1-phase power

**Output Range** 10–38 V, 15–425 A

**Net Weight** 93 lb. (42.2 kg)

**ArcReach®** Remote voltage control without a control cord

\*Available with ArcReach Smart Feeder only.

\*\*Available with ArcReach Heater only.



## Game-changing welding technologies can stop you from wasting hours every day.

ArcReach welding technology minimizes the non-value-added time spent walking to and from the power source — and maximizes arc-on time, weld quality and jobsite safety.

When operators have complete control at the feeder or remote — even hundreds of feet away from the power source — it minimizes downtime and maximizes productivity, while improving operator safety and delivering high quality welds.



**More Jobsite Productivity and Efficiency**



**Exceptional Arc Performance**



**Increased Uptime**



**Improved Jobsite Safety**



**Maximize Fleet Compatibility**



**More Operator Control**



**ArcReach® Heater Compatibility**



**XMT 350 FieldPro with ArcReach Technology**

- Ideal for:**
- Structural
  - General construction
  - Ship

**XMT 350 FieldPro with Polarity Reversing and ArcReach Technology**

- Ideal for:**
- Process pipe
  - Module assemblies

## ArcReach®

Remote voltage control at the wire feeder or remote without needing a control cord. See page 2 for more information.



Power source is warranted for three years, parts and labor.



**Miller Electric Mfg. LLC**  
An ITW Welding Company  
1635 West Spencer Street  
P.O. Box 1079  
Appleton, WI 54912-1079 USA

**Equipment Sales US and Canada**  
Phone: 866-931-9730  
FAX: 800-637-2315  
International Phone: 920-735-4554  
International FAX: 920-735-4125

**MillerWelds.com**



# XMT® 350 FieldPro™ Systems Benefits



## More Jobsite Productivity and Efficiency

ArcReach® capabilities eliminate the time spent tracing weld cables hundreds of feet back to the power source because weld operators can make adjustments at the ArcReach wire feeder or remote.

- **Cable Length Compensation (CLC™)** ensures that the voltage a weld operator sets is the voltage they get by automatically adjusting voltage based on weld cable length, even hundreds of feet away from the power source.



## Exceptional Arc Performance

XMT 350 Field Pro systems maximize weld quality, reduce training time and minimize weld defects even while using weld cables that are hundreds of feet long.

- **Common weld failures can be minimized** with stick stops that are specifically programmed to eliminate arc strikes outside of the heat-affected zone.
- **Regulated Metal Deposition (RMD®) and pulsed MIG** are fully supported, enabling operators to use these advanced processes in the field for faster, more efficient welds.



## Increased Uptime

XMT 350 FieldPro welders and ArcReach feeders and remotes have been extensively field-proven and deliver the performance you need with ruggedly constructed internal components and Wind Tunnel Technology™.

- **No more expenses related to maintaining or replacing easily damaged control cords** because the weld cables are used to communicate weld parameters between the wire feeder and power source.



## Improved Jobsite Safety

The chances of slip, trip or fall injuries are decreased because ArcReach technology allows weld operators to make parameter changes at the wire feeder/remote instead of having to travel through multistory and cluttered jobsites back to the power source.



## Maximize Fleet Compatibility

Maximize fleet compatibility and get the benefits of ArcReach when you pair XMT 350 FieldPro welders and ArcReach feeders with other ArcReach compatible products.



## More Operator Control

More control for weld operators with quick, easy adjustments at the wire feeder/remote.

- **Weld operators can Adjust While Welding (AWW™)** to change weld parameters while the arc is on.
- **Inadvertent parameter changes by other jobsite workers can be easily avoided** because connecting an ArcReach accessory from the power source automatically locks out the power source's panel controls.
- **Return to a previous weld process faster** because the power source is restored to its previous settings once the ArcReach accessory is removed.
- **Decrease the chance of an incorrect weld process being used** because Auto-Process Select™ automatically sets the power source to the correct weld process based on the polarity applied to the weld accessory.




## ArcReach® Heater Compatibility

Take charge of your field preheat and bakeout applications up to 600 degrees Fahrenheit (315°C). This system uses induction heating to generate heat in workpieces, so welders can do their own preheating quickly and safely.

## ArcReach®

### Remote control of the power source without a cord.

ArcReach technology uses the existing weld cable to communicate welding control information between the feeder or remote and power source. This technology eliminates the need for control cords, and their associated problems and costs.



# XMT<sup>®</sup> 350 FieldPro<sup>™</sup> Series Features

**AUTO-LINE<sup>™</sup> TECHNOLOGY** For portability and reliability, Auto-Line allows for any input voltage hookup (208–575 V, single- or three-phase) with no manual linking, providing convenience in any job setting. Ideal solution for dirty or unreliable input power.

**Cable Length Compensation (CLC<sup>™</sup>)** makes proper setup of weld parameters faster; automatically adjusting voltage based on weld cable length. This ensures that the voltage a welder operator sets is the voltage they get.

**Adjust While Welding (AWW<sup>™</sup>)** allows operators to make precise adjustments even while a weld bead is being laid, which allows parameters to be changed while the arc is on.

**RMD<sup>®</sup> and pulsed welding** without control cords up to 200 feet away from the power source with the ArcReach<sup>®</sup> Smart Feeder.

**Auto-Bind** automatically establishes an exclusive communication between the power source and the wire feeder, using the existing weld cables upon system power up.

**Wind Tunnel Technology<sup>™</sup>** Internal air flow that protects electrical components and PC boards from dirt, dust and debris... greatly improving reliability.

**Fan-On-Demand<sup>™</sup>** cooling system operates only when needed, reducing noise, energy use and the amount of contaminants pulled through machine.

**Lightweight aerospace-grade aluminum case** offers protection with the benefit of reduced weight.

**New durability standard for field construction.** Designed and built to withstand the harshest field environments.

**Dinse- or Tweco<sup>®</sup>-style weld disconnects** provide high-quality weld cable connections. *Note: Two Dinse-style connectors are supplied with each Dinse machine. Tweco cable connectors are not supplied with the unit and must be order separately.*

**Jobsite mobility is made easy** with a small, compact design and Auto-Line technology.

**Process selector switch** reduces the number of control setup combinations without reducing any features.

**Adaptive Hot Start<sup>™</sup>** makes starting stick electrodes easy without creating an inclusion.

**Infinite arc control** available in the stick and wire modes for easier fine tuning of tough-to-weld materials and out-of-position applications.

**Lift-Arc<sup>™</sup>** provides arc starting that minimizes contamination of the electrode and without the use of high-frequency.

**True multiprocess system** provides conventional stick, TIG, FCAW, and MIG welding as well as the advanced technologies of RMD and pulse.

**Fleet compatibility.** ArcReach-equipped power sources and wire feeders work with non-ArcReach equipment; however, the complete ArcReach benefit is only realized with the ArcReach system.



## XMT 350 FieldPro Specifications (Subject to change without notice.)



Input Power	Voltage Range in CV Mode	Amperage Range in CC Mode	Rated Output	Amps Input at Rated Load Output, 60 Hz							Max. Open-Circuit Voltage	Dimensions	Net Weight
				208 V	230 V	400 V	460 V	575 V	KVA	KW			
Three-phase	10–38 V	5–425 A	350 A at 34 VDC, 60% duty cycle	40.4	36.1	20.6	17.8	14.1	14.2	13.6	75 VDC	H: 17 in. (432 mm) W: 12.5 in. (318 mm) D: 24 in. (610 mm)	93 lb. (42.2 kg)
Single-phase	10–38 V	5–425 A	300 A at 32 VDC, 60% duty cycle	60.8	54.6	29.7	24.5	19.9	11.7	11.2			

Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

## Performance Data



## XMT® 350 FieldPro™ Features



XMT 350 FieldPro



**Remote in use indicator** provides convenient feedback indicating an ArcReach® wire feeder is controlling the power source. While under ArcReach control, process and voltage/ amperage adjustments are locked out, preventing accidental changes by personnel other than the welding operator.



**LED process indicator.** Front panel process selections are illuminated with an LED that identifies the active process. This enables the selected weld process to be seen at a distance from the power source. Includes carbon arc gouging mode for enhanced arc stability and control, and two stick modes (EXX10 and EXX18) designed to reduce spatter and enhance arc starts.

**Auto Remote Sense™** enables unit to automatically use remote control if connected to remote control receptacle.

**14-pin receptacle** has the flexibility to be used with spool guns, feeders, and remote controls.




ArcReach Stick/TIG Remote

**Portable and lightweight,** the ArcReach® Stick/TIG Remote paired with an XMT 350 FieldPro power source allows you to change weld settings at your work area, saving a trip to the power supply. No extra control cord to purchase, maintain, string or unstring — saving time and money.

## XMT 350 FieldPro Polarity Reversing Features



XMT 350 FieldPro  
with Polarity Reversing



1. Stick Process Selection Button
2. Amperage Output Adjustment
3. Stick Electrode Type Selection
4. Polarity Indicators
5. Digital Meter
6. TIG Process Selection Button
7. In Use Indicator
8. Remote Indicators

**Easy to use.** The XMT 350 FieldPro with Polarity Reversing power source is streamlined and simplified to reduce setup time and potential weld defects. Pushbutton process changeover eliminates the need for swapping cables. The robust design will withstand harsh environments common in the field.

**Superior arc performance.** The optimized stick and TIG performance specifically meets the needs of open root pipe welding and helps reduce training time and increases quality. Starts maintain root opening and prepared edge and stops limit arc marks outside of the heat-affected zone.



ArcReach Stick/TIG Remote  
Polarity Reversing

**Complete remote control.** The ArcReach® Stick/TIG Remote with Polarity Reversing provides all the same functionality of the XMT 350 FieldPro with Polarity Reversing hundreds of feet from the power source, including process changeover, and amperage adjustment with no special cables. Connect the ArcReach Stick/TIG Remote with Polarity Reversing in line with the electrode holder or TIG torch with standard welding cables and have *complete remote control*.



## ArcReach® SuitCase® 8 and 12 Features

**Setting the standard for performance.** Heavy-duty drive motor with tachometer control provides wire feed speed that is accurate and consistent from the start of the weld to the finish and from one weld to the next, which provides consistent arc quality. Wide voltage range for small and large wires with no contactor chatter or arc outages.

**Set volts and wire feed speed remotely.** The simple interface on the feeder allows operators to adjust parameters at the point of use with no control cords.

**Durable design reduces downtime.** Impact-resistant case and the elimination of feeder control cords provides a solid solution to last in harsh environments.



**Easy process changeover.** Simply connect the ArcReach SuitCase feeder to your weld lead and you are ready to go. The power source automatically switches settings to run conventional wire processes.

**Easy solution for traditional wire process.** Add the flux-cored capability of the XMT® 350 FieldPro™ for fill and cap passes for increased productivity.

**Weld with large diameter (3/32 in.) wire.** The ArcReach SuitCase 12 Heavy Duty model is specifically designed for applications using 3/32-inch wire.

## ArcReach SuitCase Specifications (Subject to change without notice.)

**CC CV DC** (Use with CC or CV, DC power sources.)

Model	Input Power	Input Welding Circuit Rating	Wire Feed Speed	Wire Type and Diameter Capacity	Max. Spool Size Capacity	Dimensions	Net Weight
8	Operates on open-circuit voltage and arc voltage: 14–48 VDC/110 max. OCV	330 A at 60% duty cycle	50–780 ipm (1.3–19.8 m/min.) dependent on arc voltage	<b>Solid wire:</b> .023–.052 in. (0.6–1.4 mm) <b>Flux-cored:</b> .030–5/64 in. (0.8–2.0 mm)	8 in. (203 mm) 14 lb. (6.4 kg)	H: 12.75 in. (324 mm) W: 7.25 in. (184 mm) D: 18 in. (457 mm)	28 lb. (13 kg)
12		425 A at 60% duty cycle		<b>Solid wire:</b> .023–.052 in. (0.6–1.4 mm) <b>Flux-cored:</b> .030–5/64 in. (0.8–2.0 mm)			
12 Heavy Duty		450 A at 60% duty cycle	30–400 ipm (1.76–10.2 m/min.) dependent on arc voltage	<b>Flux-cored:</b> .030–3/32 in. (0.8–2.4 mm)	12 in. (305 mm) 45 lb. (20 kg)	H: 15.5 in. (394 mm) W: 9 in. (229 mm) D: 21 in. (533 mm)	35 lb. (15.9 kg)

## ArcReach® Smart Feeder Features

**ArcReach Smart Feeder delivers excellent RMD® and pulsed MIG welding** up to 200 feet away from the power source with no control cords — twice the distance previously possible. RMD and pulsed MIG processes also help reduce weld failures and eliminate backing gas on some stainless and chrome-moly applications.

**Easy process changeover.** Simply connect the ArcReach Smart Feeder to your leads and you are ready to go. All controls automatically shift to the ArcReach Smart Feeder.



**Synergic processes.** RMD and pulsed MIG welding permits procedures with one wire and one gas to eliminate process switch-over time.

**Durable design reduces downtime.** Impact-resistant case and the elimination of feeder control cords provide a solid solution to last in harsh environments.

## ArcReach Smart Feeder Specifications (Subject to change without notice.)

**CC CV DC** (Use with ArcReach-equipped power sources.)

Input Power*	Input Welding Circuit Rating	Wire Feed Speed	Wire Diameter Capacity	Max. Spool Size Capacity	Dimensions	Net Weight
XMT 350 FieldPro connected to three-phase power or an ArcReach-equipped engine drive	275 A at 60% duty cycle	50–500 ipm (1.3–12.7 m/min.) dependent on arc voltage	.035–.045 in. (0.9–1.1 mm)	12 in. (305 mm), 33 lb. (15 kg)	H: 18 in. (457 mm) W: 13 in. (330 mm) D: 21.5 in. (546 mm)	50 lb. (23 kg)

\*XMT 350 FieldPro must be connected to three-phase power when using the ArcReach Smart Feeder. Using single-phase may cause the feeder to unpredictably interrupt welding.

# ArcReach® Heater Features

**Take charge of your field preheat and bakeout applications up to 600 degrees Fahrenheit (315°C).**

As part of the ArcReach technology platform, the heater is an accessory for select ArcReach welding power sources.

The induction heating tools (air-cooled cables or air-cooled quick wraps) connect to the ArcReach Heater, which is powered by select on-site welding power sources.



**Air-cooled cable**



**Air-cooled quick wrap**



## ArcReach Heater systems allow economical, insourced weld preheating and bakeout

**With ArcReach Heater systems you can:**

- Eliminate the costly overruns common with heating contractors
- Eliminate delays due to transitions between heating and welding crews
- Run your own schedule without depending on third-party contractors
- Use existing on-site welding equipment up to 200 feet away as the heating power source
- Lower preheating and bakeout costs
- Automatically and accurately document joint temperatures
- Eliminate safety concerns caused by traditional resistance and open-flame heating

The ArcReach Heater air-cooled induction heating system is specifically designed for preheating and bakeout applications up to 600 degrees Fahrenheit (315°C), without the need for a cooler and coolant. Preheat and bakeout programs can be manually entered or loaded via USB drive. Heating data is automatically recorded and can be used in quality control and documentation needs.

The air-cooled cables and quick wraps are manufactured from durable high-temperature materials, and designed to withstand the tough conditions in both industrial and construction applications.

## Induction benefits

**Easy setup** with flexibility to fit a variety of pipe diameters, plates or odd geometries.

**Time-to-temperature** is faster than conventional processes due to the method of applying heat, reducing cycle time.


**Uniform heating** is maintained along and through the heat zone by using induction heat within the material. The surface of the part is not marred by localized conducted heat at higher than specified temperatures.

**Improved working environment** during welding. Welders are not exposed to open flames, explosive gases and hot elements associated with fuel gas heating and resistance heating.

# ArcReach Heater Specifications (Subject to change without notice.)

Input Power	Ambient Temperature Range		Rated Output	Dimensions	Net Weight
	Storage	Usage			
Operates on open-circuit voltage: 50–70 V	-4–131°F (-20–55°C)	14–104°F (-10–40°C)	7.8 kW at 100% duty cycle	H: 18.6 in (472 mm) W: 11.2 in (285 mm) D: 26.7 in (678 mm)	43 lb. (20 kg) <b>CSA</b> 50.5 lb. (23.4 kg) <b>CE</b>

 Certified by Canadian Standards Association to both the Canadian and U.S. Standards.

 Manufactured and certified in accordance with IEC-60974-1, -10.

# XMT<sup>®</sup> 350 FieldPro<sup>™</sup> and XMT 350 FieldPro with Polarity Reversing Packages

## Stick/TIG system

**951736** With XMT 350 FieldPro power source and ArcReach<sup>®</sup> Stick/TIG Remote

**951737** With XMT 350 FieldPro with Polarity Reversing power source and ArcReach<sup>®</sup> Stick/TIG Remote with Polarity Reversing

- Remotely change process
- Set actual amperage

### Additional features of XMT 350 FieldPro with Polarity Reversing power source system

- Remotely change polarity
- No need to swap weld cables
- Detects improper connection



## MIG/flux-cored system

**951734** With XMT 350 FieldPro power source

**951735** With XMT 350 FieldPro with Polarity Reversing power source

MIG/flux-cored system includes power source, ArcReach<sup>®</sup> SuitCase 12 feeder with drive rolls and Bernard<sup>®</sup> BTB Gun 300 A.

- No feeder control cords
- Eliminates trips back to power source
- Total remote control
- Automatically changes to CV output when feeder is connected



## RMD<sup>®</sup>/pulse system

**951738** With XMT 350 FieldPro power source

**951739** With XMT 350 FieldPro with Polarity Reversing power source

RMD/pulse system includes power source, ArcReach<sup>®</sup> Smart Feeder with drive rolls and Bernard<sup>®</sup> PipeWorx 300-15 MIG gun.

- Offers traditional MIG and flux-cored processes, as well as advanced RMD and pulse programs.
- Weld up to 200 feet away from the power source with no special cables
- Save welding parameters for later use on SD memory card
- Complete remote control at the weld joint



## Ordering Information Most popular models ◀

XMT 350 FieldPro Packages	Stock No.	Description	Qty.	Price
<b>XMT® 350 FieldPro™ Stick/TIG System</b>	<b>951736</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro power source and ArcReach Stick/TIG Remote		
<b>XMT® 350 FieldPro™ MIG/Flux-Cored System</b>	<b>951734 ◀</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro power source, ArcReach SuitCase 12 feeder with drive rolls and Bernard BTB Gun 300 A		
<b>XMT® 350 FieldPro™ RMD®/Pulse System</b>	<b>951738</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro power source, ArcReach Smart Feeder with drive rolls and Bernard PipeWorx 300-15 MIG gun		
<b>XMT® 350 FieldPro™ with Polarity Reversing Stick/TIG System</b>	<b>951737</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro with Polarity Reversing power source and ArcReach Stick/TIG Remote with Polarity Reversing		
<b>XMT® 350 FieldPro™ with Polarity Reversing MIG/Flux-Cored System</b>	<b>951735</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro with Polarity Reversing power source, ArcReach SuitCase 12 feeder with drive rolls and Bernard BTB Gun 300 A		
<b>XMT® 350 FieldPro™ with Polarity Reversing RMD®/Pulse System</b>	<b>951739 ◀</b>	208–575 V, Tweco®-style connectors, includes XMT 350 FieldPro with Polarity Reversing power source, ArcReach Smart Feeder with drive rolls and Bernard PipeWorx 300-15 MIG gun		
<b>XMT 350 FieldPro Racks</b>				
XMT 350 FieldPro™ 4-Pack Rack	<b>907739</b>	Fused 460/575 V, 50/60 Hz, Tweco-style connectors		
XMT 350 FieldPro™ 6-Pack Rack	<b>907740</b>	Fused 460/575 V, 50/60 Hz, Tweco-style connectors		
XMT 350 FieldPro™ with Polarity Reversing 4-Pack Rack	<b>907742</b>	Fused 460/575 V, 50/60 Hz, Tweco-style connectors		
XMT 350 FieldPro™ with Polarity Reversing 6-Pack Rack	<b>907741</b>	Fused 460/575 V, 50/60 Hz, Tweco-style connectors		
<b>System Components</b>				
<b>XMT 350 FieldPro™ Power Source</b>	<b>907730 ◀</b> <b>907730002</b>	208–575 V, 50/60 Hz, Tweco-style connectors 208–575 V, 50/60 Hz, Dinse-style connectors		
<b>XMT 350 FieldPro™ with Polarity Reversing Power Source</b>	<b>907731 ◀</b> <b>907731001</b>	208–575 V, 50/60 Hz, Tweco-style connectors 208–575 V, 50/60 Hz, Dinse-style connectors		
ArcReach® SuitCase® 12 MIG/FCAW Feeder	<b>951729</b> <b>951730</b> <b>951731</b> <b>951732</b>	Tweco-style connectors, with drive rolls and Bernard BTB Gun 300 A Tweco-style connectors, with drive rolls and Bernard S-Gun Tweco-style connectors, with drive rolls and Bernard Dura-Flux™ gun Tweco-style connectors, with drive rolls and Bernard PipeWorx 300-15 MIG gun		
ArcReach® SuitCase® 8 MIG/FCAW Feeder	<b>951726</b> <b>951727</b> <b>951728</b>	Tweco-style connectors, with drive rolls and Bernard BTB Gun 300 A Tweco-style connectors, with drive rolls and Bernard S-Gun Tweco-style connectors, with drive rolls and Bernard Dura-Flux™ gun		
ArcReach® Smart Feeder MIG/FCAW/RMD®/Pulse Feeder	<b>951733</b> <b>300935</b> <b>300935001</b>	Tweco-style connectors, with drive rolls and Bernard PipeWorx 300-15 MIG gun Tweco-style connectors Dinse-style connectors		
ArcReach® Stick/TIG Remote	<b>301325</b>	Tweco-style connectors		
ArcReach® Stick/TIG Remote Polarity Reversing	<b>300934</b>	Tweco-style connectors		
ArcReach® Heater		See literature IN/16.0		
<b>Accessories</b>				
Bernard® PipeWorx 250-15 MIG Gun	<b>195399</b>	15 ft. (4.6 m), 250 A air-cooled MIG gun designed for use with all ArcReach smart systems		
Bernard® PipeWorx 300-15 MIG Gun	<b>195400</b>	15 ft. (4.6 m), 300 A air-cooled MIG gun designed for use with all ArcReach smart systems		
Gas Valve Kit	<b>195286</b>	For XMT 350 FieldPro power source (not compatible with polarity reversing model)		
ArcReach® Feeder Gas Flow Meter Kit	<b>301306</b>	For ArcReach SuitCase 8/12 feeders and ArcReach Smart Feeder		

Date:

Total Quoted Price:

Distributed by:

