

Material Name: ISOBUTANE SDS ID: 00232333

## Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name** 

**ISOBUTANE** 

**Synonyms** 

MTG MSDS 55; 2-METHYL PROPANE; TRIMETHYL METHANE; UN 1969; C4H10

**Chemical Family** 

Hydrocarbons, aliphatic

**Product Description** 

Classification determined in accordance with Compressed Gas Association standards.

**Product Use** 

Industrial and Specialty Gas Applications.

**Restrictions on Use** 

None known.

Details of the supplier of the safety data sheet

SPECIALTY CHEMICAL PRODUCTS

1407 Pennsylvania Ave. South Houston, TX 77587

General Information: 713-944-0900

Emergency #: 1-800-424-9300 (CHEMTREC) Outside the US: 1-703-527-3887 (Call collect)

## **Section 2 - HAZARDS IDENTIFICATION**

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Gases - Category 1 Gases Under Pressure - Liquefied gas

**GHS Label Elements** 

Symbol(s)





#### Signal Word

Danger

#### Hazard Statement(s)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

**Precautionary Statement(s)** 

Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Storage

Protect from sunlight. Store in a well-ventilated place.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Page 1 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

#### Other Hazards

Frostbite may occur from contact with liquefied gas.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS						
CAS	Percent					
75-28-5	ISOBUTANE	100				

#### **Section 4 - FIRST AID MEASURES**

#### Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

#### Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115°F; 41-46°C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

#### **Eves**

Contact with liquid: Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

#### **Ingestion**

If swallowed, get medical attention.

#### **Most Important Symptoms/Effects**

#### Acute

frostbite

#### **Delayed**

No information on significant adverse effects.

#### Indication of any immediate medical attention and special treatment needed

For inhalation, consider oxygen.

# **Section 5 - FIRE FIGHTING MEASURES**

## **Extinguishing Media**

#### **Suitable Extinguishing Media**

carbon dioxide, regular dry chemical, Large fires: Flood with fine water spray.

#### **Unsuitable Extinguishing Media**

Do not scatter spilled material with high-pressure water streams.

#### **Special Hazards Arising from the Chemical**

Extremely flammable gas. Severe fire hazard. Vapor/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back.

#### **Hazardous Combustion Products**

oxides of carbon

#### **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 1600 meters (1 mile). Stop flow of gas.

Page 2 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

# **Special Protective Equipment and Precautions for Firefighters**

Wear personal protective clothing and equipment such as self-contained breathing apparatus (SCBA) for protection against possible exposure.

## Section 6 - ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

# Methods and Materials for Containment and Cleaning Up

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove all sources of ignition. Ventilate closed spaces before entering. Damaged cylinders should be handled only by specialists.

#### **Environmental Precautions**

Avoid release to the environment.

## **Section 7 - HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product.

## Conditions for Safe Storage, Including any Incompatibilities

Protect from sunlight. Store in a well-ventilated place.

Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Keep separated from incompatible substances.

#### **Incompatible Materials**

oxidizing materials

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Component Exposure Limits** 

ISOBUTANE	75-28-5						
ACGIH:	1000 ppm STEL (explosion hazard )						
NIOSH:	800 ppm TWA ; 1900 mg/m3 TWA						
Mexico:	1000 ppm TWA [VLE-PPT ]						

## ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

## **Engineering Controls**

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

#### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Page 3 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

**Skin Protection** 

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing. **Respiratory Protection** 

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA. 2000 ppm. Any supplied-air respirator. Any self-contained breathing apparatus with a full facepiece. Emergency or planned entry into unknown concentrations or IDLH conditions -. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode. Escape -. Any appropriate escape-type, self-contained breathing apparatus. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

#### **Glove Recommendations**

Wear insulated gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES								
Appearance	colorless gas	Physical State	gas					
Odor	petroleum odor	Color	colorless					
Odor Threshold	Not available	рН	Not available					
Melting Point	-159 °C (-254 °F )	<b>Boiling Point</b>	-12 °C (10 °F)					
<b>Boiling Point Range</b>	Not available	Freezing point	Not available					
Evaporation Rate	Not available	Flammability (solid, gas)	Flammable gas					
Autoignition Temperature	460 °C (860 °F)	Flash Point	-88 °C Closed Cup (-126 °F)					
Lower Explosive Limit	1.8 %	<b>Decomposition temperature</b>	Not available					
<b>Upper Explosive Limit</b>	8.4 %	Vapor Pressure	3.1 Atm @ 21 °C					
Vapor Density (air=1)	2	Specific Gravity (water=1)	0.549 at 20 °C					
Water Solubility	(Slightly soluble	Partition coefficient: n-octanol/water	Not available					
Viscosity	0.0077 cp	Kinematic viscosity	Not available					
Solubility (Other)	Not available	Density	Not available					
Physical Form	Liquefied gas	Molecular Formula	C4-H10					
Molecular Weight	58.12							

Page 4 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

**Solvent Solubility** 

**Soluble** 

alcohol, ether, chloroform

## **Section 10 - STABILITY AND REACTIVITY**

## Reactivity

No reactivity hazard is expected.

## **Chemical Stability**

Stable at normal temperatures and pressure.

## **Possibility of Hazardous Reactions**

Will not polymerize.

## **Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

#### **Incompatible Materials**

oxidizing materials

#### Hazardous decomposition products

Oxides of carbon

## **Section 11 - TOXICOLOGICAL INFORMATION**

## **Information on Likely Routes of Exposure**

#### Inhalation

irritation, nausea, vomiting, headache, symptoms of drunkenness, suffocation, convulsions, coma

#### **Skin Contact**

blisters, frostbite

#### **Eye Contact**

frostbite, blurred vision

#### **Ingestion**

frostbite

## **Acute and Chronic Toxicity**

# Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

# **ISOBUTANE** (75-28-5)

Inhalation LC50 Rat 658 mg/L 4 h

#### **Product Toxicity Data**

## **Acute Toxicity Estimate**

No data available.

#### **Immediate Effects**

frostbite

## **Delayed Effects**

No information on significant adverse effects.

#### **Irritation/Corrosivity Data**

No data available.

## **Respiratory Sensitization**

No data available.

## **Dermal Sensitization**

No data available.

## **Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Page 5 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

**Germ Cell Mutagenicity** 

No data available.

**Tumorigenic Data** 

No data available

Reproductive Toxicity

No data available.

**Specific Target Organ Toxicity - Single Exposure** 

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

**Aspiration hazard** 

No data available.

**Medical Conditions Aggravated by Exposure** 

No data available. **Additional Data** 

Stimulants such as epinephrine may induce ventricular fibrillation.

## **Section 12 - ECOLOGICAL INFORMATION**

## **Component Analysis - Aquatic Toxicity**

No LOLI ecotoxicity data are available for this product's components.

Persistence and Degradability

No data available.

**Bioaccumulative Potential** 

No data available.

**Mobility** 

No data available.

## **Section 13 - DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Dispose in accordance with all applicable regulations.

## **Component Waste Numbers**

The U.S. EPA has not published waste numbers for this product's components.

## **Section 14 - TRANSPORT INFORMATION**

**US DOT Information:** 

**Shipping Name: ISOBUTANE** 

Hazard Class: 2.1 UN/NA #: UN1969 Required Label(s): 2.1

**TDG Information:** 

**Shipping Name:** ISOBUTANE

Hazard Class: 2.1 UN#: UN1969 Required Label(s): 2.1

**International Bulk Chemical Code** 

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in

bulk.

Page 6 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11



Material Name: ISOBUTANE SDS ID: 00232333

## **Section 15 - REGULATORY INFORMATION**

#### U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

## SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Gas Under Pressure

#### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
ISOBUTANE	75-28-5	No	Yes	No	Yes	Yes

## California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

## **Component Analysis - Inventory**

## **ISOBUTANE (75-28-5)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

KR - REACH CCA	MX NZ		PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

#### **Section 16 - OTHER INFORMATION**

#### **NFPA Ratings**

Health: 0 Fire: 4 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes Updated: 10/09/2017 **Key / Legend** 

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -

California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea

Page 7 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11

Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea



Material Name: ISOBUTANE SDS ID: 00232333

Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA - Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts<sup>TM</sup> - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; Ne- Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL – Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL-Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TH-TECI - Thailand - FDA Existing Chemicals Inventory (TECI); TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

#### **Other Information**

#### **Disclaimer:**

Specialty Chemical Products makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Specialty Chemical Products shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

Page 8 of 8 Issue date: 2020-07-11 Revision 5.0 Print date: 2020-07-11