

KS 18 LTX 57 (601857890) 6 1/2" Cordless circular saw 18V; Cardboard box

Order no. 601857890 EAN 4007430327352



Representative picture



- High-torque, lightweight cordless circular saw for universal construction site use
- Aluminum base plate can be used directly on guide rails by Metabo and other manufacturers
- Brake area stops the saw blade quickly and improves safety
- Precisely angled bevel cuts up to 50°, with practical snap-in point at 45°
- 0° position re-adjustable for highest cutting precision
- Clearly visible cutting indicator for precise sawing after initial cut
- Handle with non-slip soft-grip surface for secure guidance
- Extraction possibility by connecting an all-purpose vacuum cleaner
- Battery packs with capacity display for checking the charge status
- Ultra-M Technology: highest power, gentle charging, and 3 year warranty on the battery pack

www.metabo.com 1/2



Technical values	
Parameters	
Battery voltage	18 V
Swivel range from / to:	0 / + 50 °
Adjustable cutting depth	0 - 2 1/4 "
Maximum cutting depth at 90°	2 1/4 "
Maximum cutting depth at 45°	1 11/16 "
Saw blade Ø x bore	6 1/2 x 5/8 "
No-load speed	4600 RPM
Max. cutting speed	129 ft/min
Weight (including battery pack)	7.5 lbs
Vibration	
Sawing particle board	2.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Carbide circular saw blade (18 teeth)

Parallel guide / rip fence

Hexagonal wrench

MetaLoc case insert

without battery pack, without charger

www.metabo.com 2 / 2