

BS 18 LTX-3 BL Q I (602355620) Cordless Drill / Screwdriver
18V 2x5.5Ah LiHD; Charger ASC 30-36 V; Plastic Carry Case

Order no. 602355620
EAN 4007430313539



Representative picture



- Brushless 3-speed drill/screwdriver with maximum power for demanding applications
- 3 speeds with high speed (max. 3,800/min) for expanded range of use and even faster drilling progress
- Metabo "Quick" System: Quick change of tool holder and bits, ideal for fast and convenient change of applications
- Selectable "impulse" mode for removal of damaged screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: Electronic torque control with increased precision for accurate and intricate working
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminum gear housing for optimum heat dissipation and durability
- With handy belt hook and bit holder, can be fixed either on the right or left side
- LiHD Battery Pack for ultimate power, extremely long run time and service life
- Battery packs with capacity display for checking the charge status
- Ultra-M Technology: highest power, gentle charging, and 3 year warranty on the battery pack

Technical values

Parameters

| | |
|---------------------------------|-----------------------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery capacity | 2 x 5.5 Ah |
| Maximum torque - soft | 531 in-lbs |
| Pulse torque | 48 ft. lbs |
| Maximum torque, hard | 1062 in-lbs |
| Adjustable torque | 9 - 177 in-lbs |
| Max. capacity in steel | 1/2 " |
| Max. capacity in soft wood | 2 1/2 " |
| No-load speed | 0 - 500 / 0 - 2050 / 0 - 3800 RPM |
| Chuck capacity | 1/16 - 1/2 " |
| Weight (including battery pack) | 5.7 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Drilling in metal | 3.8 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 71 dB(A) |
| Sound power level (LWA) | 82 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Quick-change chuck
Quick-change system
Side Handle
Belt hook with bit case
2 LiHD Battery Packs (18 V/5.5 Ah)
Charger ASC 30-36 V "AIR COOLED"