

## WEV 15-125 HT (US600562800) Angle Grinder Cardboard box; with variable speed

Order no. US600562800 EAN 662911562802



Representative picture











- · Optimum processing of stone: robust, powerful angle grinder with gear reduction and reduced, adjustable speed for material-friendly working
- New, patent-pending Metabo Long-life motor with up to 50% more torque and up to 20% higher overload capacity for quicker material removal and longer service life
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with thumbwheel: for work with materials requiring customised speeds, which remain constant under load
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted when rotated in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values	
Parameters	
Amps	13.5 AMPS
Disc diameter	5 "
Rated input power	1550 W
Output power	900 W
No-load speed	2800 - 9600 RPM
Speed at rated load	9600 RPM
Torque	37 in-lbs
Spindle thread	5/8" - 11 UNC
Grip circumference	8 1/8 "
Weight (without power cable)	5.5 lbs
Cable length	8 ft
Vibration	
Surface grinding	5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s²
Polishing	2.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	4 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	93 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Cardboard box, 5" shroud

www.metabo.com 2/2