COMPACT AND POWERFUL

Magnum® PRO 175L Welding Gun



KEY FEATURES

The Magnum PRO 175L welding gun is a compact and powerful addition to the Magnum PRO L-series family. It is ideal for home, farm, and small shop projects, as well as auto body work and maintenance and repair applications.

- Premium Tip Performance The large mass of the Magnum PRO Copper Plus®
 contact tips help disperse heat, keeping tips cooler and expanding their life. The
 Anti-Seize™ threads prevent tips from seizing in the diffuser.
- Comfortable Grip The lightweight curved handle with soft rubber over molding enhances comfort and allows for an easier grip of the gun.
- 100% Duty Cycle The 175L runs at 100% duty cycle using mixed gas, helping it withstand tough jobs.

Process »

MIG, Pulsed MIG, Flux-Cored

Product Number »

K4529-1

K4872-1

See compatibility charts on pages 2-3

What's Included »

- » Contact Tips
 - KP2744-025T (Qty 1)
 - KP2744-035T (Qty 1)
- » 0.5 in. (12.7 mm) Thread-On Gas Nozzle Flush (KP3075-1-50F)
- » Gas Diffuser (KP3076-1)
- » Gun Liner (KP35-40-15)
- » Integrated Gun Connector



OVER-MOLDED HANDLE

The over-molded handle design offers key benefits to the operator:

- · Increased Comfort
- Enhanced Grip
- Reduced Hand Fatigue
- Improved Control



MAGNUM PRO EXPENDABLES

Lincoln Electric's long-lasting Magnum PRO expendables are designed with welding arc performance in mind. Using Magnum PRO expendables result in more time welding and less time wasted.

Copper Plus Technology

With a larger diameter to disperse heat and keep tips cooler

Anti-Seize Threads

To prevent the contact tips from melting, fusing, and seizing in the diffuser



Easy to Clean

Nickel plating keeps spatter from sticking to the nozzle

Easy to Unscrew

With coarse threads that prevent seizing

MACHINE COMPATIBILITY

Gun		Compatible Machines			
Magnum PRO 100L [4-pin] K4528-1	POWER MIG® 140C K2471-2	POWER MIG 180C K2473-2	POWER MIG 180 Dual K3018-2		
Magnum PRO 100L (8-pin) K4528-1-8P	POWER MIG 140 MP® K4498-1				
Magnum PRO 175L K4529-1	POWER MIG 210 MP K3963-1				
Magnum PRO 250L K4530-2	POWER MIG 256 K3068-1/K3068-2	POWER MIG 260 K3520-1			
Magnum DDO 2501	LE 72TM LE 74TM Corios Floy Food	® 74 HT Floy Food 94 N_25 DDO® N_25	SV® Active® ActiveV®		

Magnum PRO 250L (K466-10) K4874-2

LF-72™, LF-74™ Series, Flex Feed® 74 HT, Flex Feed 84, LN-25 PRO®, LN-25X®, Activ88®, Activ8X® Power Feed® 10, 10M, 25M, and 84

MILLER® MACHINE COMPATIBILITY

Gun	Compatible Machines	Direct Replacement For	
Magnum PRO 100L K4871-1	Millermatic® 141 and 211	MDX™-100 M-100	
Magnum PRO 175L K4872-1	Multimatic® 215 and 220 AC/DC	MDX-100 M-150	
Magnum PRO 250L K4873-2	Millermatic 212 Auto-set, 252 and 255 Multimatic 200 and 255	MDX-250 MDX-250 EZ-Select™	

CONTACT TIPS

Wire Diameter	Tapered Tip			
in (mm)	Pkg. Qty10	Pkg. Qty100		
0.025 (0.6)	KP2744-025T	KP2744-025T-B100		
0.030 (0.8)	KP2744-030T	KP2744-030T-B100		
0.035 (0.9)	KP2744-035T	KP2744-035T-B100		
0.040 (1.0)	KP2744-040T	KP2744-040T-B100		
0.045 (1.1)	KP2744-045T	KP2744-045T-B100		

GAS DIFFUSER **GASLESS NOZZLE GUN TUBE**

Pkg. Qty.	Part Number	Pkg. Qty.	Part Number	Degree	Part Number
1	KP3076-1	1	KP3084-1	60	KP4087-1
25	KP3076-1-B25	25	KP3084-1-B25		I

GAS NOZZLE¹

		Gas Nozzle Diameter			
Nozzle	Pkg. Qty.	0.375 in (9.5 mm)	0.5 in (12.7 mm)		
51. 1	1	KP3075-1-38F	KP3075-1-50F		
Flush	25	KP3075-1-38F-B25	KP3075-1-50F-B25		
1/4 in (6.4 mm) Stickout	1	KP3075-1-38S	KP3075-1-50S		
	25	KP3075-1-38S-B25	KP3075-1-50S-B25		

GUN LINER

	Cable Length	Pkg Qty	Steel 0.023-0.035 in (0.6-0.9 mm)	Steel 0.035-0.045 in (0.9-1.2 mm)	Aluminum 0.035 in (0.9 mm)
	45 (1 (4 5)	1	KP35-40-15 ³	KP45-40-15	KP1959-1 ²
15 ft (4.5 m)	10	KP35-40-15-B10	KP45-40-15-B10	<u>-</u>	

PRODUCT SPECIFICATIONS

Product Name	Product Number	Amperage Rating 100% Duty Cycle	Wire Diameter Ranger in (mm)	Cable Length ft (m)	Pin Connection
Magnum DDO 1751	K4529-1	- 175A	0.025- 0.045 (0.6- 1.2)	10 (3.0)	POWER MIG 210 MP
Magnum PRO 175L	K4872-1				Miller Compatible

⁽¹⁾ When using nozzle sizes less than 5/8 in. (15.9 mm), tapered tips are recommended.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company* is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change - This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

Recommended for aluminum wire welding, recommended maximum cable length for aluminum is 10 ft. (3.0 m)

³ Standard on Magnum PRO 175L