



## Vertical Wall Mount Brackets

### Description

Vertical Wall Mount Brackets allow servers and other networking equipment to mount vertically and flush to a wall, providing a cost-effective mounting solution for environments with limited space. These RoHS Compliant brackets feature universal cage hole mounting and an opening in the rear panel for in-wall cable access. These brackets have the versatility to support a wide variety of equipment regardless of depth.

### Features

- Space-saving vertical wall mount design
- Strong 14-gauge steel with black powder coating
- Universal fit with cage hole mounting
- Cable access through rear panel opening
- Includes hardware (10 M6 cage nuts and screws)

### Spec Information

**Product Type:** Wall Mount Bracket

**Material:** 14 Gauge Cold Rolled Steel

**Finish:** Black Powder Coated

**Loading Capacity:** 75 Lbs.

**Dimensions (HxWxD):** Varies By Item #

**Unit Weight:** Varies By Item #

**Rack Unit Quantity:** 2U, 4U or 6U

**Hardware:** 10 pcs M6 Cage Nuts

And Screws Included

**Compliance & Standards:** RoHS, ANSI / EIA RS-310D, IEC60297-2, DIN41494; Part 1, DIN41494; Part 7

**Quantity Per Package:** Sold Individually

**Carton Dimensions (HxWxD):**

Varies By Item #

**Carton Weight:** Varies By Item #



Description						
Item #	Rack Units	Loading Capacity	Unit Dims (HxWxD)	Unit Weight	Carton Dims (HxWxD)	Carton Weight
VB2-021	2U	75 Lbs.	7.80" X 19.23" X 4.20"	4.60 Lbs.	20.25" X 9.5" X 3"	5.35 Lbs.
VB2-041	4U	75 Lbs.	7.80" X 19.23" X 7.70"	5.90 Lbs.	20.25" X 9.5" X 3"	6.75 Lbs.
VB2-061	6U	75 Lbs.	7.80" X 19.23" X 11.20"	9.65 Lbs.	20.25" X 13" X 3"	10.70 Lbs.

©2025 CRN Solutions Inc. dba. Primus Cable

All Rights Reserved.

Although Primus Cable makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Primus Cable provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Primus Cable be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Primus Cable has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Primus Cable products are subject to Primus Cable's standard terms and conditions of sale.

Primus Cable believes this product to be in compliance with EU RoHS (Directive 2002/EC, 27 Jan. 2003). Material manufactured prior to the compliance date may be in stock at Primus Cable facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Primus Cable's knowledge, information, and belief at the date any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification and regulations based on their individual usage of the product.

Primus Cable declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC

**PrimusCable.com - (951) 824-1571**