METHYL ETHYL KETONE 99.7% ACS

Page: 1

Compilation date: 12/11/2021

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: METHYL ETHYL KETONE 99.7% ACS

CAS number: 78-93-3
EINECS number: 201-159-0
Product code: GPS8969

Synonyms: 2-BUTANONE

MEK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

1.3. Details of the supplier of the safety data sheet

Company name: ZOIC PalaeoTech

Orchard House Longburton Sherborne DT9 5PH

Tel: 01963 210308

Email: info@zoicpalaeotech.co.uk

1.4. Emergency telephone number

Emergency tel: 999

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066

Classification under CHIP: F: R11; Xi: R36; -: R66; -: R67

Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause

drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

METHYL ETHYL KETONE 99.7% ACS

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Precautionary statements: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+378: In case of fire: Use dry powder or dry sand for extinction.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

Other hazards: This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: METHYL ETHYL KETONE 99.7% ACS

CAS number: 78-93-3 **EINECS number:** 201-159-0

Contains: Molecular Formula: C4H8O

Molecular Weight: 72.11 g/mol

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Wash

out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for

breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: There may be irritation and redness.

Ingestion: No data available.Inhalation: No data available.

Delayed / immediate effects: No data available.

METHYL ETHYL KETONE 99.7% ACS

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flash back possible over considerable distance., Container explosion may occur under

fire conditions.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure

adequate ventilation. Eliminate all sources of ignition. Evacuate the area immediately.

Beware of vapours accumulating to form explosive concentrations. Vapours can

accumulate in low areas. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain spillage, and then collect with an electrically protected vacuum cleaner or by

wet-brushing and place in container for disposal according to local regulations (see

section 13).

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up

of electrostatic charge.

For precautions see section 2.2.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store under inert gas. Moisture sensitive. Store in cool, well ventilated area. Keep

container tightly closed. Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Hygroscopic. Store under nitrogen.

METHYL ETHYL KETONE 99.7% ACS

Page: 4

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	600 mg/m3	900 mg/m3	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 292 min

Eye protection: Face-shield. Safety glasses. Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Impervious clothing. Flame retardant antistatic protective clothing. The type of protective

equipment must be selected according to the concentration and amount of the

dangerous substance at the specific workplace.

Environmental: Do not let product enter drains. Prevent from entering in public sewers or the immediate

environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Boiling point/range°C: 80 Melting point/range°C: -87

Flammability limits %: lower: 1.8 upper: 10.1

Flash point°C: -3 Part.coeff. n-octanol/water: log Pow: 0.29

Vapour pressure: 95 hPa at 20 °C Relative density: 0.805 g/mL at 25 °C

METHYL ETHYL KETONE 99.7% ACS

Page: 5

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Moist air. Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	2,737	mg/kg
INHALATION	MUS	4H LC50	32,000	mg/m3
DERMAL	RBT	LD50	6,480	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis	
Serious eye damage/irritation	OPT	Based on test data	
STOT-single exposure	-	Based on test data	

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: There may be irritation and redness.

Ingestion: No data available.Inhalation: No data available.

METHYL ETHYL KETONE 99.7% ACS

Page: 6

Delayed / immediate effects: No data available. **Other information:** Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H ErC50	400	mg/l
DAPHNIA	48H EC50	> 520	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra

care in igniting as this material is highly flammable. Offer surplus and non-recyclable

solutions to a licensed disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1193

14.2. UN proper shipping name

Shipping name: ADR/RID: ETHYL METHYL KETONE

IMDG: ETHYL METHYL KETONE

IATA: Ethyl methyl ketone

METHYL ETHYL KETONE 99.7% ACS

Page: 7

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 2

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This safety datasheet complies with the requirements of Regulation (EC) No.

1907/2006.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.