1. Interpret dimensions and tolerances per ASME Y14.5-2009. Third-angle projection is used to project drawing views
2. For complete product definition, use this drawing in conjuction with associated model. CAD geometry is basic
3. Single-segment feature control frames (FCFs) and the upper segment of composite FCFs apply simultaneously
4. FCF segments denoted by a letter-in-triangle (example: Z) apply simultaneously with FCF segments denoted by the same letter-in-triangle
5. Default surface roughness: Ra shall not exceed 4% of the form requirement. ASME B46.1-2009 Table 3-2 specifies cutoff values
6. Dimensions are given in millimeters. Default tolerances: ⌖ ∅0.1 Ⓜ for screw threads. ⌓ 0.2 for surfaces

REVISION HISTORY		
REV	DCN	DATE
00		2020-06-05

SECTION A-A

creativecommons.org/licenses/by/4.0
BY SA

Slice Engineering®

SLICE ENGINEERING, LLC • GAINESVILLE, FLORIDA • SLICEENGINEERING.COM

MATERIAL	DESCRIPTION	
UNS C18150 - TEMPER TH04	HEAT BREAK SHANK C-PRO MAX	
FINISH: NATURAL	ITEM NUMBER: COP-P036	REV: 00
COPYRIGHT © 2019 SLICE ENGINEERING LLC THIS DRAWING IS PROTECTED BY UNITED STATES AND INTERNATIONAL COPYRIGHT LAWS	CREATED BY: C.M. MONTGOMERY	SHEET: 1/1

PRINTED ON: 2020-08-19