

Pico-2CH-RS485

This is a 2-Channel RS485 module for Raspberry Pi Pico, SP3485 transceiver, UART To RS485


Features

- Standard Raspberry Pi Pico header supports Raspberry Pi Pico series
- Using UART bus, easily converting UART to RS485 or vice versa

Specification

- Operating voltage: 3.3V
- Communication bus: UART
- RS485 transceiver: SP3485
- Baudrate: 300~500000bps

Pinout



GP0	1	40	VBUS
GP1	2	39	VSYS
GND	3	38	GND
GP2	4	37	3V3_EN
GP3	5	36	3V3(OUT)
GP4	6	35	ADC_VREF
GP5	7	34	GP28
GND	8	33	GND
GP6	9	32	GP27
GP7	10	31	GP26
GP8	11	30	RUN
GP9	12	29	GP22
GND	13	28	GND
GP10	14	27	GP21
GP11	15	26	GP20
GP12	16	25	GP19
GP13	17	24	GP18
GND	18	23	GND
GP14	19	22	GP17
GP15	20	21	GP16

3V3(OUT)	Power supply	
GND	Ground	
GP0	TXD0	UART TX
GP1	RXD0	UART RX
GP4	TXD1	UART TX
GP5	RXD1	UART RX

Hardware connection

When connecting PICO, please pay attention not to connect in the opposite direction. The direction can be judged by observing the USB screen printing end of the module and the USB interface end of the Pico (also can be judged by the pin label of the platoon master on the module and the pin label of the Pico).


You can also wire it according to the table below

RS485	Pico	Description
VCC	VSYS	Power input
GND	GND	Ground

TX_CH0	GP0	UART transmit pin
RX_CH0	GP1	UART receive pin
TX_CH1	GP4	UART transmit pin
RX_CH1	GP5	UART receive pin

Connection

The connection of the RS485 board is same as the Pico-2CH-RS232



Setup environment

To setup the Pico for working, please refer to the official guide: <https://www.raspberrypi.org/documentation/pico/getting-started/>

Download example

Open a terminal and run the follow command

```
sudo apt-get install p7zip-full
cd ~
sudo wget https://www.waveshare.com/w/upload/9/94/Pico_2CH_RS485.7z
7z x Pico_2CH_RS485.7z -o./Pico_2CH_RS485
cd ~/Pico_2CH_RS485
```

```
cd c/build/
```

Run the examples

C codes

- Go the example directory and build it

```
cd ~/Pico_2CH_RS485/c/
```

Create the build folder and add SDK path to it:

By default, the ../../pico-sdk is the path of SDK

We have created the build folder in examples, you can just enter it.

Note: If the actual path of your Pi is different, you need to write the correct path.

```
cd build
export PICO_SDK_PATH=../../pico-sdk
```

Run the cmake to generate Makefile file

```
cmake ..
```

Run the make command to build the codes and generate an executable file.

```
make -j9
```


After building, an uf2 file is generated. Press and hold the key on the Pico board to connect the Pico to the Raspberry Pi's USB port via the Micro USB cable, then release the key. Once connected, Raspberry will automatically recognize a removable disk (RPI-RP2). Copy the file main.uf2 in the corresponding folder to the recognized removable disk (RPI-RP2).

```
cp main.uf2 /media/pi/RPI-RP2/
```

Python codes

Run in Raspberry Pi

- Hold the BOOTSET key of the Pico board, then connect the Pico to Raspberry Pi by USB cable, then release the key.
- Once the removable disk (RPI-RPI2) is recognized, copy the rp2-pico-20210418-v1.15.uf2 file to pico.
- Open the Thonny IDE in Raspberry Pi, update it if it doesn't support Pico
- Configure the port by choosing MicroPython(Raspberry Pi and ttyACM0 port) in Tools -> Options... -> Interpreter



If your Thonny doesn't support Pico, you can update it with the following command:

```
sudo apt upgrade thonny
```

- Choose File->Open...->python/ and select the corresponding .py file to run the codes

Documents

- [Schematic](#)
- [SP2485 Datasheet](#)

Demo Codes

- [Demo code](#)

If you require technical support, please go to the [Support](#) page and open a tickets.