

JV330 Series



High volume production technology

64"

54"

Commercial Printing Capabilities

Compatible with Mimaki Original Eco-Solvent inks this printer offers commercial level workflows and quality for high demand print businesses. Capable of producing a wide range of sign & graphic applications including durable banners, signs, posters, and more for internal and external use.

- Multiple media roll handling unit
- Integrated XY Slitter
- In machine lighting
- V-shaped cut function
- Mimaki Remote Access
- 2 staggered heads (6400 nozzles)

For best results, always use Mimaki original inks.

Mimaki® JV330 Series

Printhead	On-demand piezo head (2 staggered printheads)
Print resolution	600dpi, 800 dpi, 900dpi, 1200dpi
Print speed (4 color mode)	up to 1076.4 SqFt/Hr (100.00 m2/h)
Maximum print width	53.5 in (1360 mm) 63.4 in (1610 mm)
Maximum media width	53.9in (1370 mm) 63.8 in (1620 mm)
Ink Type/Color	Eco-solvent ink SS21 (C, M, Y, K, Lc, Lm, Lk, Or, W) BS4 (C, M, Y, K)
Ink Package Size	2L ink pack
Media Thickness	up to 0.04 in (1.0 mm)
Rolled Media Weight	One roll: Max. 45 kg (99.2 lb) or less Three rolls: Total 90 kg (198.4 lb) or less
Certifications	VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, EAC, KC, UKCA, GREENGUARD Gold Certificate No. 67174-420
Interface	Ethernet 1000 BASE-T (Recommended) / USB2.0 Hi-speed
Power Supply	Main unit: (Single phase AC100-120/200-240V±10%, 50/60Hz±1Hz) x2
Power Consumption	Max. 1,440 W or less x 2 / Min. 4.5 W or less (Sleep mode)
Operational Environment	Temperature: 20–30 °C (68–86 °F) Humidity: 35–65% Rh (Non condensing) Recommended temperature: 20–25 °C (68–77 °F) Dust level: General office level
Dimensions (W x D x H)	2,920 × 1,215 × 1,305 mm (115.0 x 47.8 x 51.4") 3,170 × 1,215 × 1,305 mm (124.8 x 47.8 x 51.4")
Weight	789.2 lbs. (358 kg)

High volume production technology

64"

54"

Please visit us at: www.mimakiusa.com

Mimaki USA, Inc.
150-A Satellite Blvd NE, Suwanee, GA 30024

Print speeds are based on factory tests. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. For best performance, always use Mimaki original inks. Specifications subject to change without notice.

Mimaki is a trademark of Mimaki Engineering Co. Ltd. Copyright 2022, Mimaki USA, Inc.

Rev. 4/25/22