



# SPECIFICATIONS 101 CHEMICAL TRANSFER HOSE

## CONTI | EXTREMEFLEX PETROLEUM

AVAILABLE AS A HOSE ASSEMBLY OR IN BULK



### NITRILE

CONSTRUCTION TUBE

Nitrile Synthetic Rubber (APRM Class A - high oil resistance).

### CHEMIVIC SYNTHETIC RUBBER

CORRUGATED OUTER COVER

### REINFORCEMENT

Spiral-Plied Synthetic Fabric with wire helix.

### TEMPERATURE

-40°F to 200°F (-40°C to 93°C).

### FITTING CONFIGURATION

Instalock Female Camlock, Male Camlock, and NPT Male.

### SPECIFICATIONS BY SIZE

Size	Pressure	Temperature	O.D.	I.D.	Weight/ft
2"	200 PSI	-40°F to 200°F	2.47"	2"	0.99 lbs/ft
3"	200 PSI	-40°F to 200°F	3.56"	3"	1.77 lbs/ft

The Continental ExtremeFlex Petroleum Tank Truck Hose is the perfect drop hose for use in a tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil, and petroleum-based products with up to 50% aromatic content. It has a corrugated construction for lower drag coefficient and superior abrasion resistance.

**CONFIRM COMPATIBILITY**  
WITH OUR CHEMICAL COMPATIBILITY TOOL.

**CROSS REFERENCE**  
YOUR CURRENT HOSE CONFIGURATION TO OUR SELECTION OF PRODUCTS.

**AND MORE..**  
CONVENIENTLY LOCATED IN THE BUYERS PORTAL SECTION OF OUR WEBSITE.

