

CONTINENTAL | VIPER

AVAILABLE AS A HOSE ASSEMBLY OR IN BULK



MODIFIED XLPE

CONSTRUCTION TUBE

Beige Alphasyn Modified Cross-Linked Polyethylene.

BLACK OMEGASYN / EPDM

OUTER COVER

REINFORCEMENT

Spiral-Plied Synthetic Fabric with Dual Steel Helix.

TEMPERATURE

-40°F to 250°F (-40°C to 121°C).

FITTING CONFIGURATION

Instalock Female Camlock, Male Camlock, and NPT Male.

SPECIFICATIONS BY SIZE

Size	Pressure	Temperature	O.D.	I.D.	Weight/ft
1"	200 PSI	-40°F to 250°F	1.45"	1"	0.53 lbs/ft
1.5"	200 PSI	-40°F to 250°F	1.95"	1.5"	0.74 lbs/ft
2"	200 PSI	-40°F to 250°F	2.54"	2"	1.16 lbs/ft
3"	200 PSI	-40°F to 250°F	3.59"	3"	1.82 lbs/ft

The Continental Viper is designed for the transfer of a variety of industrial chemicals used today. It is ideal for use with pressure, gravity flow, and / or suction service. The hose may be cleaned using open-end steam, up to 50 psi or in a bath containing 10% Sodium Hydroxide, up to 212°F.

CONFIRM COMPATIBILITY
WITH OUR CHEMICAL COMPATIBILITY TOOL.

CROSS REFERENCE
YOUR CURRENT HOSE CONFIGURATION TO OUR SELECTION OF PRODUCTS.

AND MORE..
CONVENIENTLY LOCATED IN THE BUYERS PORTAL SECTION OF OUR WEBSITE.