PRODUCT INFORMATION PACKET

Model No: D258 Catalog No: D258 1/5-1/10 HP Fan Coil / Room Air Conditioner Motor, 1550 RPM, 2 Speed, 208/230 Volts, 42 Frame, OAO Fan Coil / Room Air Conditioner Motors





Regal and Fasco are trademarks of Regal Beloit Corporation or one of its affiliated companies. ©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E





Product Information Packet: Model No: D258, Catalog No:D258 1/5-1/10 HP Fan Coil / Room Air Conditioner Motor, 1550 RPM, 2 Speed, 208/230 Volts, 42 Frame, OAO

FASCO

Nameplate Specifications

Output HP	1/5-1/10 Hp	Output KW	0.15 kW	
Frequency	60 Hz	Voltage	208/230 V	
Current	2.8/1.3 A	Speed	1550 rpm	
Service Factor	1	Phase	1	
Duty	Continuous	Insulation Class	В	
Frame	42	Enclosure	Totally Enclosed	
Thermal Protection	Automatic	Ambient Temperature	40 °C	
UL	Recognized	CSA	Y	
CE	Ν			

Technical Specifications

Electrical Type	Permanent Split Capacitor	Starting Method	Across The Line
Poles	4	Rotation	Clockwise Lead End
Mounting	Resilient Rings	Drive End Bearing	Sleeve
Opp Drive End Bearing	Sleeve	Frame Material	Na
Shaft Type	Flat	Overall Length	19.45 in
Shaft Diameter	0.500 in	Shaft Extension	8.00 in
Outline Drawing	7184001115_S001	Connection Drawing	SEE OUTLINE

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/11/2020

	B. SEE DRAWIN C. CENTER LAB C. CENTER LAB D. PLACE PAMP WITH .56%, LEAD DAT7 WITH .56%, C. CENTER LAB D. PLACE PAMP GROUND TERMAN. ACKED WITH MOTOR TYPE S. MOTOR TYPE S. MOTOR TYPE S. MOTOR TYPE S. MOTOR TYPE S. MOTOR TYPE	ASS: B B B B B B B B B B B B B B B B B B B	SPECIAL INSTRUCTIONS: FL ROTOR IS RUSTPROOFED. PERIPHERY. PAMPHLET PAN MOTORS PACKED MAX. PER CUSTOMER: D258 INSULATION CO. FINIS RUSTPROOFED. D258 INSULATION CO. FINIS RUSTPROOFED. D258 INSULATION CO. FINIS RUSTPROOFED. TAPPLICATION: DIST SALES INSULATION CO. FINIS RUSTPROOFED. D258 INSULATION CO. FINIS RUSTPROOFED. TAPPLICATION: DIST SALES INSULATION CO. FINIS RUSTPROOFED. TO TAX XXXXZ T1XX XXXXXZ T1XX XXXXXZ T1XX XXXXXX T1XX XXXXXXXXX T1XX XXXXXX T1XX XXXXXXXXXX	SPECIAL INSTR ROTOR IS RUS ROTOR S PACK NOTORS PACK INSULATION CLISTOMER: FASCO DISTRUE INSULATION WEIGHT	SAFETY SAFETY H47 H47 H47 H47 H47 H47 H47 H47 H47 H47	PERFORMANCE TEST IDLE RPM AMP 1782 1.00 1787 .31 1787 .31 1787 .31 1787 .31 1788 .271 TVP .055 4 .31 1.00 .059 4 .053 .07 TVP .059 4 .005 .07 TVP .059 5 .07 TVP .005 5 .07 TV	PERFORM PERFORM PLAY. 0050 PLAY. 0050	BOTH ENDS WOOL DZ58 REF PLAY HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH HIGH	ATION	PRODUCTION TEST AT IDLE 230 VOLTS (20 IZ AMP WAT 1.1392 159 - 	718 718 718 718 718 718 718 718
MANUAL PAGE 2 FOR PACKA itor/carton; itors/Layer; vers/pall et.	A. SEE PA PROCE					¢	TO USE.	HICH PACK	SALES TO SPECIFY ON P.O. WHICH PACK TO USE	SALES TO SF	
3-20-09 9-15-10	639255 641561					A)279, DETAIL	HART C600 (FOR WASHER SET-UP, SEE CHART C600 0279, DETAIL "A"	FOR WASHE	
13 11-11-08 GAE/GAE	638801						ŕ	E 7-12 IN. LE	THE BOLT TORQUE TOLERANCE 7-12 IN LBS	LING SUIL OF	N .
2-10-03	630714					MIN	AND METAL 094 MIN.	I WIRE AND	THRU AIR SPACING BETWEEN WIRE	THRU AIR SP	1. THR
. DATE S	ECO		Сору	ncontrollec	C					סהי	
_											

If Printed, this is an Uncontrolled Document.