

PRODUCT INFORMATION PACKET

FASCO®

Model No: D908
Catalog No: D908
1/3 HP Condenser Fan Motor, 1075 RPM, 208/230 Volts, 48 Frame, TEAO
Condenser Fans Motors



Regal and Fasco are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E

REGAL



Nameplate Specifications


Output HP	1/3 Hp	Output KW	0.25 kW
Frequency	60 Hz	Voltage	208-230 V
Current	2.4 A	Speed	1075 rpm
Service Factor	1	Phase	1
Duty	Continuous	Insulation Class	B
Frame	48	Enclosure	Totally Enclosed Air Over
Thermal Protection	Automatic	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
CE	N		

Technical Specifications

Electrical Type	Permanent Split Capacitor	Starting Method	Across The Line
Poles	4	Rotation	Reversible
Mounting	Extended Studs	Drive End Bearing	Sleeve
Opp Drive End Bearing	Sleeve	Frame Material	Rolled Steel
Shaft Type	Double Flat	Frame Length	4.45 in
Shaft Diameter	0.500 in	Shaft Extension	6.5 in
Outline Drawing	8856NTS-A11U		

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:22/09/2020

FASCO MOTORS MAY PROVIDE TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN MANY AREAS. HOWEVER, SINCE FASCO MOTOR IS NOT AWARE OF ALL DATA CONCERNING THE USE AND APPLICATION OF THIS MOTOR, THE FITNESS OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY AND IS THE RESPONSIBILITY OF THE CUSTOMER.






MOTOR SPECIFICATION

8856NTS-A11U


Q.R. No.	Y005165	CUSTOMER NO.	D908					
CUSTOMER	FASCO USA							
MOTOR RATING	VOLTS	208/230	Hz	60	Ph	1	Duty	S1 AOM
	RPM.	1075		2.4		AMPS		
NOM. OUTPUT		1/3 HP						
ROTATION		REVERSIBLE						
CAPACITOR START		-----		μF/V		RUN		7.5/---
ENCLOSURE		T.E.A.O.						
MOTOR TYPE		PSC		INSULATION CLASS		130 (B)		
THERMAL PROTECTION		AUTO RESET OVERLOAD						
APPLICATION		FAN CONDENSING - SHAFT HORIZONTAL						
BEARING D.E.		SLEEVE		LUBRICATION		PERMAWICK OPERA.TEMP -15°-90°C		
BEARING N.D.E.		SLEEVE						
SUPPLY LEAD		AS SHOWN						
EARTH PROVISION		SUPPLIED						
BASIC BUILD SPECIFICATION		305-881-28		PAINT/ COLOUR		PC GREY PLAIN E/SHIELDS		
PERFORMANCE SPECIFICATION		SP88012-01						
CONNECTION DIAGRAM		AS SHOWN		RATING LABEL		AS SHOWN		

FINAL INSPECTED MOTORS MUST COMPLY WITH ELECTRIC MOTOR VIBRATION SPECIFICATION (ES049)

THIRD ANGLE PROJECTION



NOTE: DIMENSIONS SHOWN INCH (mm.)
STK - 38



SPECIAL REQUIREMENTS:
1)_CAPACITOR SUPPLIED BY CUSTOMER.
2)_SCREW (SM13-13 / 4 EA) AND WASHER LOCK (SM19-1 / 4 EA) TO BE PACKED IN PLASTIC BAG AND PUT INTO INDIVIDUAL CARTON WITH MOTOR, IN CASE OF SINGLE PACKING.
3)_STAMPED FDC PART NUMBER FDC-D908 ON THE BULK PACK.
4)_ADD SAFETY BOOK P/N 398-063-02 IN ALL INDIVIDUAL CARTON.

UNLESS OTHERWISE SPECIFIED : DIMENSIONS ARE IN MM. TOLERANCES		MOTOR WEIGHT	
		5.7 kg.	
DECIMALS	ANGULAR	DRAWN	muntana 22/10/2013
.X ± 1.0	± 30'	CHECKED	Pipat 21/08/2017
.XX ± 0.1		RELEASED	Sutthipant 21/08/2017
THIS DRAWING REMAINS THE PROPERTY OF FASCO MOTORS AND MAY NOT BE USED, COPIED OR ISSUED WITHOUT WRITTEN PERMISSION FROM FASCO MOTORS		SCALE	N.T.S.

FASCO THAILAND
29/7-8 MOO 3, BANGKRUAY - SAINOI Rd., BANGKRANG, MIJANG NONTABURI DISTRICT, NONTABURI 11000 THAILAND

FRAME	MOTOR	
STATUS	S012:8856T-342-MCX:FDC	
SHEET	DWG. NO.	REVISION
A3	8856NTS-A11U	F