



## Submittal Data Sheet

FTXS12LVJU

FTXS12LVJU

### FEATURES

- Intelligent eye occupancy sensor
- Weekly timer for programmable comfort
- Low ambient heat operation down to 0° F
- Titanium apatite photocatalytic air purifying
- 12 year limited parts and compressor warranty with online registration

### BENEFITS

- Quiet operation





## Submittal Data Sheet

FTXS12LVJU

FTXS12LVJU

### PERFORMANCE

|                                  |              |                               |   |
|----------------------------------|--------------|-------------------------------|---|
| Indoor Unit Model No.            | FTXS12LVJU   | Indoor Unit Name:             | FTXS12LVJU  |
| Type:                            | Wall Mounted | Rated Cooling Conditions:     | Indoor (°F DB/WB): 80 / 67<br>Ambient (°F DB/WB): 95 / 75 |
| Rated Cooling Capacity (Btu/hr): | 12,000       | Rated Heating Conditions:     | Indoor (°F DB/WB): 70 / 70<br>Ambient (°F DB/WB): 47 / 43 |
| Sensible Capacity (Btu/hr):      | 9,250        | Rated Piping Length(ft):      |   |
| Cooling Input Power (kW):        | 0.940        | Rated Height Separation (ft): |   |
| Rated Heating Capacity (Btu/hr): | 14,400       |                               |   |
| Heating Input Power (kW):        | 0.97         |                               |   |

### INDOOR UNIT DETAILS

|                                       |                                       |  |                 |
|---------------------------------------|---------------------------------------|--|-----------------|
| Power Supply (V/Hz/Ph):               | 208-230 / 60 / 1                      | Airflow Rate (H/M/L/SL) (CFM):           | 403/309/205/155 |
| Power Supply Connections:             | See Outdoor Unit for Electrical Specs | Moisture Removal (Gal/hr):               | 4.0             |
| Min. Circuit Amps MCA (A):            |                                       | Gas Pipe Connection (inch):              | 3/8             |
| Max Overcurrent Protection (MOP) (A): |                                       | Liquid Pipe Connection (inch):           | 1/4             |
| Dimensions (HxWxD) (in):              | 11-5/8 x 31-1/2 x 8-7/16              | Condensate Connection (inch):            | 5/8             |
| Panel (HxWxD) (in):                   |                                       | Sound Pressure (H/M) (dBA):              | 45/23           |
| Net Weight (lb):                      | 22                                    | Sound Power Level (dBA):                 |                 |
| Panel Weight (lb):                    |                                       | Ext. Static Pressure (Rated/Max) (inWg): | 0.00 / 0.00     |

**Submittal Data Sheet**

FTXS12LVJU

FTXS12LVJU

**DIMENSIONAL DRAWING**

**FTXS09, 12LVJU**

