


Job Name:	
Tag#	



Submittal Data Sheet	FTK24NMVJU / RK24NMVJU
2-Ton Wall Mounted Cooling Only System	



Efficiency	
Cooling	
SEER	18
EER	12.5

Performance	
Cooling (Btu/hr)	
Rated (Min/Max)	21,200 (5,500 / 24,000)
Sensible @ AHRI	15,760
Moisture Removal gal/h	1.2
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-4°F – 115°F
Rated Cooling Conditions:	
	Indoor: 80°F DB/67°F WB
	Outdoor: 95°F DB/75°F WB
*With field settings and wind baffle	

Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Indoor Specifications		
Airflow Rate (cfm)	Cooling	
	H	M
	713	579
	L	SL
512	403	
Sound (dBA) H / M / L / SL	53 / 45 / 39 / 34	
Dimensions (H x W x D) (in)	11-5/8 x 39 x 10-3/8	
Weight (Lbs)	27	

Electrical		
	208/60/1	230/60/1
System MCA	18.3	18.3
System MFA	20	20
Compressor RLA	12.0	12.0
Outdoor fan motor FLA	.38	.38
Outdoor fan motor W	58	58
Indoor fan motor FLA	.30	.30
Indoor fan motor W	46	46
MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A) RLA: Rated load amps (A) W: Fan motor rated output (W)		


Outdoor Specifications		
Compressor	Hermetically Sealed Swing Type	
Refrigerant	R-410A	
Factory Charge (Lbs)	3.20	
Refrigerant Oil	PVE (FVC50K)	
Airflow Rate (cfm)	Cooling	
	H	2,101
	SL	1,762
Sound Pressure Level (dBA)	55	
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/8	
Weight (Lbs)	108	

Piping	
Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.21

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)




FTK24NMVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

RK24NMVJU Dimensional Data



unit: inch (mm)
C: 3D092230

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter (S21 Adapter Included)
	BRC944B2-A08	Wired Remote Controller kit (Adaptor Required)
	BRCW901A08	Wired Remote Controller Cable – 25ft (Included in above kit)
	BRCW901A03	Wired Remote Controller Cable – 10ft
	KRP980B2	Adaptor for wired remote controller (18 & 24)
	KAF970A45	Titanium apatite photocatalytic air-purifying filter WITH frame
	KAF970A46	Titanium apatite photocatalytic air-purifying filter WITHOUT frame
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S + KRP980B2	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	DACA-WB-1	Powder-Coated Wall-Mounted Bracket
	KPW063A4	Air direction adjustment grille (18 & 24)
	KEH063A4E	Daikin BML Drain Pan Heater Large RX18,24 & RXN18,24
	KKG063A42	Back protection wire net (18 & 24)
	KKP937A4	Drain Plug for OD Unit