

PRODUCT INFORMATION PACKET



Model No: FSP4016

Catalog No: FSP4016

1/5 HP Fan & Blower Motor, 1050 RPM, 3 Speed, 115 Volts, 48 Frame, Semi Enclosed
Direct Drive Motors



Regal and Century are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E

The REGAL logo is a grey rectangular box with the word 'REGAL' in white, slanted capital letters. It is positioned on a blue background with a halftone dot pattern that tapers to the right.

REGAL



Nameplate Specifications

Output HP	1/5 Hp	Output KW	0.15 kW
Frequency	60 Hz	Voltage	115 V
Current	3.2 A	Speed	1050 rpm
Service Factor	1	Phase	1
Duty	Air Over	Insulation Class	A
Frame	48Y	Enclosure	Semi Enclosed
Thermal Protection	Automatic	Ambient Temperature	40 °C
UL	Recognized	CSA	N
CE	N		

Technical Specifications

Electrical Type	Permanent Split Capacitor	Starting Method	Across The Line
Poles	6	Rotation	Counterclockwise Lead End
Mounting	Resilient Rings	Motor Orientation	Horizontal
Drive End Bearing	Sleeve	Opp Drive End Bearing	Sleeve
Frame Material	Rolled Steel	Shaft Type	Flat
Overall Length	9.61 in	Frame Length	3.75 in
Shaft Diameter	0.500 in	Shaft Extension	4.8 in
Outline Drawing	11760-062	Connection Drawing	614131-086

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/11/2020

4	3	2	1																																						
GENERAL INFORMATION: SHAFT RUNOUT: .001[.03] T.I.R PER INCH LENGTH OF EXTENSION END PLAY: .010[.25] TO .063[1.60] BEARINGS: SLEEVE MOUNTING POSITION: HORIZONTAL ELECTRICAL DATA: OVERLOAD PROTECTOR: AUTOMATIC RESET (T.I. 7AM 032) LINE LEADS: NO. 18 GA., .06[1.5] THK. 125°C INSUL. CAPACITOR LEADS: NO. 18 GA., .03[.8] THK. 125°C INSUL. GROUND LEAD: NO. 18 GA., .03[.8] THK. (GREEN) INSUL.		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>REV</th> <th>ECO</th> <th>REV BY</th> <th>DATE</th> <th>APPD</th> <th>DATE</th> </tr> <tr> <td>C</td> <td>0025550</td> <td>A. ARREOLA</td> <td>04-27-2012</td> <td>D. BALDERRAMA</td> <td>04-27-2012</td> </tr> </table>		REV	ECO	REV BY	DATE	APPD	DATE	C	0025550	A. ARREOLA	04-27-2012	D. BALDERRAMA	04-27-2012																										
REV	ECO	REV BY	DATE	APPD	DATE																																				
C	0025550	A. ARREOLA	04-27-2012	D. BALDERRAMA	04-27-2012																																				
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>NAMEPLATE DATA:</th> <th>EXTERNAL CONNECTION DIAGRAM</th> </tr> <tr> <td> MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED </td> <td> </td> </tr> </table>		NAMEPLATE DATA:	EXTERNAL CONNECTION DIAGRAM	MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED		<p style="text-align: center;">CCW ROTATION</p> <p style="text-align: center;">TOP OF STICKER WARNING (WHEN REQ'D)</p> <p style="text-align: center;">TOP OF NAMEPLATE</p> <p style="text-align: center;">LEAD LENGTH</p> <p style="text-align: center;">LEAD LENGTH</p> <p style="text-align: center;">LEAD LENGTH</p> <p style="text-align: center;">GROUND LEAD (TERMINAL AT MOTOR MUST NOT PROTRUDE BEYOND MOTOR O.D.)</p> <p style="text-align: center;">2X #2.50 [Ø63.5]</p> <p style="text-align: center;">4.92 [124.9]</p> <p style="text-align: center;">4X .64 [16.3]</p> <p style="text-align: center;">4X #8-32 THD'S EQUALLY SPACED ON A Ø5.147[Ø130.56] B.C.</p> <p style="text-align: center;">.50 [12.7]</p> <p style="text-align: center;">.50 [12.7]</p> <p style="text-align: center;">3.50 [88.9] USABLE FLAT</p> <p style="text-align: center;">.453±.005 [11.51±.13] FLAT</p> <p style="text-align: center;">Ø5.70 [Ø144.8] MAX.</p> <p style="text-align: center;">9.11 [231.4]</p> <p style="text-align: center;">4.36 [110.7]</p> <p style="text-align: center;">4.75 [120.6]</p>																																			
NAMEPLATE DATA:	EXTERNAL CONNECTION DIAGRAM																																								
MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>PERFORMANCE CURVE NO.</th> <th>TORQUE @1050 RPM (25°C)</th> <th>APPROVED SAMPLE</th> <th>UL COMPONENT FILE #</th> <th>GUIDE #</th> <th>CSA FILE #</th> <th>GUIDE #</th> </tr> <tr> <td>C31446</td> <td>16.3 OZ. FT.</td> <td>97AC039A</td> <td>E46412</td> <td>PRGY2</td> <td>-----</td> <td>-----</td> </tr> </table>		PERFORMANCE CURVE NO.	TORQUE @1050 RPM (25°C)	APPROVED SAMPLE	UL COMPONENT FILE #	GUIDE #	CSA FILE #	GUIDE #	C31446	16.3 OZ. FT.	97AC039A	E46412	PRGY2	-----	-----	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>COLOR</th> <th>LENGTH</th> <th>TERMINAL OR STRIP LENGTH</th> </tr> <tr> <td>GREEN (GRD)</td> <td>9/11 [229/279]</td> <td>#10 EYELET</td> </tr> <tr> <td>BROWN</td> <td>CONNECTED TO CAPACITOR</td> <td>.19[4.8] FEMALE SPADE</td> </tr> <tr> <td>BROWN</td> <td>CONNECTED TO CAPACITOR</td> <td>.19[4.8] FEMALE SPADE</td> </tr> <tr> <td>YELLOW</td> <td>26/28 [660/711]</td> <td>.25[6.4] FEMALE SPADE</td> </tr> <tr> <td>BLACK</td> <td>26/28 [660/711]</td> <td>.25[6.4] FEMALE SPADE</td> </tr> <tr> <td>BLUE</td> <td>26/28 [660/711]</td> <td>.25[6.4] FEMALE SPADE</td> </tr> <tr> <td>RED</td> <td>26/28 [660/711]</td> <td>.25[6.4] FEMALE SPADE</td> </tr> </table>		COLOR	LENGTH	TERMINAL OR STRIP LENGTH	GREEN (GRD)	9/11 [229/279]	#10 EYELET	BROWN	CONNECTED TO CAPACITOR	.19[4.8] FEMALE SPADE	BROWN	CONNECTED TO CAPACITOR	.19[4.8] FEMALE SPADE	YELLOW	26/28 [660/711]	.25[6.4] FEMALE SPADE	BLACK	26/28 [660/711]	.25[6.4] FEMALE SPADE	BLUE	26/28 [660/711]	.25[6.4] FEMALE SPADE	RED	26/28 [660/711]	.25[6.4] FEMALE SPADE
PERFORMANCE CURVE NO.	TORQUE @1050 RPM (25°C)	APPROVED SAMPLE	UL COMPONENT FILE #	GUIDE #	CSA FILE #	GUIDE #																																			
C31446	16.3 OZ. FT.	97AC039A	E46412	PRGY2	-----	-----																																			
COLOR	LENGTH	TERMINAL OR STRIP LENGTH																																							
GREEN (GRD)	9/11 [229/279]	#10 EYELET																																							
BROWN	CONNECTED TO CAPACITOR	.19[4.8] FEMALE SPADE																																							
BROWN	CONNECTED TO CAPACITOR	.19[4.8] FEMALE SPADE																																							
YELLOW	26/28 [660/711]	.25[6.4] FEMALE SPADE																																							
BLACK	26/28 [660/711]	.25[6.4] FEMALE SPADE																																							
BLUE	26/28 [660/711]	.25[6.4] FEMALE SPADE																																							
RED	26/28 [660/711]	.25[6.4] FEMALE SPADE																																							
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>MAIN FRAME - OLE</th> <th>SEMI-ENCLOSED</th> </tr> <tr> <td>END FRAME - OLE</td> <td>OPEN</td> </tr> <tr> <th>MAIN FRAME - LE</th> <th>SEMI-ENCLOSED</th> </tr> <tr> <td>END FRAME - LE</td> <td>OPEN</td> </tr> </table>		MAIN FRAME - OLE	SEMI-ENCLOSED	END FRAME - OLE	OPEN	MAIN FRAME - LE	SEMI-ENCLOSED	END FRAME - LE	OPEN	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>ENCLOSURE</th> <th>CUSTOMER</th> <th>DISTRIBUTION SERVICES</th> </tr> <tr> <td></td> <td></td> <td></td> </tr> </table>		ENCLOSURE	CUSTOMER	DISTRIBUTION SERVICES																											
MAIN FRAME - OLE	SEMI-ENCLOSED																																								
END FRAME - OLE	OPEN																																								
MAIN FRAME - LE	SEMI-ENCLOSED																																								
END FRAME - LE	OPEN																																								
ENCLOSURE	CUSTOMER	DISTRIBUTION SERVICES																																							
GEOMETRIC CHARACTERISTICS & SYMBOLS ▽ FLATNESS - STRAIGHTNESS < ANGLARITY ⊥ PERPENDICULARITY (SQUARENESS) ∥ PARALLELISM ○ ROUNDNESS (CIRCULARITY) ⌀ CYLINDRICITY ~ PROFILE OF ANY SURFACE ~ PROFILE OF ANY LINE † RUNOUT ● TRUE POSITION ⊙ CONCENTRICITY = SYMMETRY ASME Y14.5M 1994		REGAL-BELOIT CORPORATION (RBC) PROVIDES TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN SEVERAL AREAS. SINCE RBC DOES NOT RECEIVE ALL DATA CONCERNING THE USE AND APPLICATION OF THE MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY THE CUSTOMER. DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.																																							
DR BY: J. RUPERT 03-21-1997 APPD: T. RILEY 03-24-1997 THRD ANGLE PROJECTION:		EDS DATE 11-11-2011 FORMAT REV G DESCRIPTION: MODEL-RFHP-48FR OUTLINE SIZE: C DWG NO: 11760-062 SCALE: NONE SHEET 1																																							

4	3	2	1																								
INFORMACION GENERAL: OSCILACION DE FLECHA: .001[.03] L.T.I. POR LONGITUD DE EXTENSION JUEGO AXIAL: .010[.25] A .063[1.60] BALEROS: FUNDA POSICION DEL MONTAJE: HORIZONTAL INFORMACION ELECTRICA: PROTECTOR DE SOBRECARGA: REINICIO AUTOMATICO (T.I. 7AM 032) LINEA DE CABLES: CALIBRE 18 AISLANTE .06[1.5] GROSOR 125°C CABLES DE CAPACITOR: CALIBRE 18 AISLANTE .03[.8] GROSOR 125°C CABLE DE TIERRA: CALIBRE 18 AISLANTE .03[.8] GROSOR (VERDE)		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>REVISION: ECO</td> <td>REVISADO POR: A. ARREOLA</td> <td>FECHA: 04-27-2012</td> <td>APROBADO POR: D. BALDERRAMA</td> <td>FECHA: 04-27-2012</td> </tr> <tr> <td>C</td> <td>0025550</td> <td></td> <td></td> <td></td> </tr> </table>		REVISION: ECO	REVISADO POR: A. ARREOLA	FECHA: 04-27-2012	APROBADO POR: D. BALDERRAMA	FECHA: 04-27-2012	C	0025550																	
REVISION: ECO	REVISADO POR: A. ARREOLA	FECHA: 04-27-2012	APROBADO POR: D. BALDERRAMA	FECHA: 04-27-2012																							
C	0025550																										
INFORMACION DE ETIQUETA: MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED		<p>ROTACION CCW</p> <p>Ø5.70 [Ø144.8] MAX.</p> <p>PARTE SUPERIOR DE ETIQUETA DE ADVERTENCIA (CUANDO SE REQUIERA)</p> <p>LONGITUD DE CABLES</p> <p>9.11 [231.4]</p> <p>4.36 [110.7]</p> <p>4.75 [120.6]</p> <p>PARTE SUPERIOR DE PLACA DE DATOS</p> <p>.50 [12.7]</p> <p>3.50 [88.9] PLANO UTILIZABLE</p> <p>2X Ø2.50 [Ø63.5]</p> <p>Ø4.998^{+0.000}/_{-.0005}</p> <p>Ø12.695^{+0.000}/_{-.013}</p> <p>.453±.005 [11.51±.13] PLANO</p> <p>4X .64 [16.3]</p> <p>4X ROSCAS #8-32 IGUALMENTE ESPACIADAS EN UN Ø5.147[Ø130.56] ENTRE CENTROS</p> <p>CABLE DE TIERRA (LA TERMINAL EN EL MOTOR NO DEBE RESALTAR MAS ALLA DEL DIAMETRO EXTERIOR DEL MOTOR)</p>																									
DIAGRAMA DE CONEXION EXTERNA YELLOW BLACK HI BLUE MED RED LO LINE		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>VERDE (TIERRA)</td> <td>9/11 [229/279]</td> <td>OJAL #10</td> </tr> <tr> <td>CAFE</td> <td>CONECTADO AL CAPACITOR</td> <td>.19[4.8] TERMINAL HEMBRA</td> </tr> <tr> <td>CAFE</td> <td>CONECTADO AL CAPACITOR</td> <td>.19[4.8] TERMINAL HEMBRA</td> </tr> <tr> <td>AMARILLO</td> <td>26/28 [660/711]</td> <td>.25[6.4] TERMINAL HEMBRA</td> </tr> <tr> <td>NEGRO</td> <td>26/28 [660/711]</td> <td>.25[6.4] TERMINAL HEMBRA</td> </tr> <tr> <td>AZUL</td> <td>26/28 [660/711]</td> <td>.25[6.4] TERMINAL HEMBRA</td> </tr> <tr> <td>ROJO</td> <td>26/28 [660/711]</td> <td>.25[6.4] TERMINAL HEMBRA</td> </tr> <tr> <td>COLOR</td> <td>LONGITUD</td> <td>TERMINAL O LONGITUD DE DESFORRE</td> </tr> </table>		VERDE (TIERRA)	9/11 [229/279]	OJAL #10	CAFE	CONECTADO AL CAPACITOR	.19[4.8] TERMINAL HEMBRA	CAFE	CONECTADO AL CAPACITOR	.19[4.8] TERMINAL HEMBRA	AMARILLO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA	NEGRO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA	AZUL	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA	ROJO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA	COLOR	LONGITUD	TERMINAL O LONGITUD DE DESFORRE
VERDE (TIERRA)	9/11 [229/279]	OJAL #10																									
CAFE	CONECTADO AL CAPACITOR	.19[4.8] TERMINAL HEMBRA																									
CAFE	CONECTADO AL CAPACITOR	.19[4.8] TERMINAL HEMBRA																									
AMARILLO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA																									
NEGRO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA																									
AZUL	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA																									
ROJO	26/28 [660/711]	.25[6.4] TERMINAL HEMBRA																									
COLOR	LONGITUD	TERMINAL O LONGITUD DE DESFORRE																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>CURVAS DE FUNCIONAMIENTO</td> <td>TORSION @1050 RPM (25°C)</td> <td>MUESTRA APROBADA</td> <td>COMPONENTE UL</td> <td>CSA</td> </tr> <tr> <td>C31446</td> <td>16.3 OZ. FT.</td> <td>97AC039A</td> <td>E46412 PRGY2</td> <td>-----</td> </tr> </table>		CURVAS DE FUNCIONAMIENTO	TORSION @1050 RPM (25°C)	MUESTRA APROBADA	COMPONENTE UL	CSA	C31446	16.3 OZ. FT.	97AC039A	E46412 PRGY2	-----	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>CARCASA - LOC</td> <td>SEMI CERRADO</td> </tr> <tr> <td>TAPA - LOC</td> <td>ABIERTO</td> </tr> <tr> <td>CARCASA - LC</td> <td>SEMI CERRADO</td> </tr> <tr> <td>TAPA - LC</td> <td>ABIERTO</td> </tr> </table>		CARCASA - LOC	SEMI CERRADO	TAPA - LOC	ABIERTO	CARCASA - LC	SEMI CERRADO	TAPA - LC	ABIERTO						
CURVAS DE FUNCIONAMIENTO	TORSION @1050 RPM (25°C)	MUESTRA APROBADA	COMPONENTE UL	CSA																							
C31446	16.3 OZ. FT.	97AC039A	E46412 PRGY2	-----																							
CARCASA - LOC	SEMI CERRADO																										
TAPA - LOC	ABIERTO																										
CARCASA - LC	SEMI CERRADO																										
TAPA - LC	ABIERTO																										
INFORMACION DE CABLES VERDE (TIERRA) 9/11 [229/279] OJAL #10 CAFE CONECTADO AL CAPACITOR .19[4.8] TERMINAL HEMBRA CAFE CONECTADO AL CAPACITOR .19[4.8] TERMINAL HEMBRA AMARILLO 26/28 [660/711] .25[6.4] TERMINAL HEMBRA NEGRO 26/28 [660/711] .25[6.4] TERMINAL HEMBRA AZUL 26/28 [660/711] .25[6.4] TERMINAL HEMBRA ROJO 26/28 [660/711] .25[6.4] TERMINAL HEMBRA COLOR LONGITUD TERMINAL O LONGITUD DE DESFORRE		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>CLIENTE</td> <td>DISTRIBUTION SERVICES</td> </tr> </table>		CLIENTE	DISTRIBUTION SERVICES																						
CLIENTE	DISTRIBUTION SERVICES																										
CARACTERISTICAS DE GEOMETRIA Y SIMBOLOS ▽ PLANICIDAD - RECTITUD < ANGULARIDAD ⊥ PERPENDICULARIDAD (A ESQUADRA) // PARALELISMO ○ REDONDEZ (CIRCULARIDAD) ⌀ CILINDRICIDAD ⊖ PERFIL DE CUALQUIER SUPERFICIE ⊖ PERFIL DE CUALQUIER LINEA † VARIACION ⊕ POSICION REAL ⊙ CONCENRICIDAD ⇌ SIMETRIA ASME Y14.5M 1994		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>REGAL-BELOIT CORPORATION (RBC) PROVEE ASISTENCIA TECNICA A NUESTROS CLIENTES EN VARIAS AREAS. DESDE QUE RBC NO RECIBE TODOS LOS DATOS EN RELACION AL USO Y A LA APLICACION DEL MOTOR, LA APLICACION ADECUADA DEL MOTOR DEBE SER DETERMINADA POR EL CLIENTE.</td> <td>DIBUJADO POR: J. RUPERT 03-21-1997</td> </tr> <tr> <td>DIMENSIONES SIN TOLERANCIA SON DE REFERENCIA SOLAMENTE</td> <td>APROBADO POR: T. RILEY 03-24-1997</td> </tr> <tr> <td></td> <td>FECHA EDS: 11-11-2011 REV. FORMATO: G</td> </tr> </table>		REGAL-BELOIT CORPORATION (RBC) PROVEE ASISTENCIA TECNICA A NUESTROS CLIENTES EN VARIAS AREAS. DESDE QUE RBC NO RECIBE TODOS LOS DATOS EN RELACION AL USO Y A LA APLICACION DEL MOTOR, LA APLICACION ADECUADA DEL MOTOR DEBE SER DETERMINADA POR EL CLIENTE.	DIBUJADO POR: J. RUPERT 03-21-1997	DIMENSIONES SIN TOLERANCIA SON DE REFERENCIA SOLAMENTE	APROBADO POR: T. RILEY 03-24-1997		FECHA EDS: 11-11-2011 REV. FORMATO: G																		
REGAL-BELOIT CORPORATION (RBC) PROVEE ASISTENCIA TECNICA A NUESTROS CLIENTES EN VARIAS AREAS. DESDE QUE RBC NO RECIBE TODOS LOS DATOS EN RELACION AL USO Y A LA APLICACION DEL MOTOR, LA APLICACION ADECUADA DEL MOTOR DEBE SER DETERMINADA POR EL CLIENTE.	DIBUJADO POR: J. RUPERT 03-21-1997																										
DIMENSIONES SIN TOLERANCIA SON DE REFERENCIA SOLAMENTE	APROBADO POR: T. RILEY 03-24-1997																										
	FECHA EDS: 11-11-2011 REV. FORMATO: G																										
DESCRIPCION: MODEL-RFHP-48FR OUTLINE TAMANO: C NUMERO DE DIBUJO: 11760-062 ESCALA: NONE HOJA: 1		REGAL-BELOIT CORPORATION																									

<p>总技术要求:</p> <p>轴跳动:</p> <p>端部窜动量</p> <p>轴承:</p> <p>安装位置:</p> <p>电气数据:</p> <p>过载保护:</p> <p>引线:</p> <p>接地线:</p>	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>版本</td> <td>ECO</td> <td>编制</td> <td>日期</td> <td>批准</td> <td>日期</td> </tr> <tr> <td>C</td> <td>0025550</td> <td>A. ARREOLA</td> <td>04-27-2012</td> <td>D. BALDERRAMA</td> <td>04-27-2012</td> </tr> </table>	版本	ECO	编制	日期	批准	日期	C	0025550	A. ARREOLA	04-27-2012	D. BALDERRAMA	04-27-2012																	
版本	ECO	编制	日期	批准	日期																									
C	0025550	A. ARREOLA	04-27-2012	D. BALDERRAMA	04-27-2012																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>铭牌数据</th> <th>外部数据</th> </tr> <tr> <td> MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED </td> <td> YELLOW </td> </tr> </table>	铭牌数据	外部数据	MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED	YELLOW 	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>9/11</td> <td>[229/279]</td> <td></td> </tr> <tr> <td>26/28</td> <td>[660/711]</td> <td></td> </tr> <tr> <td>26/28</td> <td>[660/711]</td> <td></td> </tr> <tr> <td>26/28</td> <td>[660/711]</td> <td></td> </tr> <tr> <td>26/28</td> <td>[660/711]</td> <td></td> </tr> <tr> <td>26/28</td> <td>[660/711]</td> <td></td> </tr> <tr> <th>颜色</th> <th>长度</th> <th>端子或剥线长度</th> </tr> </table>	9/11	[229/279]		26/28	[660/711]		26/28	[660/711]		26/28	[660/711]		26/28	[660/711]		26/28	[660/711]		颜色	长度	端子或剥线长度				
铭牌数据	外部数据																													
MODEL NO.: F48H92A01 CUST. P/N: FSP4016 HP: 1/5 ROT.: CCWLE RPM: 1050/3 SPD. TYPE: UF FRAME: 48Y VOLTS: 115 PH: 1 AMPS: 3.2 (4.0 MAX.) HZ: 60 INS.: A AMB.: 40° C DUTY: AIR OVER CAP.: 5 MFD/250 V ENCL: SEMI-ENCL. UL LOGO THERMALLY PROTECTED	YELLOW 																													
9/11	[229/279]																													
26/28	[660/711]																													
26/28	[660/711]																													
26/28	[660/711]																													
26/28	[660/711]																													
26/28	[660/711]																													
颜色	长度	端子或剥线长度																												
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>性能曲线编号</th> <th>转矩在 @ RPM (25° C)</th> <th>批准样品</th> <th colspan="4">UL部件</th> <th colspan="2">CSA</th> </tr> <tr> <td>C31446</td> <td>16.3 OZ. FT.</td> <td>97AC039A</td> <td>E46412</td> <td>PRGY2</td> <td>-----</td> <td>-----</td> <td></td> <td></td> </tr> </table>	性能曲线编号	转矩在 @ RPM (25° C)	批准样品	UL部件				CSA		C31446	16.3 OZ. FT.	97AC039A	E46412	PRGY2	-----	-----			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>无引线端机壳</td> <td></td> </tr> <tr> <td>无引线端盖</td> <td></td> </tr> <tr> <td>有引线端机壳</td> <td></td> </tr> <tr> <td>有引线端盖</td> <td></td> </tr> </table>	无引线端机壳		无引线端盖		有引线端机壳		有引线端盖		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>用户</td> <td>DISTRIBUTION SERVICES</td> </tr> </table>	用户	DISTRIBUTION SERVICES
性能曲线编号	转矩在 @ RPM (25° C)	批准样品	UL部件				CSA																							
C31446	16.3 OZ. FT.	97AC039A	E46412	PRGY2	-----	-----																								
无引线端机壳																														
无引线端盖																														
有引线端机壳																														
有引线端盖																														
用户	DISTRIBUTION SERVICES																													
<p>ASME Y14.5M 1994</p>	<p>REGAL-BELOIT CORPORATION (RBC) 在个别领域为客户提供技术支持。鉴于RBC未收到任何涉及电机使用和应用环境的数据，电机的适用性由客户自己决定。</p> <p>未注公差尺寸仅供参考。</p>	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>绘图:</td> <td>J. RUPERT</td> <td>03-21-1997</td> </tr> <tr> <td>批准:</td> <td>T. RILEY</td> <td>03-24-1997</td> </tr> <tr> <td>第三角投影</td> <td></td> <td>图版格式发布日期 11-11-2011 图版格式版本 C</td> </tr> <tr> <td colspan="3">机密: 本图版及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权, 不得泄露、复制、传播或作其他用途。--版权所有</td> </tr> </table>	绘图:	J. RUPERT	03-21-1997	批准:	T. RILEY	03-24-1997	第三角投影		图版格式发布日期 11-11-2011 图版格式版本 C	机密: 本图版及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权, 不得泄露、复制、传播或作其他用途。--版权所有			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"></td> </tr> <tr> <td colspan="2" style="text-align: center;">MODEL-RFHP-48FR OUTLINE</td> </tr> <tr> <td>名称</td> <td></td> </tr> <tr> <td>图幅</td> <td>C</td> </tr> <tr> <td>图号</td> <td>11760-062</td> </tr> <tr> <td>比例</td> <td>NONE</td> </tr> <tr> <td>页号</td> <td>1</td> </tr> </table>			MODEL-RFHP-48FR OUTLINE		名称		图幅	C	图号	11760-062	比例	NONE	页号	1	
绘图:	J. RUPERT	03-21-1997																												
批准:	T. RILEY	03-24-1997																												
第三角投影		图版格式发布日期 11-11-2011 图版格式版本 C																												
机密: 本图版及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权, 不得泄露、复制、传播或作其他用途。--版权所有																														
MODEL-RFHP-48FR OUTLINE																														
名称																														
图幅	C																													
图号	11760-062																													
比例	NONE																													
页号	1																													