

# PRODUCT INFORMATION PACKET



Model No: OWW6516  
Catalog No: OWW6516  
1/5 HP OEM Replacement Motor, 1075 RPM, 208-230 Volts, 42 Frame, OAO  
HVAC/R OEM Replacement Motors



Regal and Century are trademarks of Regal Beloit Corporation or one of its affiliated companies.  
©2020 Regal Beloit Corporation, All Rights Reserved. MC017097E





**Nameplate Specifications**

Output HP	1/5 Hp	Output KW	0.15 kW
Frequency	60 Hz	Voltage	208-230 V
Current	1.5 A	Speed	1075 rpm
Service Factor	1	Phase	1
Duty	Air Over	Insulation Class	B
Frame	42Y	Enclosure	Open Enclosed
Thermal Protection	Automatic	Ambient Temperature	40 °C
UL	Recognized	CSA	Y
CE	N		

**Technical Specifications**

Electrical Type	Permanent Split Capacitor	Starting Method	Across The Line
Poles	6	Rotation	Reversible
Mounting	Extended Studs	Motor Orientation	Horizontal
Drive End Bearing	Sleeve	Opp Drive End Bearing	Sleeve
Frame Material	Na	Shaft Type	Flat
Overall Length	8.15 in	Shaft Diameter	0.500 in
Shaft Extension	4.3 in		
Outline Drawing	11704-004	Connection Drawing	7553A62F01

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:06/11/2020

4	3	2	1																																
<b>GENERAL INFORMATION:</b>  SHAFT RUNOUT: .001[.03] T.I.R. PER INCH LENGTH OF EXTENSION.  END PLAY: .010[.25] TO .063[1.60]  BEARINGS: SLEEVE  MOUNTING POSITION: HORIZONTAL  <b>ELECTRICAL DATA:</b>  OVERLOAD PROTECTOR: AUTOMATIC RESET (T.I. 7AM 304)  LEADS: NO.18 GA. .06[1.5] THK, 125°C INSUL.  REVERSING LEADS: NO.18 GA. .03[.8] THK, 125°C INSUL.  GROUND LEAD: NO.18 GA. .03[.8] THK, 125°C GREEN INSUL.		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>REV</th> <th>ECO</th> <th>REV BY</th> <th>DATE</th> <th>APPD</th> <th>DATE</th> </tr> <tr> <td>D</td> <td>0026379</td> <td>R.LIAN</td> <td>05-28-2012</td> <td>B.SHEN</td> <td>05-28-2012</td> </tr> </table>		REV	ECO	REV BY	DATE	APPD	DATE	D	0026379	R.LIAN	05-28-2012	B.SHEN	05-28-2012																				
REV	ECO	REV BY	DATE	APPD	DATE																														
D	0026379	R.LIAN	05-28-2012	B.SHEN	05-28-2012																														
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>NAMEPLATE DATA:</th> <th>EXTERNAL CONNECTION DIAGRAM</th> </tr> <tr> <td>                     MODEL NO.: 322P757                      CUST. P/N: OWW6516                      HP: 1/5                      ROT.: REVERSIBLE                      RPM: 1075                      TYPE: FLL                      FRAME: 42Y                      VOLTS: 208-230                      PH: 1                      AMPS: 1.5                      HZ: 60                      INS.: B*                      AMB.: 40° C                      DUTY: AIR COVER                      CAP.: 7.5 MFD/370 V                      ENCL: -                      UL LOGO                      CSA LOGO                      THERMALLY PROTECTED TYPE C                 </td> <td> </td> </tr> </table>		NAMEPLATE DATA:	EXTERNAL CONNECTION DIAGRAM	MODEL NO.: 322P757 CUST. P/N: OWW6516 HP: 1/5 ROT.: REVERSIBLE RPM: 1075 TYPE: FLL FRAME: 42Y VOLTS: 208-230 PH: 1 AMPS: 1.5 HZ: 60 INS.: B* AMB.: 40° C DUTY: AIR COVER CAP.: 7.5 MFD/370 V ENCL: - UL LOGO CSA LOGO THERMALLY PROTECTED TYPE C																															
NAMEPLATE DATA:	EXTERNAL CONNECTION DIAGRAM																																		
MODEL NO.: 322P757 CUST. P/N: OWW6516 HP: 1/5 ROT.: REVERSIBLE RPM: 1075 TYPE: FLL FRAME: 42Y VOLTS: 208-230 PH: 1 AMPS: 1.5 HZ: 60 INS.: B* AMB.: 40° C DUTY: AIR COVER CAP.: 7.5 MFD/370 V ENCL: - UL LOGO CSA LOGO THERMALLY PROTECTED TYPE C																																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>PERFORMANCE CURVE NO.</th> <th>TORQUE @ 1075 RPM (25°C)</th> <th>APPROVED SAMPLE</th> <th>UL COMPONENT FILE #</th> <th>CCN #</th> <th>CSA FILE #</th> <th>CLASS #</th> </tr> <tr> <td>C31088</td> <td>19.2 OZ. FT.</td> <td>PSE 7404</td> <td>E46412</td> <td>PRGY2</td> <td>LR43341</td> <td>4211-01</td> </tr> </table>		PERFORMANCE CURVE NO.	TORQUE @ 1075 RPM (25°C)	APPROVED SAMPLE	UL COMPONENT FILE #	CCN #	CSA FILE #	CLASS #	C31088	19.2 OZ. FT.	PSE 7404	E46412	PRGY2	LR43341	4211-01	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>COLOR</th> <th>LENGTH</th> <th>TERMINAL OR STRIP LENGTH</th> </tr> <tr> <td>GREEN (GRD)</td> <td>9.0/11.0 [229/279]</td> <td>#10 EYELET</td> </tr> <tr> <td>BROWN/WHITE</td> <td>34.5/37.5 [876/940]</td> <td>.60[15.2] SKIN</td> </tr> <tr> <td>BROWN</td> <td>34.5/37.5 [876/940]</td> <td>.60[15.2] SKIN</td> </tr> <tr> <td>PURPLE</td> <td>34.5/37.5 [876/940]</td> <td>.60[15.2] SKIN</td> </tr> <tr> <td>BLACK</td> <td>34.5/37.5 [876/940]</td> <td>.60[15.2] SKIN</td> </tr> </table>		COLOR	LENGTH	TERMINAL OR STRIP LENGTH	GREEN (GRD)	9.0/11.0 [229/279]	#10 EYELET	BROWN/WHITE	34.5/37.5 [876/940]	.60[15.2] SKIN	BROWN	34.5/37.5 [876/940]	.60[15.2] SKIN	PURPLE	34.5/37.5 [876/940]	.60[15.2] SKIN	BLACK	34.5/37.5 [876/940]	.60[15.2] SKIN
PERFORMANCE CURVE NO.	TORQUE @ 1075 RPM (25°C)	APPROVED SAMPLE	UL COMPONENT FILE #	CCN #	CSA FILE #	CLASS #																													
C31088	19.2 OZ. FT.	PSE 7404	E46412	PRGY2	LR43341	4211-01																													
COLOR	LENGTH	TERMINAL OR STRIP LENGTH																																	
GREEN (GRD)	9.0/11.0 [229/279]	#10 EYELET																																	
BROWN/WHITE	34.5/37.5 [876/940]	.60[15.2] SKIN																																	
BROWN	34.5/37.5 [876/940]	.60[15.2] SKIN																																	
PURPLE	34.5/37.5 [876/940]	.60[15.2] SKIN																																	
BLACK	34.5/37.5 [876/940]	.60[15.2] SKIN																																	
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>GEOMETRIC CHARACTERISTICS &amp; SYMBOLS</th> <th>REGAL-BELOIT CORPORATION (RBC) PROVIDES TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN SEVERAL AREAS. SINCE RBC DOES NOT RECEIVE ALL DATA CONCERNING THE USE AND APPLICATION OF THE MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY THE CUSTOMER.</th> </tr> <tr> <td>                     ▽ FLATNESS                      - STRAIGHTNESS                      ∠ ANGULARITY                      ⊥ PERPENDICULARITY (SQUARENESS)                      ∥ PARALLELISM                      ○ ROUNDNESS (CIRCULARITY)                      ⌀ CYLINDRICITY                      ~ PROFILE OF ANY SURFACE                      ~ PROFILE OF ANY LINE                      † RUNOUT                      ● TRUE POSITION                      ⊙ CONCENTRICITY                      = SYMMETRY                 </td> <td>                     DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.                 </td> </tr> </table>		GEOMETRIC CHARACTERISTICS & SYMBOLS	REGAL-BELOIT CORPORATION (RBC) PROVIDES TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN SEVERAL AREAS. SINCE RBC DOES NOT RECEIVE ALL DATA CONCERNING THE USE AND APPLICATION OF THE MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY THE CUSTOMER.	▽ FLATNESS - STRAIGHTNESS ∠ ANGULARITY ⊥ PERPENDICULARITY (SQUARENESS) ∥ PARALLELISM ○ ROUNDNESS (CIRCULARITY) ⌀ CYLINDRICITY ~ PROFILE OF ANY SURFACE ~ PROFILE OF ANY LINE † RUNOUT ● TRUE POSITION ⊙ CONCENTRICITY = SYMMETRY	DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>DR BY: J. RUPERT</td> <td>02-02-1996</td> </tr> <tr> <td>APPD:</td> <td></td> </tr> <tr> <td>THIRD ANGLE PROJECTION</td> <td>EDS DATE 11-11-2011 FORMAT REV H</td> </tr> </table>		DR BY: J. RUPERT	02-02-1996	APPD:		THIRD ANGLE PROJECTION	EDS DATE 11-11-2011 FORMAT REV H																						
GEOMETRIC CHARACTERISTICS & SYMBOLS	REGAL-BELOIT CORPORATION (RBC) PROVIDES TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN SEVERAL AREAS. SINCE RBC DOES NOT RECEIVE ALL DATA CONCERNING THE USE AND APPLICATION OF THE MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY THE CUSTOMER.																																		
▽ FLATNESS - STRAIGHTNESS ∠ ANGULARITY ⊥ PERPENDICULARITY (SQUARENESS) ∥ PARALLELISM ○ ROUNDNESS (CIRCULARITY) ⌀ CYLINDRICITY ~ PROFILE OF ANY SURFACE ~ PROFILE OF ANY LINE † RUNOUT ● TRUE POSITION ⊙ CONCENTRICITY = SYMMETRY	DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.																																		
DR BY: J. RUPERT	02-02-1996																																		
APPD:																																			
THIRD ANGLE PROJECTION	EDS DATE 11-11-2011 FORMAT REV H																																		
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"><b>REGAL-BELOIT CORPORATION</b></td> </tr> <tr> <td colspan="2" style="text-align: center;">DESCRIPTION MODEL-RFHP-42FR OUTLINE</td> </tr> <tr> <td>SIZE C</td> <td>DWG NO 11704-004</td> </tr> <tr> <td>SCALE NONE</td> <td>SHEET 1</td> </tr> </table>		<b>REGAL-BELOIT CORPORATION</b>		DESCRIPTION MODEL-RFHP-42FR OUTLINE		SIZE C	DWG NO 11704-004	SCALE NONE	SHEET 1	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>ENCLOSURE</th> <th>CUST.</th> <th>DISTRIBUTION SERVICE</th> </tr> <tr> <td>                 MAIN FRAME - OLE OPEN                  END FRAME - OLE OPEN                  MAIN FRAME - LE OPEN                  END FRAME - LE OPEN             </td> <td></td> <td></td> </tr> </table>		ENCLOSURE	CUST.	DISTRIBUTION SERVICE	MAIN FRAME - OLE OPEN END FRAME - OLE OPEN MAIN FRAME - LE OPEN END FRAME - LE OPEN																				
<b>REGAL-BELOIT CORPORATION</b>																																			
DESCRIPTION MODEL-RFHP-42FR OUTLINE																																			
SIZE C	DWG NO 11704-004																																		
SCALE NONE	SHEET 1																																		
ENCLOSURE	CUST.	DISTRIBUTION SERVICE																																	
MAIN FRAME - OLE OPEN END FRAME - OLE OPEN MAIN FRAME - LE OPEN END FRAME - LE OPEN																																			

4	3	2	1																				
<p><b>INFORMACION GENERAL:</b></p> <p>OSCILACION DE FLECHA: -</p> <p>JUEGO AXIAL: -</p> <p>BALEROS: -</p> <p>POSICION DEL MONTAJE: -</p> <hr/> <p><b>INFORMACION ELECTRICA:</b></p> <p>PROTECTOR DE SOBRECARGA: -</p> <p>CABLES: -</p> <p>CABLE DE TIERRA: -</p>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>REVISION: ECO</td> <td>REVISADO POR: R.LIAN</td> <td>FECHA: 05-28-2012</td> <td>APROBADO POR: B.SHEN</td> <td>FECHA: 05-28-2012</td> </tr> <tr> <td>D</td> <td>0026379</td> <td></td> <td></td> <td></td> </tr> </table>		REVISION: ECO	REVISADO POR: R.LIAN	FECHA: 05-28-2012	APROBADO POR: B.SHEN	FECHA: 05-28-2012	D	0026379													
REVISION: ECO	REVISADO POR: R.LIAN	FECHA: 05-28-2012	APROBADO POR: B.SHEN	FECHA: 05-28-2012																			
D	0026379																						
<p><b>INFORMACION DE ETIQUETA:</b></p> <p>MODEL NO.: 322P757                  CUST. P/N: OWW6516                  HP: 1/5                  ROT.: REVERSIBLE                  RPM: 1075                  TYPE: FLL                  FRAME: 42Y                  VOLTS: 208-230                  PH: 1                  AMPS: 1.5                  HZ: 60                  INS.: B*                  AMB.: 40° C                  DUTY: AIR COVER                  CAP.: 7.5 MFD/370 V                  ENCL: -                  UL LOGO                  CSA LOGO                  THERMALLY PROTECTED TYPE C</p>																							
<p><b>DIAGRAMA DE CONEXION EXTRNA</b></p> <p>BRN ————</p> <p>BRN/WHT ————</p> <p>PUR ————</p> <p>BLACK ————</p> <p>BLACK ———— ROTATION ———— BLACK</p> <p>WHITE ———— CCWLE ———— WHITE</p> <p>BLACK ———— WHITE</p> <p>WHITE ———— BLACK</p> <p>————— CWLE</p>		<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>9.0/11.0</td> <td></td> </tr> <tr> <td>[229/279]</td> <td></td> </tr> <tr> <td>34.5/37.5</td> <td></td> </tr> <tr> <td>[876/940]</td> <td></td> </tr> <tr> <td>34.5/37.5</td> <td></td> </tr> <tr> <td>[876/940]</td> <td></td> </tr> <tr> <td>34.5/37.5</td> <td></td> </tr> <tr> <td>[876/940]</td> <td></td> </tr> <tr> <td>34.5/37.5</td> <td></td> </tr> <tr> <td>[876/940]</td> <td></td> </tr> </table>		9.0/11.0		[229/279]		34.5/37.5		[876/940]		34.5/37.5		[876/940]		34.5/37.5		[876/940]		34.5/37.5		[876/940]	
9.0/11.0																							
[229/279]																							
34.5/37.5																							
[876/940]																							
34.5/37.5																							
[876/940]																							
34.5/37.5																							
[876/940]																							
34.5/37.5																							
[876/940]																							
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>CURVAS DE FUNCIONAMIENTO</th> <th>TORQUE @ 110/75 RPM (25°C)</th> <th>MUESTRA APROBADA</th> <th>COMPONENTE UL</th> <th>CSA</th> </tr> <tr> <td>C31088</td> <td>19.2 OZ. FT.</td> <td>PSE 7404</td> <td>E46412 PRGY2</td> <td>LR43341 4211-01</td> </tr> </table>		CURVAS DE FUNCIONAMIENTO	TORQUE @ 110/75 RPM (25°C)	MUESTRA APROBADA	COMPONENTE UL	CSA	C31088	19.2 OZ. FT.	PSE 7404	E46412 PRGY2	LR43341 4211-01	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>CLIENTE</td> <td>DISTRIBUTION SERVICE</td> </tr> </table>		CLIENTE	DISTRIBUTION SERVICE								
CURVAS DE FUNCIONAMIENTO	TORQUE @ 110/75 RPM (25°C)	MUESTRA APROBADA	COMPONENTE UL	CSA																			
C31088	19.2 OZ. FT.	PSE 7404	E46412 PRGY2	LR43341 4211-01																			
CLIENTE	DISTRIBUTION SERVICE																						
<p><b>CARACTERISTICAS DE GEOMETRIA Y SIMBOLOS</b></p> <p>∠ PLANICIDAD</p> <p>— RECTITUD</p> <p>∠ ANGULARIDAD</p> <p>⊥ PERPENDICULARIDAD (A ESQUADRA)</p> <p>// PARALELISMO</p> <p>○ REDONDEZ (CIRCULARIDAD)</p> <p>∅ CILINDRICIDAD</p> <p>⊖ PERFIL DE CUALQUIER SUPERFICIE</p> <p>⊖ PERFIL DE CUALQUIER LINEA</p> <p>∠ VARIACION</p> <p>⊕ POSICION REAL</p> <p>⊙ CONCENRICIDAD</p> <p>≡ SIMETRIA</p> <p style="text-align: right;">ASME Y14.5M 1994</p>		<p>REGAL-BELOIT CORPORATION (RBC) PROVEE ASISTENCIA TECNICA A NUESTROS CLIENTES EN VARIAS AREAS. DESDE QUE RBC NO RECIBE TODOS LOS DATOS EN RELACION AL USO Y A LA APLICACION DEL MOTOR, LA APLICACION ADECUADA DEL MOTOR DEBE SER DETERMINADA POR EL CLIENTE.</p> <p>DIMENSIONES SIN TOLERANCIA SON DE REFERENCIA SOLAMENTE</p> <p>DIBUJADO POR: J. RUPERT</p> <p>02-02-1996</p> <p>APROBADO POR:</p> <p>TERCER ANGULO DE PROYECCION</p> <p>FECHA EDS: 11-11-2011</p> <p>REV. FORMATO: H</p> <p>CONFIDENCIAL: ESTE DIBUJO Y SU INFORMACION SON PROPIEDAD DE USO EXCLUSIVO Y CONFIDENCIAL DE REGAL-BELOIT CORPORATION. Y NO DEBERAN SER REVELADOS, DUPLICADOS, DISTRIBUIDOS O USARSE DE OTRA MANERA SIN EL CONSENTIMIENTO ESCRITO DE REGAL-BELOIT CORPORATION. -TODOS LOS DERECHOS RESERVADOS.</p>																					
<p>REGAL-BELOIT CORPORATION</p>		<p>DESCRIPCION: MODEL-RFHP-42FR OUTLINE</p> <p>TAMAÑO: C</p> <p>NUMERO DE DIBUJO: 11704-004</p> <p>ESCALA: NONE</p> <p>HOJA: 1</p>																					
4	3	2	1																				

<p>总技术要求: _____</p> <p>轴跳动: _____</p> <p>端部窜动量 _____</p> <p>安装位置: _____</p> <p>电气数据: _____</p> <p>过载保护: _____</p> <p>引线: _____</p> <p>接地线: _____</p>			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>版本</td> <td>ECO</td> <td>编制</td> <td>日期</td> <td>批准</td> <td>日期</td> </tr> <tr> <td>D</td> <td>0026379</td> <td>R.LIAN</td> <td>05-28-2012</td> <td>B.SHEN</td> <td>05-28-2012</td> </tr> </table>	版本	ECO	编制	日期	批准	日期	D	0026379	R.LIAN	05-28-2012	B.SHEN	05-28-2012																																																															
版本	ECO	编制	日期	批准	日期																																																																									
D	0026379	R.LIAN	05-28-2012	B.SHEN	05-28-2012																																																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:50%;">铭牌数据</th> <th style="width:50%;">外部数据线</th> </tr> <tr> <td>                     MODEL NO.: 322P757                      CUST. P/N: OWW6516                      HP: 1/5                      ROT.: REVERSIBLE                      RPM: 1075                      TYPE: FLL                      FRAME: 42Y                      VOLTS: 208-230                      PH: 1                      AMPS: 1.5                      HZ: 60                      INS.: B*                      AMB.: 40° C                      DUTY: AIR COVER                      CAP.: 7.5 MFD/370 V                      ENCL: -                      UL LOGO                      CSA LOGO                      THERMALLY PROTECTED TYPE C                 </td> <td> <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>BRN</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>BRN/WHT</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>PUR</td> <td>└───┘</td> <td>LINE</td> </tr> <tr> <td>BLACK</td> <td>└───┘</td> <td></td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>ROTATION</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td>WHITE</td> <td>┌───┐</td> <td>CCWLE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>WHITE</td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>WHITE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td></td> <td>└───┘</td> <td>CWLE</td> </tr> </table> </td> </tr> </table>	铭牌数据	外部数据线	MODEL NO.: 322P757 CUST. P/N: OWW6516 HP: 1/5 ROT.: REVERSIBLE RPM: 1075 TYPE: FLL FRAME: 42Y VOLTS: 208-230 PH: 1 AMPS: 1.5 HZ: 60 INS.: B* AMB.: 40° C DUTY: AIR COVER CAP.: 7.5 MFD/370 V ENCL: - UL LOGO CSA LOGO THERMALLY PROTECTED TYPE C	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>BRN</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>BRN/WHT</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>PUR</td> <td>└───┘</td> <td>LINE</td> </tr> <tr> <td>BLACK</td> <td>└───┘</td> <td></td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>ROTATION</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td>WHITE</td> <td>┌───┐</td> <td>CCWLE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>WHITE</td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>WHITE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td></td> <td>└───┘</td> <td>CWLE</td> </tr> </table>	BRN	┌───┐		BRN/WHT	┌───┐		PUR	└───┘	LINE	BLACK	└───┘		BLACK	┌───┐	ROTATION	WHITE	└───┘	BLACK	WHITE	┌───┐	CCWLE	WHITE	└───┘	WHITE	BLACK	┌───┐	WHITE	WHITE	└───┘	BLACK		└───┘	CWLE	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:20%;"></td> <td style="width:20%; text-align: center;">9.0/11.0 [229/279]</td> <td style="width:20%;"></td> <td style="width:20%;"></td> </tr> <tr> <td></td> <td style="text-align: center;">34.5/37.5 [876/940]</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">34.5/37.5 [876/940]</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">34.5/37.5 [876/940]</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">34.5/37.5 [876/940]</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">34.5/37.5 [876/940]</td> <td></td> <td></td> </tr> </table>		9.0/11.0 [229/279]				34.5/37.5 [876/940]				34.5/37.5 [876/940]				34.5/37.5 [876/940]				34.5/37.5 [876/940]				34.5/37.5 [876/940]			<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:20%;">性能曲线编号</td> <td style="width:20%;">TORQUE @ 1075 RPMs (25°C)</td> <td style="width:20%;">批准样品</td> <td style="width:20%;">UL部件</td> <td style="width:20%;">CSA</td> </tr> <tr> <td>C31088</td> <td>19.2 OZ. FT.</td> <td>PSE 7404</td> <td>文件号</td> <td>文件号 指南</td> </tr> <tr> <td></td> <td></td> <td></td> <td>E46412 PRGY2</td> <td>LR43341 4211-01</td> </tr> </table>	性能曲线编号	TORQUE @ 1075 RPMs (25°C)	批准样品	UL部件	CSA	C31088	19.2 OZ. FT.	PSE 7404	文件号	文件号 指南				E46412 PRGY2	LR43341 4211-01
铭牌数据	外部数据线																																																																													
MODEL NO.: 322P757 CUST. P/N: OWW6516 HP: 1/5 ROT.: REVERSIBLE RPM: 1075 TYPE: FLL FRAME: 42Y VOLTS: 208-230 PH: 1 AMPS: 1.5 HZ: 60 INS.: B* AMB.: 40° C DUTY: AIR COVER CAP.: 7.5 MFD/370 V ENCL: - UL LOGO CSA LOGO THERMALLY PROTECTED TYPE C	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>BRN</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>BRN/WHT</td> <td>┌───┐</td> <td></td> </tr> <tr> <td>PUR</td> <td>└───┘</td> <td>LINE</td> </tr> <tr> <td>BLACK</td> <td>└───┘</td> <td></td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>ROTATION</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td>WHITE</td> <td>┌───┐</td> <td>CCWLE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>WHITE</td> </tr> <tr> <td>BLACK</td> <td>┌───┐</td> <td>WHITE</td> </tr> <tr> <td>WHITE</td> <td>└───┘</td> <td>BLACK</td> </tr> <tr> <td></td> <td>└───┘</td> <td>CWLE</td> </tr> </table>	BRN	┌───┐		BRN/WHT	┌───┐		PUR	└───┘	LINE	BLACK	└───┘		BLACK	┌───┐	ROTATION	WHITE	└───┘	BLACK	WHITE	┌───┐	CCWLE	WHITE	└───┘	WHITE	BLACK	┌───┐	WHITE	WHITE	└───┘	BLACK		└───┘	CWLE																																												
BRN	┌───┐																																																																													
BRN/WHT	┌───┐																																																																													
PUR	└───┘	LINE																																																																												
BLACK	└───┘																																																																													
BLACK	┌───┐	ROTATION																																																																												
WHITE	└───┘	BLACK																																																																												
WHITE	┌───┐	CCWLE																																																																												
WHITE	└───┘	WHITE																																																																												
BLACK	┌───┐	WHITE																																																																												
WHITE	└───┘	BLACK																																																																												
	└───┘	CWLE																																																																												
	9.0/11.0 [229/279]																																																																													
	34.5/37.5 [876/940]																																																																													
	34.5/37.5 [876/940]																																																																													
	34.5/37.5 [876/940]																																																																													
	34.5/37.5 [876/940]																																																																													
	34.5/37.5 [876/940]																																																																													
性能曲线编号	TORQUE @ 1075 RPMs (25°C)	批准样品	UL部件	CSA																																																																										
C31088	19.2 OZ. FT.	PSE 7404	文件号	文件号 指南																																																																										
			E46412 PRGY2	LR43341 4211-01																																																																										
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:30%;">                 形位公差                  □ 平面度                  - 直线度                  &lt; 倾斜度                  ⊥ 垂直度                  // 平行度                  ○ 圆度                  ⊙ 圆跳动                  Ⓢ 面轮廓度                  Ⓡ 线轮廓度                  ↗ 圆跳动                  ↖ 位置度                  ⊕ 同轴度                  ≡ 对称度             </td> <td style="width:40%;">                 REGAL-BELOIT CORPORATION (RBC) 在个别领域为客户提供技术支持。鉴于RBC未收到任何涉及电机使用和应用环境的数据，电机的适用性由客户自己决定。                   未注公差尺寸仅供参考。             </td> <td style="width:30%;">                 绘图: J. RUPERT                  批准: _____                  第三角投影                  机密: 本图纸及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权，不得泄露、复制、传播或作其他用途。--版权所有             </td> </tr> </table>	形位公差 □ 平面度 - 直线度 < 倾斜度 ⊥ 垂直度 // 平行度 ○ 圆度 ⊙ 圆跳动 Ⓢ 面轮廓度 Ⓡ 线轮廓度 ↗ 圆跳动 ↖ 位置度 ⊕ 同轴度 ≡ 对称度	REGAL-BELOIT CORPORATION (RBC) 在个别领域为客户提供技术支持。鉴于RBC未收到任何涉及电机使用和应用环境的数据，电机的适用性由客户自己决定。  未注公差尺寸仅供参考。	绘图: J. RUPERT 批准: _____ 第三角投影 机密: 本图纸及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权，不得泄露、复制、传播或作其他用途。--版权所有	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:20%; text-align: center;"> </td> <td style="width:80%;"> <b>REGAL-BELOIT CORPORATION</b> </td> </tr> <tr> <td style="width:20%;"></td> <td style="width:80%;">                 名称: MODEL-RFHP-42FR OUTLINE             </td> </tr> <tr> <td style="width:20%;"></td> <td style="width:80%;">                 图幅: C 图号: 11704-004             </td> </tr> <tr> <td style="width:20%;">比例: NONE</td> <td style="width:80%;">页号: 1</td> </tr> </table>		<b>REGAL-BELOIT CORPORATION</b>		名称: MODEL-RFHP-42FR OUTLINE		图幅: C 图号: 11704-004	比例: NONE	页号: 1																																																																		
形位公差 □ 平面度 - 直线度 < 倾斜度 ⊥ 垂直度 // 平行度 ○ 圆度 ⊙ 圆跳动 Ⓢ 面轮廓度 Ⓡ 线轮廓度 ↗ 圆跳动 ↖ 位置度 ⊕ 同轴度 ≡ 对称度	REGAL-BELOIT CORPORATION (RBC) 在个别领域为客户提供技术支持。鉴于RBC未收到任何涉及电机使用和应用环境的数据，电机的适用性由客户自己决定。  未注公差尺寸仅供参考。	绘图: J. RUPERT 批准: _____ 第三角投影 机密: 本图纸及相关信息所有权归REGAL-BELOIT CORPORATION。未经REGAL-BELOIT CORPORATION书面授权，不得泄露、复制、传播或作其他用途。--版权所有																																																																												
	<b>REGAL-BELOIT CORPORATION</b>																																																																													
	名称: MODEL-RFHP-42FR OUTLINE																																																																													
	图幅: C 图号: 11704-004																																																																													
比例: NONE	页号: 1																																																																													