

SAFETY DATA SHEET

1. Product and Company Identification

| | |
|--------------------------------------|---|
| Product identifier | Degreasing Solvent LV (4083-83) |
| Other means of identification | Not available |
| Recommended use | Degreaser |
| Recommended restrictions | None known. |
| Manufacturer | Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC) |

2. Hazards Identification

| | | |
|------------------------------|---|-----------------------------|
| Physical hazards | Flammable aerosols | Category 1 |
| | Gases under pressure | Liquefied gas |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2 |
| | Reproductive toxicity (the unborn child) | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



Signal word Danger

Hazard statement Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness. Suspected of damaging the unborn child.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Do not breathe gas. Use only outdoors or in a well-ventilated area.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Specific treatment (see this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
If exposed or concerned: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/Information on Ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|--------------------------------------|--------------------------|-------------|-------|
| Acetone | | 67-64-1 | 81-83 |
| Heptane | | 142-82-5 | 8-10 |
| Heptane, Branched, Cyclic And Linear | | 426260-76-6 | 8-10 |
| Carbon dioxide | | 124-38-9 | 7-9 |
| Toluene | | 108-88-3 | 0.1-1 |

4. First Aid Measures

| | |
|---|--|
| Inhalation | If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. |
| Skin contact | If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. |
| Eye contact | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Ingestion | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. |
| Most important symptoms/effects, acute and delayed | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause drowsiness or dizziness. May cause redness and pain. Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wear suitable protective clothing. |

5. Fire Fighting Measures

| | |
|--|--|
| Suitable extinguishing media | Powder. Alcohol resistant foam. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire-fighting equipment/instructions | Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. |
| Hazardous combustion products | May include and are not limited to: Oxides of carbon. |
| Explosion data | |
| Sensitivity to mechanical impact | Not available. |
| Sensitivity to static discharge | Not available. |

6. Accidental Release Measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|---|

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike far ahead of spill for later disposal. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe gas. Avoid contact during pregnancy/while nursing. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use personal protective equipment as required. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Contents under pressure. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Avoid exposure to long periods of sunlight. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value |
|-------------------------------|------|------------|
| Acetone (CAS 67-64-1) | PEL | 2400 mg/m3 |
| | | 1000 ppm |
| Carbon dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 |
| | | 5000 ppm |
| Heptane (CAS 142-82-5) | PEL | 2000 mg/m3 |
| | | 500 ppm |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|------------------------|---------|---------|
| Toluene (CAS 108-88-3) | Ceiling | 300 ppm |
| | TWA | 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|-------------------------------|------|-----------|
| Acetone (CAS 67-64-1) | STEL | 750 ppm |
| | TWA | 500 ppm |
| Carbon dioxide (CAS 124-38-9) | STEL | 30000 ppm |
| | TWA | 5000 ppm |
| Heptane (CAS 142-82-5) | STEL | 500 ppm |
| | TWA | 400 ppm |
| Toluene (CAS 108-88-3) | TWA | 20 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|-------------------------------|------|-------------|
| Acetone (CAS 67-64-1) | TWA | 590 mg/m3 |
| | | 250 ppm |
| Carbon dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|------------------------|---------|------------|
| Heptane (CAS 142-82-5) | | 30000 ppm |
| | TWA | 9000 mg/m3 |
| | | 5000 ppm |
| Toluene (CAS 108-88-3) | Ceiling | 1800 mg/m3 |
| | | 440 ppm |
| | TWA | 350 mg/m3 |
| Toluene (CAS 108-88-3) | | 85 ppm |
| | STEL | 560 mg/m3 |
| | | 150 ppm |
| | TWA | 375 mg/m3 |
| | | 100 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------|-----------|---------------------------|---------------------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone | Urine | * |
| Toluene (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not applicable.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

| | |
|--|---------------------|
| Appearance | Clear |
| Physical state | Gas. |
| Form | Aerosol |
| Color | Colorless |
| Odor | Solvent |
| Odor threshold | Not available. |
| pH | Not applicable |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Pour point | Not available. |
| Specific gravity | 0.770 (Concentrate) |
| Partition coefficient (n-octanol/water) | Not available. |
| Flash point | Not available. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |

Upper/lower flammability or explosive limits

| | |
|---------------------------------------|---------------------------|
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 65 - 75 psig @ 70°F |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | Partial |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | < 20.5 mm ² /s |
| Other information | |
| Flame extension | > 150 cm |
| Flammability (flash back) | Yes |
| Heat of combustion | 29.3 kJ/g |
| VOC (Weight %) | 9.7 % |

10. Stability and Reactivity

| | |
|---|---|
| Reactivity | Do not mix with other chemicals. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Chemical stability | Material is stable under normal conditions. |
| Conditions to avoid | Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. Acids. |
| Hazardous decomposition products | May include and are not limited to: Oxides of carbon. |

11. Toxicological Information

| | |
|---|--|
| Routes of exposure | Inhalation. Ingestion. Skin contact. Eye contact. |
| Information on likely routes of exposure | |
| Ingestion | Expected to be a low ingestion hazard. |
| Inhalation | Prolonged inhalation may be harmful. Narcotic effects. |
| Skin contact | Causes skin irritation. |
| Eye contact | Causes serious eye irritation. Direct contact with eyes may cause temporary irritation. |
| Symptoms related to the physical, chemical and toxicological characteristics | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. |

Information on toxicological effects

Acute toxicity Narcotic effects.

| Components | Species | Test Results |
|-----------------------|----------------|--|
| Acetone (CAS 67-64-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 15800 mg/kg 20 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 44000 mg/m ³ /4H |
| | Rat | 76 mg/l, 4 Hours 50.1 mg/l, 8 Hours 39 mg/l/4h |
| <i>Oral</i> | | |
| LD50 | Human | 2857 mg/kg |

| Components | Species | Test Results |
|--|--------------------------------|--|
| | Mouse | 3000 mg/kg |
| | Rabbit | 5340 mg/kg |
| | Rat | 5800 mg/kg |
| Carbon dioxide (CAS 124-38-9) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Not available | |
| Heptane (CAS 142-82-5) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Rat | 103 mg/l, 4 Hours |
| LD50 | Mouse | 75 mg/l, 2 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | 15000 mg/kg |
| Heptane, Branched, Cyclic And Linear (CAS 426260-76-6) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Not available | |
| Toluene (CAS 108-88-3) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 12196 mg/kg, Sigma 12125 mg/kg 8390 mg/kg 14.1 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 7100 mg/l, 4 Hours 5320 ppm, 8 Hours 400 ppm, 24 Hours |
| | Rat | 26700 ppm, 1 Hours <= 28800 mg/m ³ , 4 Hours, Sigma 12200 ppm, 2 Hours 8000 ppm, 4 Hours 12.5 mg/l/4h |
| LD50 | Rat | > 5580 mg/kg, Sigma 636 mg/kg |
| Skin corrosion/irritation | Causes skin irritation. | |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |

| | |
|---|--|
| Conjunctival oedema value | Not available. |
| Recover days | Not available. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not available. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, NTP, or OSHA. |
| ACGIH Carcinogens | |
| Acetone (CAS 67-64-1) | A4 Not classifiable as a human carcinogen. |
| Toluene (CAS 108-88-3) | A4 Not classifiable as a human carcinogen. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| Toluene (CAS 108-88-3) | Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans. |
| US - California Proposition 65 - CRT: Listed date/Carcinogenic substance | |
| Benzene (CAS 71-43-2) | Carcinogenic. |
| Benzene, ethyl- (CAS 100-41-4) | Carcinogenic. |
| Reproductive toxicity | Suspected of damaging the unborn child. |
| Teratogenicity | Toluene (benzene, methyl-) has caused fetotoxicity (reduced fetal weight), behavioural effects (effects on learning and memory) and hearing loss (in males). These effects have been observed in the offspring of rats exposed by inhalation to 1200 or 1800 ppm toluene. These effects were observed in the absence of maternal toxicity. |
| Specific target organ toxicity - single exposure | Narcotic effects. |
| Specific target organ toxicity - repeated exposure | Not applicable. |
| Aspiration hazard | Not likely, due to the form of the product. |
| Chronic effects | Prolonged inhalation may be harmful. |
| Further information | Not available. |
| Name of Toxicologically Synergistic Products | Not available. |

12. Ecological Information

| | | | |
|--------------------------------------|--|--|----------------------------|
| Ecotoxicity | See below | | |
| Components | | Species | Test Results |
| Acetone (CAS 67-64-1) | | | |
| Crustacea | EC50 | Daphnia | 13999 mg/L, 48 Hours |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 21.6 - 23.9 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 4740 - 6330 mg/l, 96 hours |
| Heptane (CAS 142-82-5) | | | |
| Aquatic | | | |
| Fish | LC50 | Mozambique tilapia (Tilapia mossambica) | 375 mg/l, 96 hours |
| Toluene (CAS 108-88-3) | | | |
| Algae | IC50 | Algae | 433 mg/L, 72 Hours |
| Crustacea | EC50 | Daphnia | 7.645 mg/L, 48 Hours |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Coho salmon, silver salmon (Oncorhynchus kisutch) | 8.11 mg/l, 96 hours |
| Persistence and degradability | No data is available on the degradability of this product. | | |
| Bioaccumulative potential | No data available. | | |
| Mobility in soil | No data available. | | |

| | |
|------------------------------|---|
| Mobility in general | Not available. |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

13. Disposal Considerations

| | |
|--|--|
| Disposal instructions | Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| US RCRA Hazardous Waste U List: Reference | |
| Acetone (CAS 67-64-1) | U002 |
| Toluene (CAS 108-88-3) | U220 |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. |

14. Transport Information

U.S. Department of Transportation (DOT)

Basic shipping requirements:

| | |
|-----------------------------|-----------------------|
| UN number | UN1950 |
| Proper shipping name | Aerosols, flammable |
| Hazard class | Limited Quantity - US |
| Special provisions | N82 |
| Packaging exceptions | 306 |

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

| | |
|-----------------------------|---------------------------|
| UN number | UN1950 |
| Proper shipping name | AEROSOLS, flammable |
| Hazard class | Limited Quantity - Canada |
| Special provisions | 80 |

IATA/ICAO (Air)

Basic shipping requirements:


| | |
|-----------------------------|-------------------------|
| UN number | UN1950 |
| Proper shipping name | Aerosols, flammable |
| Hazard class | Limited Quantity - IATA |

IMDG (Marine Transport)

Basic shipping requirements:

| | |
|-----------------------------|-----------------------|
| UN number | UN1950 |
| Proper shipping name | AEROSOLS, flammable |
| Hazard class | Limited Quantity - US |

DOT; IMDG; TDG





15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada CEPA Schedule I: Listed substance

Carbon dioxide (CAS 124-38-9) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Heptane (CAS 142-82-5) 1 TONNES

Toluene (CAS 108-88-3) 1 TONNES

Canada WHMIS Ingredient Disclosure: Threshold limits

Acetone (CAS 67-64-1) 1 %

Carbon dioxide (CAS 124-38-9) 1 %

Heptane (CAS 142-82-5) 1 %

Toluene (CAS 108-88-3) 1 %

WHMIS status Controlled

WHMIS classification Class A - Compressed Gas, Class B - Division 5 - Flammable Aerosol, Class D - Division 2A, 2B

WHMIS labeling



US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Toluene (CAS 108-88-3) 1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Toluene (CAS 108-88-3) Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US CWA Section 311 Hazardous Substances: Listed substance

Toluene (CAS 108-88-3) Listed.

US CWA Section 307(a)(1) Toxic Pollutants: Listed substance

Toluene (CAS 108-88-3) Listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.

Heptane (CAS 142-82-5) Listed.

Toluene (CAS 108-88-3) Listed.

US – CAA Mandatory Reporting of GHGs: Global warming potential (100 year)

Carbon dioxide (CAS 124-38-9) 1

US CAA Section 111 Volatile Organic Compounds: Listed substance

Acetone (CAS 67-64-1) Listed.

Toluene (CAS 108-88-3) Listed.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3) Listed.

US CAA Section 612 SNAP Program: Listed substance

Acetone (CAS 67-64-1) Listed.

Carbon dioxide (CAS 124-38-9) Listed.

US CAA VOCs with Negligible Photochemical Activity: Listed substance

Acetone (CAS 67-64-1) Listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Acetone (CAS 67-64-1) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2) Listed.
Benzene, ethyl- (CAS 100-41-4) Listed.
Toluene (CAS 108-88-3) Listed.

US - Illinois Chemical Safety Act: Listed substance

Acetone (CAS 67-64-1) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - Louisiana Spill Reporting: Listed substance

Acetone (CAS 67-64-1) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - Michigan Critical Materials Register: Parameter number

Toluene (CAS 108-88-3) 00108-88-3 Listed.

US - Minnesota Haz Subs: Listed substance

Acetone (CAS 67-64-1) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - New Jersey RTK - Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - New York Release Reporting: Hazardous Substances: Listed substance

Acetone (CAS 67-64-1) Listed.
Toluene (CAS 108-88-3) Listed.

US - North Carolina Toxic Air Pollutants: Listed substance

Toluene (CAS 108-88-3) Listed.

US - Texas Effects Screening Levels: Listed substance

Acetone (CAS 67-64-1) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US - Washington Chemical of High Concern to Children: Listed substance

Toluene (CAS 108-88-3) Listed.

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Listed.
Carbon dioxide (CAS 124-38-9) Listed.
Heptane (CAS 142-82-5) Listed.
Toluene (CAS 108-88-3) Listed.

US. Pennsylvania RTK - Hazardous Substances

| | |
|-------------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Carbon dioxide (CAS 124-38-9) | Listed. |
| Heptane (CAS 142-82-5) | Listed. |
| Toluene (CAS 108-88-3) | Listed. |

US. Rhode Island RTK

| | |
|------------------------|---------|
| Acetone (CAS 67-64-1) | Listed. |
| Toluene (CAS 108-88-3) | Listed. |

Inventory status


| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

| LEGEND | |
|----------|---|
| Severe | 4 |
| Serious | 3 |
| Moderate | 2 |
| Slight | 1 |
| Minimal | 0 |

| | |
|---------------------|-----|
| HEALTH | / 2 |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 1 |
| PERSONAL PROTECTION | X |

**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 05-December-2014

Effective date 01-December-2014

Expiry date 01-December-2017

Further information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by Nu-Calgon Technical Service Phone: (314) 469-7000

Other information This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).