

# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Food Grade Silicone (4084-03)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Lubricant
<b>Recommended restrictions</b>	None known.
<b>Manufacturer</b>	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		



<b>Signal word</b>	Danger
<b>Hazard statement</b>	Contains gas under pressure; may explode if heated. Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

**Precautionary statement**

<b>Prevention</b>	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection. Avoid breathing gas. Use only outdoors or in a well-ventilated area.
<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Keep container tightly closed.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Not applicable.

## 3. Composition/Information on Ingredients

**Mixture**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	15 - 40

Chemical name	Common name and synonyms	CAS number	%
Heptane		142-82-5	15 - 40
Butane		106-97-8	10 - 30
Propane		74-98-6	1 - 5
Siloxanes and Silicones, dimethyl-		63148-62-9	1 - 5

**Composition comments** US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

#### 4. First Aid Measures

<b>Inhalation</b>	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
<b>Skin contact</b>	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see product label).
<b>Eye contact</b>	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause drowsiness or dizziness. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Do not puncture or incinerate container. Do not store at temperatures above 49°C. Keep away from sources of ignition. No smoking.

#### 5. Fire Fighting Measures

<b>Suitable extinguishing media</b>	Powder. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out. Firefighters should wear a self-contained breathing apparatus.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters should wear full protective clothing including self contained breathing apparatus.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	Not available.
<b>Sensitivity to static discharge</b>	Not available.

#### 6. Accidental Release Measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

---

## 7. Handling and Storage

---

**Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only with adequate ventilation. Avoid breathing gas. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children. Do not store at temperatures above 49 °C (120.2°F).

---

## 8. Exposure Controls/Personal Protection

---

**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3
		1000 ppm
Heptane (CAS 142-82-5)	PEL	2000 mg/m3
		500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
	STEL	500 ppm
Heptane (CAS 142-82-5)	TWA	400 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
	TWA	350 mg/m3
Propane (CAS 74-98-6)		85 ppm
	TWA	1800 mg/m3
		1000 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields.
<b>Skin protection</b>	
<b>Hand protection</b>	Rubber gloves. Confirm with a reputable supplier first.
<b>Other</b>	Wear appropriate chemical resistant clothing. As required by employer code.
<b>Respiratory protection</b>	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
<b>Thermal hazards</b>	Not applicable.
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

---

## 9. Physical and Chemical Properties

---

<b>Appearance</b>	Clear
<b>Physical state</b>	Gas.
<b>Form</b>	Spray
<b>Color</b>	Colorless
<b>Odor</b>	Petroleum
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	0.751
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	> 1 (Water = 1)
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	23 33 psig @ 70°F
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	< 20.5 cm <sup>2</sup> /s
<b>Other information</b>	
<b>Flame projection</b>	> 18 in
<b>Heat of combustion</b>	39.8 kJ/g
<b>VOC (Weight %)</b>	59.2 % (Us Federal/CARB/OTC/LADCO)

---

## 10. Stability and Reactivity

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Stable under recommended storage conditions.

**Conditions to avoid**

Do not mix with other chemicals. Aerosol containers are unstable at temperatures above 49°C (120.2°F).

**Incompatible materials**

Strong oxidizing agents. Acids. Nitrates. Fluorine. Chlorine.

**Hazardous decomposition products**

May include and are not limited to: Oxides of carbon.

---

## 11. Toxicological Information

---

**Routes of exposure**

Eye, Skin contact, Inhalation, Ingestion.

**Information on likely routes of exposure****Ingestion**

May be fatal if swallowed and enters airways.

**Inhalation**

May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects.

**Skin contact**

Causes skin irritation.

**Eye contact**

Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Information on toxicological effects****Acute toxicity**

May be fatal if swallowed and enters airways. Narcotic effects.

**Components****Species****Test Results**

Acetone (CAS 67-64-1)

**Acute***Dermal*

LD50

Rabbit

15800 mg/kg

20 ml/kg

*Inhalation*

LC50

Mouse

44000 mg/m<sup>3</sup>/4H

Rat

76 mg/l, 4 Hours

50.1 mg/l, 8 Hours

39 mg/l/4h

*Oral*

LD50

Human

2857 mg/kg

Mouse

3000 mg/kg

Rabbit

5340 mg/kg

Rat

5800 mg/kg

Butane (CAS 106-97-8)

**Acute***Inhalation*

LC50

Mouse

680 mg/l, 2 Hours

Rat

276000 ppm, 4 Hours

658 mg/l/4h

*Oral*

LD50

Not available

Heptane (CAS 142-82-5)

**Acute***Inhalation*

LC50

Rat

103 mg/l, 4 Hours

LD50

Mouse

75 mg/l, 2 Hours

*Oral*

LD50

Rat

15000 mg/kg

Propane (CAS 74-98-6)

**Acute***Inhalation*

LC50

Rat

&gt; 1442.8 mg/l, 15 Minutes

Components	Species	Test Results
<i>Oral</i> LD50	Not available	
Siloxanes and Silicones, dimethyl- (CAS 63148-62-9)		
<b>Acute</b>		
<i>Dermal</i> LD50	Rabbit	> 2000 mg/kg
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Rat	> 17000 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not available.	
<b>Skin sensitization</b>	Prolonged or repeated exposure can cause drying, defatting and dermatitis.	
<b>Germ cell mutagenicity</b>	Non-hazardous by WHMIS/OSHA criteria.	
<b>Mutagenicity</b>	Non-hazardous by WHMIS/OSHA criteria.	
<b>Carcinogenicity</b>	Non-hazardous by WHMIS/OSHA criteria.	
<b>ACGIH Carcinogens</b>		
Acetone (CAS 67-64-1)	A4 Not classifiable as a human carcinogen.	
<b>Reproductive toxicity</b>	Non-hazardous by WHMIS/OSHA criteria.	
<b>Teratogenicity</b>	Non-hazardous by WHMIS/OSHA criteria.	
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.	
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful.	
<b>Further information</b>	Not available.	
<b>Name of Toxicologically Synergistic Products</b>	Not available.	

## 12. Ecological Information

Ecotoxicity	See below		
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

Components	Species	Test Results
Heptane (CAS 142-82-5) <b>Aquatic</b>		
Fish	LC50 Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Siloxanes and Silicones, dimethyl- (CAS 63148-62-9) <b>Aquatic</b>		
Fish	LC50 Channel catfish (Ictalurus punctatus)	2.36 - 4.15 mg/l, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.	
<b>Bioaccumulative potential</b>	No data available.	
<b>Mobility in soil</b>	No data available.	
<b>Mobility in general</b>	Not available.	
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

### 13. Disposal Considerations

<b>Disposal instructions</b>	Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>US RCRA Hazardous Waste U List: Reference</b>	
Acetone (CAS 67-64-1)	U002
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

### 14. Transport Information

#### U.S. Department of Transportation (DOT)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Hazard class</b>	Limited Quantity - US

#### Transportation of Dangerous Goods (TDG - Canada)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	Limited Quantity - Canada

#### IATA/ICAO (Air)

##### Basic shipping requirements:


<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	Limited Quantity - IATA

#### IMDG (Marine Transport)

##### Basic shipping requirements:

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS
<b>Hazard class</b>	Limited Quantity - IMDG

DOT; IMDG; TDG



IATA



---

## 15. Regulatory Information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**Canada DSL Challenge Substances: Listed substance**

Butane (CAS 106-97-8) Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Butane (CAS 106-97-8) 1 TONNES

Heptane (CAS 142-82-5) 1 TONNES

Propane (CAS 74-98-6) 1 TONNES

**Canada WHMIS Ingredient Disclosure: Threshold limits**

Acetone (CAS 67-64-1) 1 %

Butane (CAS 106-97-8) 1 %

Heptane (CAS 142-82-5) 1 %

**WHMIS status** Controlled

**WHMIS classification** Class A - Compressed Gas, Class B - Division 5 - Flammable Aerosol, Class D - Division 2B

**WHMIS labeling**



**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1) Listed.

Butane (CAS 106-97-8) Listed.

Heptane (CAS 142-82-5) Listed.

Propane (CAS 74-98-6) Listed.

**US CAA Section 111 Volatile Organic Compounds: Listed substance**

Acetone (CAS 67-64-1) Listed.

**US CAA Section 112(r) Accidental Release Prevention - Regulated Flammable Substance: Listed substance**

Butane (CAS 106-97-8) Regulated flammable substance.

Propane (CAS 74-98-6) Regulated flammable substance.

**US CAA Section 112(r) Accidental Release Prevention: Threshold quantity**

Butane (CAS 106-97-8) 10000 LBS

Propane (CAS 74-98-6) 10000 LBS

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8) Listed.

Propane (CAS 74-98-6) Listed.



**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**US CAA Section 612 SNAP Program: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Propane (CAS 74-98-6) Listed.

**US CAA VOCs with Negligible Photochemical Activity: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Siloxanes and Silicones, dimethyl- (CAS 63148-62-9) Listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**  
Not regulated.

**Other federal regulations**

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations** This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**US - California Hazardous Substances (Director's): Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Not listed.

**US - Illinois Chemical Safety Act: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.  
Propane (CAS 74-98-6) Listed.

**US - Louisiana Spill Reporting: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.  
Propane (CAS 74-98-6) Listed.

**US - Minnesota Haz Subs: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.  
Propane (CAS 74-98-6) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.  
Propane (CAS 74-98-6) Listed.

**US - New York Release Reporting: Hazardous Substances: Listed substance**

Acetone (CAS 67-64-1) Listed.

**US - Texas Effects Screening Levels: Listed substance**

Acetone (CAS 67-64-1) Listed.  
Butane (CAS 106-97-8) Listed.  
Heptane (CAS 142-82-5) Listed.  
Propane (CAS 74-98-6) Listed.  
Siloxanes and Silicones, dimethyl- (CAS 63148-62-9) Listed.

**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1) Listed.  
 Butane (CAS 106-97-8) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Propane (CAS 74-98-6) Listed.

**US. Pennsylvania RTK - Hazardous Substances**

Acetone (CAS 67-64-1) Listed.  
 Butane (CAS 106-97-8) Listed.  
 Heptane (CAS 142-82-5) Listed.  
 Propane (CAS 74-98-6) Listed.

**US. Rhode Island RTK**

Acetone (CAS 67-64-1) Listed.  
 Butane (CAS 106-97-8) Listed.  
 Propane (CAS 74-98-6) Listed.

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other Information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	/ 2
<b>FLAMMABILITY</b>	3
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X



**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

02-March-2015

**Effective date**

01-March-2015

**Expiry date**

01-March-2018

**Further information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

**Prepared by**

Nu-Calgon Technical Service Phone: (314) 469-7000

**Other information**

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).  
 This SDS conforms to the ANSI Z400.1/Z129.1-2010 Standard.