

# SAFETY DATA SHEET

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Stainless Steel Cleaner (4084-75)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Stainless Steel Cleaner
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
<b>Supplier</b>	See above.

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Sensitization, skin	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
May be fatal if swallowed and enters airways.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.  
May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement**

<b>Prevention</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Use only outdoors or in a well-ventilated area.
<b>Response</b>	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
<b>Storage</b>	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

**WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)** None known

**WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)** None known

**Hazard(s) not otherwise classified (HNOC)** None known.

---

### 3. Composition/Information on Ingredients

---

**Mixture**

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), light hydrotreated		64742-47-8	60-100
Distillates (petroleum), straight-run middle		64741-44-2	10-30
Propane		74-98-6	7-13
Butane		106-97-8	1-5
d-Limonene		5989-27-5	0.1-1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

---

### 4. First Aid Measures

---

<b>Inhalation</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse.
<b>Eye contact</b>	Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

---

### 5. Fire Fighting Measures

---

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Not available.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

---

## 6. Accidental Release Measures

---

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Dike far ahead of spill for later disposal. Scoop up used absorbent into drums or other appropriate container. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

---

## 7. Handling and Storage

---

### Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

### Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Stored containers should be periodically checked for general condition and leakage. Keep out of reach of children.

---

## 8. Exposure Controls/Personal Protection

---

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Butane (CAS 106-97-8)	TWA	1000 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Vapor.
Propane (CAS 74-98-6)	TWA	1000 ppm	

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Butane (CAS 106-97-8)	STEL	750 ppm	
	TWA	600 ppm	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	200 mg/m3	Non-aerosol.
Propane (CAS 74-98-6)	TWA	1000 ppm	

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

---

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Butane (CAS 106-97-8)	TWA	800 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)	TWA	100 mg/m3
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
d-Limonene (CAS 5989-27-5)	TWA	165.5 mg/m3 30 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Exposure guidelines****Canada - Alberta OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Impervious gloves. Confirm with reputable supplier first.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

---

**9. Physical and Chemical Properties**

---

<b>Appearance</b>	Aerosol.
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol.
<b>Color</b>	Colorless
<b>Odor</b>	Lemon
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	0.821 (liquid)
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	-156.0 °F (-104.4 °C) (Propellant)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	35 - 55 psi (20°F) 75 - 95 psi (130°F)
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	< 25 cps
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Flame projection</b>	12 in
<b>Flammability (flash back)</b>	Yes
<b>Heat of combustion</b>	37.89 kJ/g
<b>Oxidizing properties</b>	Not oxidizing.

---

**10. Stability and Reactivity**

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Heat, open flames, static discharge, sparks and other ignition sources. Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

## 11. Toxicological Information

**Routes of exposure** Eye, Skin contact, Inhalation, Ingestion.

**Information on likely routes of exposure**

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

**Inhalation** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

**Skin contact** May cause an allergic skin reaction.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Diarrhea. May cause an allergic skin reaction. Dermatitis. Rash.

**Information on toxicological effects**

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects. May cause an allergic skin reaction.

Components	Species	Test Results
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	680 mg/L, 2 Hours
	Rat	276000 ppm, 4 Hours
		658 mg/l/4h
<i>Oral</i>		
LD50	Not available	
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Cat	> 6.4 mg/L, 6 Hours
	Rat	> 7.5 mg/L, 6 Hours
		> 4.3 mg/L, 4 Hours
		> 0.1 mg/L, 8 Hours
		5.2 mg/l/4h
<i>Oral</i>		
LD50	Rat	> 20000 mg/kg
		> 5000 mg/kg
Distillates (petroleum), straight-run middle (CAS 64741-44-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	1.8 mg/l/4h
		1.7 mg/L, 4 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
d-Limonene (CAS 5989-27-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg

Components	Species	Test Results
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Mouse	5600 mg/kg
	Rat	4400 mg/kg
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours > 800000 ppm, 10 Minutes, ECHA > 1464 mg/L, 15 Minutes, HSDB 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i> LD50	Not available	
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	See below.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Distillates (petroleum), straight-run middle (CAS 64741-44-2)	Volume 45 - 3	Not classifiable as to carcinogenicity to humans.
d-Limonene (CAS 5989-27-5)	Volume 73 - 3	Not classifiable as to carcinogenicity to humans.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Not listed.		
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.	
<b>Teratogenicity</b>	Not available.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.	

<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

---

## 12. Ecological Information

---

**Ecotoxicity** See below

**Ecotoxicological data**

Components	Species	Test Results
Distillates (petroleum), light hydrotreated (CAS 64742-47-8)		
<b>Aquatic</b>		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2.9 mg/L, 96 hours
d-Limonene (CAS 5989-27-5)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia pulex)	69.6 mg/L, 48 hours
Fish	LC50 Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/L, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Mobility in soil** No data available.

**Mobility in general** Not available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

## 13. Disposal Considerations

---

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

---

## 14. Transport Information

---

**Transport of Dangerous Goods (TDG) Proof of Classification** In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Hazard class</b>	Limited Quantity - US
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	Limited Quantity - Canada
<b>Special provisions</b>	80, 107
<b>Packaging exceptions</b>	<1L - Limited Quantity

**IATA/ICAO (Air)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
------------------	--------



**Proper shipping name** Aerosols, flammable  
**Hazard class** Limited Quantity - IATA  
**ERG code** 10L

**IMDG (Marine Transport)**

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** AEROSOLS  
**Hazard class** Limited Quantity - IMDG

**DOT; IMDG; TDG**



**IATA**



---

## 15. Regulatory Information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada DSL Challenge Substances: Listed substance**

Butane (CAS 106-97-8) Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/identification Number**

Butane (CAS 106-97-8) 1 TONNES  
Distillates (petroleum), light hydrotreated (CAS 64742-47-8) 1 TONNES  
d-Limonene (CAS 5989-27-5) 1 TONNES  
Propane (CAS 74-98-6) 1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

Not listed.

**Precursor Control Regulations**

Not regulated.

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Butane (CAS 106-97-8) Listed.  
Propane (CAS 74-98-6) Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No  
**SARA 311/312 Hazardous chemical** No  
**SARA 313 (TRI reporting)**  
 Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)

**US state regulations** See below

**US - California Hazardous Substances (Director's): Listed substance**

Butane (CAS 106-97-8) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)

**US - Louisiana Spill Reporting: Listed substance**

Butane (CAS 106-97-8) Listed.  
 Propane (CAS 74-98-6) Listed.

**US - Minnesota Haz Subs: Listed substance**

Butane (CAS 106-97-8) Listed.  
 Propane (CAS 74-98-6) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)

**US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant**

Propane (CAS 74-98-6)

**US - Texas Effects Screening Levels: Listed substance**

Butane (CAS 106-97-8) Listed.  
 Distillates (petroleum), light hydrotreated (CAS 64742-47-8) Listed.  
 Distillates (petroleum), straight-run middle (CAS 64741-44-2) Listed.  
 d-Limonene (CAS 5989-27-5) Listed.  
 Propane (CAS 74-98-6) Listed.

**US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8)  
 Distillates (petroleum), light hydrotreated (CAS 64742-47-8)  
 Propane (CAS 74-98-6)

**US. New Jersey Worker and Community Right-to-Know Act**

Butane (CAS 106-97-8)  
 Distillates (petroleum), light hydrotreated (CAS 64742-47-8)  
 Propane (CAS 74-98-6)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Butane (CAS 106-97-8)  
 Distillates (petroleum), light hydrotreated (CAS 64742-47-8)  
 Propane (CAS 74-98-6)

**US. Rhode Island RTK**

Butane (CAS 106-97-8)  
 Propane (CAS 74-98-6)

**US. California Proposition 65**

Not Listed.

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## 16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

02-March-2017

### Version #

01

### Effective date

02-March-2017

### Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

### Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.