

# SAFETY DATA SHEET

## 1. Product and Company Identification

**Product identifier** Evap Foam No Rinse-Aerosol (4171-75)  
**Other means of identification** Not available  
**Recommended use** Cleaner  
**Recommended restrictions** None known.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** Nu-Calgon  
**Address** 2008 Altom Court  
 St. Louis, MO 63146  
 United States  
**Telephone** 314-469-7000 / 800-554-5499  
**E-mail** info@nucalgon.com

**Emergency phone number** 1-800-424-9300 (CHEMTREC)

## 2. Hazards Identification

**Physical hazards** Gases under pressure Liquefied gas  
**Health hazards** Serious eye damage/eye irritation Category 1  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

#### Label elements



**Signal word** Danger

**Hazard statement** Contains gas under pressure; may explode if heated. Causes serious eye damage.

#### Precautionary statement

**Prevention** Wear eye/face protection.

**Response** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.

**Storage** Protect from sunlight. Store in a well-ventilated place.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** Not applicable.

## 3. Composition/Information on Ingredients

#### Mixtures

| Chemical name                            | Common name and synonyms | CAS number | %    |
|--|--------------------------|------------|------|
| Butane                                   |                          | 106-97-8   | 2.95 |
| Diethylene glycol monoethyl ether        |                          | 111-90-0   | 2.84 |
| Propane                                  |                          | 74-98-6    | 2.05 |
| Ethanol, 2-butoxy-                       |                          | 111-76-2   | 2    |
| Tetrasodium ethylenediamine tetraacetate |                          | 64-02-8    | 1.64 |
| Sodium metasilicate                      |                          | 6834-92-0  | 0.14 |

## 4. First Aid Measures

**Inhalation** If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

|   |   |
|---|---|
| <b>Skin contact</b>   | Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.   |
| <b>Eye contact</b>  | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. |
| <b>Ingestion</b>  | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.  |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Symptoms may include stinging, tearing, redness, swelling, and blurred vision.  |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically.  |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.  |

## 5. Fire Fighting Measures

|  |  |
|--|--|
| <b>Suitable extinguishing media</b>                                  | Alcohol foam. Carbon dioxide. Dry chemical. Foam.  |
| <b>Unsuitable extinguishing media</b>                                | None known.  |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure.   |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.   |
| <b>Fire-fighting equipment/instructions</b>                          | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>Specific methods</b>  | Cool containers exposed to flames with water until well after the fire is out.   |

## 6. Accidental Release Measures

|  |  |
|--|--|
| <b>Personal precautions, protective equipment and emergency procedures</b> | Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.  |
| <b>Methods and materials for containment and cleaning up</b>               | Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. |
| <b>Environmental precautions</b>   | Avoid discharge into drains, water courses or onto the ground.   |

## 7. Handling and Storage

|   |  |
|---|--|
| <b>Precautions for safe handling</b>                                | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. |
| <b>Conditions for safe storage, including any incompatibilities</b> | Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).  |

## 8. Exposure Controls/Personal Protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                        | Type | Value                              |
|-----------------------------------|------|------------------------------------|
| Ethanol, 2-butoxy- (CAS 111-76-2) | PEL  | 240 mg/m <sup>3</sup>              |
| Propane (CAS 74-98-6)             | PEL  | 50 ppm                             |
|                                   |      | 1800 mg/m <sup>3</sup><br>1000 ppm |

**US. ACGIH Threshold Limit Values**

| Components                        | Type | Value    |
|-----------------------------------|------|----------|
| Butane (CAS 106-97-8)             | STEL | 1000 ppm |
| Ethanol, 2-butoxy- (CAS 111-76-2) | TWA  | 20 ppm   |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                        | Type | Value                  |
|-----------------------------------|------|------------------------|
| Butane (CAS 106-97-8)             | TWA  | 1900 mg/m3<br>800 ppm  |
| Ethanol, 2-butoxy- (CAS 111-76-2) | TWA  | 24 mg/m3<br>5 ppm      |
| Propane (CAS 74-98-6)             | TWA  | 1800 mg/m3<br>1000 ppm |

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

| Components                                       | Type | Value               |
|--|------|---------------------|
| Diethylene glycol monoethyl ether (CAS 111-90-0) | TWA  | 140 mg/m3<br>25 ppm |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components                        | Value    | Determinant                              | Specimen            | Sampling Time |
|-----------------------------------|----------|--|---------------------|---------------|
| Ethanol, 2-butoxy- (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | *             |

\* - For sampling details, please see the source document.

**Exposure guidelines****US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants**

2-BUTOXYETHANOL (EGBE) (CAS 111-76-2) Can be absorbed through the skin.

**US. Minnesota Hazardous Substances List (Minn. Rules 5206.0400).**

Ethanol, 2-butoxy- (CAS 111-76-2) Skin designation applies.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Ethanol, 2-butoxy- (CAS 111-76-2) Can be absorbed through the skin.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Ethanol, 2-butoxy- (CAS 111-76-2) Can be absorbed through the skin.

**US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A**

Ethanol, 2-butoxy- (CAS 111-76-2) Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical splash goggles.

**Skin protection**

**Hand protection** Wear protective gloves.

**Other** Not available.

**Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA).

**Thermal hazards** Not applicable.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and Chemical Properties**

|                       |                          |
|-----------------------|--------------------------|
| <b>Appearance</b>     | Compressed liquefied gas |
| <b>Physical state</b> | Gas.                     |
| <b>Form</b>           | Liquefied gas.           |
| <b>Color</b>          | Clear                    |
| <b>Odor</b>           | Lemon lime               |

|   |   |
|---|---|
| <b>Odor threshold</b>                               | Not available.  |
| <b>pH</b>   | 12.3  |
| <b>Melting point/freezing point</b>                 | Not available.  |
| <b>Initial boiling point and boiling range</b>      | 32 - 401 °F (0 - 205 °C)  |
| <b>Pour point</b>                                   | Not available.  |
| <b>Specific gravity</b>                             | Not available.  |
| <b>Partition coefficient (n-octanol/water)</b>      | Not available   |
| <b>Flash point</b>                                  | Not available.  |
| <b>Evaporation rate</b>                             | Not available   |
| <b>Flammability (solid, gas)</b>                    | Not applicable.   |
| <b>Upper/lower flammability or explosive limits</b> |   |
| <b>Flammability limit - lower (%)</b>               | Not available.  |
| <b>Flammability limit - upper (%)</b>               | Not available.  |
| <b>Explosive limit - lower (%)</b>                  | Not available.  |
| <b>Explosive limit - upper (%)</b>                  | Not available.  |
| <b>Vapor pressure</b>                               | 65 psi @ 70°F   |
| <b>Vapor density</b>                                | Not available   |
| <b>Relative density</b>                             | Not available.  |
| <b>Solubility(ies)</b>                              | Not available   |
| <b>Auto-ignition temperature</b>                    | Not available   |
| <b>Decomposition temperature</b>                    | Not available.  |
| <b>Viscosity</b>                                    | Not available.  |
| <b>Other information</b>                            |   |
| <b>Flash point class</b>                            | Not Flammable as per testing under UN Manual of Tests and Criteria Part 3, Section 31.5 |

---

## 10. Stability and Reactivity

---

|   |   |
|---|---|
| <b>Reactivity</b>                         | Reacts vigorously with acids.   |
| <b>Possibility of hazardous reactions</b> | No dangerous reaction known under conditions of normal use.   |
| <b>Chemical stability</b>                 | Material is stable under normal conditions.   |
| <b>Conditions to avoid</b>                | Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals. Contact with incompatible materials.                                 |
| <b>Incompatible materials</b>             | Not corrosive to SAE 1020 Steel or non-clad Aluminum based on test data (UN Manual of Tests and Criteria, Part III, Section 37.1 -Corrosion to metals).<br><br>Oxidizing agents. Acids. |
| <b>Hazardous decomposition products</b>   | May include and are not limited to: Oxides of carbon.   |

---

## 11. Toxicological Information

---

### Information on likely routes of exposure

|                     |   |
|---------------------|---|
| <b>Ingestion</b>    | Expected to be a low ingestion hazard.  |
| <b>Inhalation</b>   | Prolonged inhalation may be harmful.  |
| <b>Skin contact</b> | Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®). |
| <b>Eye contact</b>  | Causes serious eye damage.  |

**Symptoms related to the physical, chemical and toxicological characteristics**      Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

### Information on toxicological effects

**Acute toxicity**

| Components                                       | Species       | Test Results              |
|--|---------------|---------------------------|
| Butane (CAS 106-97-8)                            |               |                           |
| <b>Acute</b>                                     |               |                           |
| <i>Dermal</i>                                    |               |                           |
| LD50   | Not available |                           |
| <i>Inhalation</i>                                |               |                           |
| LC50   | Mouse         | 680 mg/l, 2 Hours         |
|  | Rat           | 276000 ppm, 4 Hours       |
|  |               | 658 mg/l/4h               |
| <i>Oral</i>                                      |               |                           |
| LD50   | Not available |                           |
| Diethylene glycol monoethyl ether (CAS 111-90-0) |               |                           |
| <b>Acute</b>                                     |               |                           |
| <i>Dermal</i>                                    |               |                           |
| LD50   | Guinea pig    | 5900 mg/kg                |
|  | Mouse         | 6000 mg/kg                |
|  | Rabbit        | 6000 mg/kg                |
|  | Rat           | 6000 mg/kg                |
| <i>Inhalation</i>                                |               |                           |
| LC50   | Rat           | 5240 mg/l/4h              |
| <i>Oral</i>                                      |               |                           |
| LD50   | Guinea pig    | 3000 mg/kg                |
|  | Rabbit        | 3620 mg/kg                |
|  | Rat           | 5500 mg/kg                |
|  |               | 1920 mg/kg                |
| Ethanol, 2-butoxy- (CAS 111-76-2)                |               |                           |
| <b>Acute</b>                                     |               |                           |
| <i>Dermal</i>                                    |               |                           |
| LD50   | Guinea pig    | 207 mg/kg                 |
|  | Rabbit        | 400 mg/kg                 |
|  |               | 220 mg/kg                 |
|  |               | 99 mg/kg                  |
|  | Rat           | 99 mg/kg                  |
| <i>Inhalation</i>                                |               |                           |
| LC50   | Mouse         | 700 ppm, 7 Hours          |
|  | Rat           | 450 ppm, 4 Hours          |
|  |               | 2.2 mg/l, 4 Hours         |
| <i>Oral</i>                                      |               |                           |
| LD50   | Guinea pig    | 1200 mg/kg                |
|  | Mouse         | 1200 mg/kg                |
|  | Rabbit        | 320 mg/kg                 |
|  | Rat           | 470 mg/kg                 |
| Propane (CAS 74-98-6)                            |               |                           |
| <b>Acute</b>                                     |               |                           |
| <i>Dermal</i>                                    |               |                           |
| LD50   | Not available |                           |
| <i>Inhalation</i>                                |               |                           |
| LC50   | Rat           | > 1442.8 mg/l, 15 Minutes |
| <i>Oral</i>                                      |               |                           |
| LD50   | Not available |                           |

| Components  | Species  | Test Results |
|---|--|--------------|
| Sodium metasilicate (CAS 6834-92-0)                                       |  |              |
| <b>Acute</b>  |  |              |
| <i>Dermal</i>   |  |              |
| LD50  | Not available  |              |
| <i>Inhalation</i>   |  |              |
| LC50  | Not available  |              |
| <i>Oral</i>   |  |              |
| LD50  | Mouse  | 2400 mg/kg   |
|   | Rat  | 1153 mg/kg   |
| Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)                    |  |              |
| <b>Acute</b>  |  |              |
| <i>Dermal</i>   |  |              |
| LD50  | Not available  |              |
| <i>Inhalation</i>   |  |              |
| LC50  | Not available  |              |
| <i>Oral</i>   |  |              |
| LD50  | Rat  | 1658 mg/kg   |
| <b>Skin corrosion/irritation</b>  | Not corrosive to skin based on in-vitro test data (OECD Guideline 435 - Corrositex®).                            |              |
| <b>Exposure minutes</b>   | Not available.   |              |
| <b>Erythema value</b>   | Not available.   |              |
| <b>Oedema value</b>   | Not available.   |              |
| <b>Serious eye damage/eye irritation</b>                                  | Causes serious eye damage.   |              |
| <b>Corneal opacity value</b>  | Not available.   |              |
| <b>Iris lesion value</b>  | Not available.   |              |
| <b>Conjunctival reddening value</b>                                       | Not available.   |              |
| <b>Conjunctival oedema value</b>  | Not available.   |              |
| <b>Recover days</b>   | Not available.   |              |
| <b>Respiratory or skin sensitization</b>                                  |  |              |
| <b>Respiratory sensitization</b>  | Not available.   |              |
| <b>Skin sensitization</b>   | This product is not expected to cause skin sensitization.  |              |
| <b>Germ cell mutagenicity</b>   | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |              |
| <b>Carcinogenicity</b>  | This product is not considered to be a carcinogen by IARC, NTP, or OSHA.   |              |
| <b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>             |  |              |
| Ethanol, 2-butoxy- (CAS 111-76-2)   | 3 Not classifiable as to carcinogenicity to humans.  |              |
| <b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b> |  |              |
| Not listed.   |  |              |
| <b>Reproductive toxicity</b>  | This product is not expected to cause reproductive or developmental effects.                                     |              |
| <b>Specific target organ toxicity - single exposure</b>                   | Not classified.  |              |
| <b>Specific target organ toxicity - repeated exposure</b>                 | Not classified.  |              |
| <b>Aspiration hazard</b>  | Not likely, due to the form of the product.  |              |
| <b>Chronic effects</b>  | Prolonged inhalation may be harmful.   |              |
| <b>Further information</b>  | Not available.   |              |

## 12. Ecological Information

|  |                |                     |                     |
|--|----------------|---------------------|---------------------|
| <b>Ecotoxicity</b>                               | See below      |                     |                     |
| <b>Components</b>                                | <b>Species</b> | <b>Test Results</b> |                     |
| Diethylene glycol monoethyl ether (CAS 111-90-0) |                |                     |                     |
| Crustacea  | EC50           | Daphnia             | 4305 mg/L, 48 Hours |

| Components   |      | Species  | Test Results               |
|--|------|--|----------------------------|
| <b>Aquatic</b>   |      |  |                            |
| Fish   | LC50 | Bluegill ( <i>Lepomis macrochirus</i> )          | > 10000 mg/l, 96 hours     |
| Ethanol, 2-butoxy- (CAS 111-76-2)                      |      |  |                            |
| Crustacea  | EC50 | Daphnia  | 1819 mg/L, 48 Hours        |
| <b>Aquatic</b>   |      |  |                            |
| Fish   | LC50 | Inland silverside ( <i>Menidia beryllina</i> )   | 1250 mg/l, 96 hours        |
| Sodium metasilicate (CAS 6834-92-0)                    |      |  |                            |
| <b>Aquatic</b>   |      |  |                            |
| Crustacea  | EC50 | Water flea ( <i>Ceriodaphnia dubia</i> )         | 0.28 - 0.57 mg/l, 48 hours |
| Fish   | LC50 | Western mosquitofish ( <i>Gambusia affinis</i> ) | 1800 mg/l, 96 hours        |
| Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8) |      |  |                            |
| Algae  | EC50 | Algae  | 1.01 mg/L, 72 Hours        |
| <b>Aquatic</b>   |      |  |                            |
| Crustacea  | EC50 | Water flea ( <i>Daphnia magna</i> )              | 610 mg/l, 24 hours         |
| Fish   | LC50 | Bluegill ( <i>Lepomis macrochirus</i> )          | 472 - 500 mg/l, 96 hours   |

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

|                                   |       |
|-----------------------------------|-------|
| Butane                            | 2.89  |
| Diethylene glycol monoethyl ether | -0.54 |
| Ethanol, 2-butoxy-                | 0.83  |
| Propane                           | 2.36  |

**Mobility in soil** No data available.

**Mobility in general** Not available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal Considerations

|  |   |
|--|---|
| <b>Disposal instructions</b>                 | Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Local disposal regulations</b>            | Dispose in accordance with all applicable regulations.  |
| <b>Hazardous waste code</b>                  | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.  |
| <b>Waste from residues / unused products</b> | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).  |
| <b>Contaminated packaging</b>                | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.  |

### 14. Transport Information

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

|                             |  |
|-----------------------------|--|
| <b>UN number</b>            | UN1950   |
| <b>Proper shipping name</b> | Aerosols, non-flammable, (each not exceeding 1 L capacity) |
| <b>Hazard class</b>         | Limited Quantity - US                                      |
| <b>Packaging exceptions</b> | 306  |
| <b>Packaging non bulk</b>   | None   |
| <b>Packaging bulk</b>       | None   |

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

|                             |                           |
|-----------------------------|---------------------------|
| <b>UN number</b>            | UN1950                    |
| <b>Proper shipping name</b> | AEROSOLS, non-flammable   |
| <b>Hazard class</b>         | Limited Quantity - Canada |
| <b>Special provisions</b>   | 80                        |

**IATA/ICAO (Air)**

**Basic shipping requirements:**


**UN number** UN1950  
**Proper shipping name** Aerosols, non-flammable  
**Hazard class** Limited Quantity - IATA  
**ERG code** 2L

**IMDG (Marine Transport)**

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** AEROSOLS  
**Hazard class** Limited Quantity - US

**DOT; IMDG; TDG**



**IATA**



---

**15. Regulatory Information**

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

|  |         |
|--|---------|
| Butane (CAS 106-97-8)                            | Listed. |
| Diethylene glycol monoethyl ether (CAS 111-90-0) | Listed. |
| Ethanol, 2-butoxy- (CAS 111-76-2)                | Listed. |
| Propane (CAS 74-98-6)                            | Listed. |

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - No  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

| <b>Chemical name</b>              | <b>CAS number</b> | <b>% by wt.</b> |
|-----------------------------------|-------------------|-----------------|
| Diethylene glycol monoethyl ether | 111-90-0          | 2.84            |
| Ethanol, 2-butoxy-                | 111-76-2          | 2               |



**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Diethylene glycol monoethyl ether (CAS 111-90-0)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Clean Water Act (CWA) Section 112(r) (40 CFR 68.130)** Hazardous substance

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations** California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**US - California Hazardous Substances (Director's): Listed substance**

Butane (CAS 106-97-8) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Not listed.

**US - Illinois Chemical Safety Act: Listed substance**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US - Louisiana Spill Reporting List: Reportable quantity (total mass into atmosphere)**

Diethylene glycol monoethyl ether (CAS 111-90-0) 100 LBS

Ethanol, 2-butoxy- (CAS 111-76-2) 100 LBS

**US - Louisiana Spill Reporting: Listed substance**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US - Minnesota Haz Subs: Listed substance**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US - New Jersey RTK - Substances: Listed substance**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US. Massachusetts RTK - Substance List**

Butane (CAS 106-97-8) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US. Pennsylvania RTK - Hazardous Substances**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.

**US. Rhode Island RTK**

Butane (CAS 106-97-8) Listed.

Diethylene glycol monoethyl ether (CAS 111-90-0) Listed.

Ethanol, 2-butoxy- (CAS 111-76-2) Listed.

Propane (CAS 74-98-6) Listed.


| <b>Country(s) or region</b> | <b>Inventory name</b>                         | <b>On inventory (yes/no)*</b> |
|-----------------------------|---|-------------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes                           |

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

## 16. Other Information

| LEGEND   |   |
|----------|---|
| Severe   | 4 |
| Serious  | 3 |
| Moderate | 2 |
| Slight   | 1 |
| Minimal  | 0 |

|                     |     |
|---------------------|-----|
| HEALTH              | / 2 |
| FLAMMABILITY        | 1   |
| PHYSICAL HAZARD     | 0   |
| PERSONAL PROTECTION | X   |



### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

24-September-2014

### Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

### Other information

This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

### Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000