

### **Safety Data Sheet**

SDS Name: Lighter Flints, FL34, FL34D, FL3437TC, FL35, FL36, FL37

1. Identification

**Product Name:** Lighter Flints

Relevant identified uses of the substance or mixture and uses advised against

Application of the substance /

**the preparation:** Raw material for industrial applications.

Lighter Flints

Details of the supplier of the safety data sheet

**Supplier:** Uniweld Products, Inc.,

Address: 2850 Ravenswood Road, Ft. Lauderdale, FL 33312 United States of America

**Emergency:** For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak,

Fire, Exposure, or Accident Call CHEMTREC Day or Night within USA and Canada: 1-800-424-9300 or +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Classification of the

**substance or mixture**The product is not classified according to the Globally Harmonized System (GHS).

**Label elements** 

GHS label elements
Hazard pictograms
Signal word
Hazard statements

Void
Void

Classification system:NFPA ratings (scale 0 - 4)



Health = 0 Fire = 0 Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH 0 Health = 0

FIRE 0 Fire = 0

REACTIVITY 0 Reactivity = 0

Other hazards Lighter flints in the delivered form (cylindrical pieces) have no special risk.

Moderate risk of explosions of fine material.

Dust can have irritant effects to eyes and respiratory organs.

Inappropriate use of lighter flints (e.g. use for sparking effects) can lead to fire

and burn injuries.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 1/10

### 3. Composition/information on ingredients

**Chemical characterization: Substances** 

Ferro Cerium Lighter Flints

**Product name:** Ferro Cerium

**Lighter Flints** Chemical characterization: Mixtures

**Components:** 

 Mischmetal (Rare Earth Metals)
 > 76%

 CAS: 7439-89-6
 Iron
 ~20%

EINECS: 231-096-4

Reg.nr.: 01-2119462838-24-0360

CAS: 7439-95-4 Magnesium EINECS: 231-104-6 -Pyr. Sol. 1, H250; Water-react. 1, H260

EINECS: 231-104-6 -Pyr. Sol. 1, H250; Water-react. 1, H260 Index number: 012-001-00-3

**Additional information:** Rare Earth Mischmetal contains:

Cerium (EINECS: 231-154-9; CAS: 7440-45-1) Lanthanum (EINECS: 231-099-0; CAS: 7439-91-0) ~2%

#### 4. First-Aid Measures

**Description of first aid measures** 

After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

**After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Most important symptoms and effects,

both acute and delayed

No further relevant information available.

**Information for doctor:** Treat symptomatically.

Indication of any immediate medical

attention and special treatment needed No further relevant information available.

#### 5. Fire-Fighting Measures

**Extinguishing media** 

Suitable extinguishing agents: Dry sand

Fire-extinguishing powder

Special powder for metal fires. Do not use water.

For safety reasons unsuitable

extinguishing agents:

Water

Carbon dioxide Halogen extinguisher

Special hazards arising from the

substance or mixture

In case of fire, the following can be released:

Toxic metal oxide smoke

Advice for firefighters

**Protective equipment:** Wear self-contained respiratory protective device.

Wear fully protective suit.

**Additional information:** Cover all exposed surfaces with sand, salt or metal-extinguisher powder.

Material should not be mixed until the material has been allowed to cool down. Dispose of fire debris and contaminated firefighting water in accordance with

official regulations.

Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 2/10



### **6. Accidental Release Measures**

Personal precautions, protective

equipment and emergency procedures Avoid formation of dust.

Keep away from ignition sources

**Environmental precautions:** No special measures required.

Methods and material for

containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Use non-sparking tools, because the rubbing of the product with metallic objects

may cause a formation of sparks.

Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7. Handling and Storage

**Precautions for safe handling** Prevent formation of dust.

When working with powdered material it is recommended to use a dry inert gas

atmosphere and a local explosion proof exhaust system.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep away from oxidizing agents.

Finely distributed particles may be flammable or explosive.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep receptacle tightly sealed.

Store in dry conditions.

·Information about storage in one common storage facility:

Store away from flammable substances.

Do not store together with acids. Store away from oxidizing agents.

Store away from water.

**Further information about** 

storage conditions:

Protect from contamination.

Never store lighter flints uncontrolled.

Specific end use(s) No further relevant information available.

3/10 **Lighter Flints** Version#: 01 Issue date: 5-May-2015 **SDS Uniweld** 

# **8. Exposure Controls/Personal Protection**

Additional information about design of technical systems:


Ensure good ventilation/exhaustion at the workplace.

Control parameters Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### **DNELs**

7440-45-1 Cerium			
Oral Dermal	DNEL system. Effects DNEL system. Effects	3.04 mg/kg bw/day (Human (consumer)) 3.04 mg/kg bw/day (Human (consumer)) 5.07 mg/kg bw/day (Human (worker))	
Inhalative	DNEL system. effects	6 mg/m³ (Human (consumer)) 10 mg/m³ (Human (worker))	
7439-91-0 Lanthanum			
Oral	Oral Acute syst. Effects LT syst. Effects	(General Population) No hazard identified (General Population) No hazard identified	
Dermal	Acute local effects	(General Population) No hazard identified (Human (worker) No hazard identified	
	Acute syst. Effects	(General Population) No hazard identified	
	LT local effects	(General Population) No hazard identified	
	LT syst. effects	(General Population) No hazard identified (Human (worker) No hazard identified	
Inhalative	Acute local effects	(General Population) No hazard identified	
	Acute syst. Effects	(General Population) No hazard identified	
	DNEL acute effects	(Human (worker) No hazard identified	
	DNEL local effects	(Human (worker) No hazard identified	
	LT local effects	(General Population) No hazard identified	
	LT syst. Effects	(General Population) No hazard identified (Human (worker) No hazard identified	
Irritation of eyes	Local effects	(General Population) No hazard identified (Human (worker) No hazard identified	
PNECs			
7440-45-1 Cerium			
PNEC STP	60.9 mg/l (Microorganisms (activated sludge)) (OECD 209 (Activated Sludge, Resp. Inhibition Test)) Test material: Dicerium tricarbonate Grutzner I (2006)		
PNEC freshwater	0.6 mg/l (Freshwater organisms) Extrapolation method: assessment factor		
PNEC marine	60.9 μg/l (Marine organisms) Extrapolation method: assessment factor		
7439-91-0 Lanthanum			
PNEC	No hazard identified		





**Additional information:** The lists that were valid during the creation were used as basis.

**Exposure controls** 

Personal protective equipment:

**General protective and** 

**hygienic measures:** Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

**Breathing equipment:** Not necessary if room is well-ventilated.

**Protection of hands:** Protective gloves

**Material of gloves** Wear gloves for the protection against mechanical hazards according to EN 388.

**Penetration time of glove material** The exact break through time has to be found out by the manufacturer of

The protective gloves and has to be observed.

**Eye protection:** Safety glasses

**Body protection:** Protective work clothing

#### 9. Physical and Chemical Properties

Information on basic physical and chemical properties

**General Information** 

**Appearance:** 

Form: Solid, Lumpy

Color: Grey

-Different according to coloring

**Odor:** Odorless

Odor threshold: Not applicable pH-value: Not applicable

**Melting point/Melting range:** ca. 700 °C (ca. 1292 °F) **Boiling point/Boiling range:** ca. 1100 °C (ca. 2012 °F)

Flash point: Not applicable Flammability (solid, gaseous): Flammable.

**Ignition temperature:** Solid material (flints): 400 °C (752°F)

Powder: 195 - 280 °C (338°F - 536°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Lighter flints: not applicable. Powder: not determined.

**Explosion limits:** 

Lower: Not determined Upper: Not determined

Oxidizing properties Lumpy: none

In form of powder: yes.

**Density:** 6.5 g/cm<sup>3</sup> (54.243 lbs/gal)

Solubility in / Miscibility with

Water: Insoluble.

Partition coefficient (n-octanol/water): Not determined

Viscosity:

**Dynamic:** Not determined **Kinematic:** Not determined

**Other information** No further relevant information available.

Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 5/10



## **10. Stability and Reactivity**

Reactivity Chemical stability

Thermal decomposition /

conditions to be avoided: Lumpy material is stable against corrosion.

Reacts with strong oxidizing agents. Reacts with water and acids. Possibility of hazardous reactions

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** Keep away from water.

Keep away from oxidising agents and acidic substances.

No dangerous decomposition products known **Hazardous decomposition products:** 

**Additional information:** If ferro mischmetal gets inadvertently wet, put it on an absorptive material and

dry it with warm air (not to hot).

### 11. Toxicological Information

Information on toxicological effects

Acute toxicity:

7440-45-1 Cerium

LD/LC50 values that are relevant for classification:

/440-45-1 Cerium		
Oral	LD50	> 5000 mg/kg (rat (Sprague-Dawley) (EPA OPPTS 870.1100 (Acute Oral Toxicity)) Test material: Dicerium tricarbonate Lambert CE, Barnum EC, Shapiro R (1993)
	NOAEL	150 mg/kg bw/day (rat (Sprague-Dawley)) (OECD Guideline 422) Repeated dose toxicity oral Test material: Dicerium tricarbonate Target organs: digestive: stomach
Inhalative	LC50/4 h	5.05 mg/l (rat (wistar)) (OECD Guideline 403 (Acute Inhalation Toxicity)) Test material: Dicerium tricarbonate F. Duchosal (1993)
7439-91-0 Lanthanum		
Oral	LD50	- mg/kg (-) Study technically not feasible
	NOAEL	10648 ppm (rat (wistar)) (OECD Guideline 408; EU Method B.7) read-across from supporting substance(structural analogue or surrogate) Test material: lanthanum carbonate octahydrate 1126 mg/kg bw/day (rat (wistar - female)) (OECD Guideline 408; E U Method B.7) Read-across von unterstützender Substanz (Strukturanalog oder Ersatz) Testmaterial: Lanthankarbonat oktahydrat 741 mg/kg bw/day (rat (wistar - male)) (OECD Guideline 408; EU Method B.7) read-across from supporting substance (structural analogue or surrogate) Test material: lanthanum carbonate octahydrate
Dermal	LD50	mg/kg (-) Study technically not feasible
Inhalative	LC50	mg/kg (-) Study technically not feasible
Irritation of skin		-(-) Study technically not feasible
Irritation of eyes Study technically not feasible		-(-)
7439-89-6 Iron		
Oral	LD50	20000 mg/kg (Guinea pig) Lit.: Indian Journal of Pharmacy. Vol. 13, Pg. 240, 1951. 30000 mg/kg (Rat) Lit.: Indian Journal of Pharmacy. Vol. 13, Pg. 240, 1951.

**Lighter Flints** SDS Uniweld 6/10 Version#: 01 Issue date: 5-May-2015



**on the skin:**No data available.

on the eye: No data available.

**Sensitization:** No sensitizing effects known.

Other information

**about experimental toxicology):** Warning, substance not yet fully tested

**Additional toxicological information:** The product is not subject to classification according to internally approved

calculation methods for preparations:

Carcinogenic categories IARC (International Agency for

Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Not determined

#### 12. Ecological Information

Toxicity

· Aquatic toxicity:

#### 7440-45-1 Cerium

EC50/72h >100 mg/l (Desmodesmus subspicatus) (OECD Guideline 201 (Alga, Growth Inhibition Test))

Test material: Dicerium tricarbonate

Bätscher Roger (2007)

LC50/48h > 100 mg/l (Daphnia magna) (OECD Guideline 202; EU Method C.2)

Test material: Dicerium tricarbonate

Bätscher R (2007b)

LC50/96h > 100 mg/l (Oncorhynchus mykiss) (OECD Guideline 203; EU Method C.1)

Test material: Dicerium tricarbonate

Bätscher R (2007a)

#### 7439-91-0 Lanthanum

EC50/48h mg/l (Daphnia)

Study technically not feasible

EC50/72h = EC50/72h - mg/l (Ag)

Study technically not feasible

Persistence and degradability Not determined

Bioaccumulative potential Not determined

**Mobility in soil** No further relevant information available.

**Additional ecological information:** 

**AOX-indication:** The product does not contain organically bounded halogens (AOX-free).

**General notes:** Generally not hazardous for water

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available

Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 7/10



### 13. Disposal Considerations

**Waste treatment methods Recommendation:** 

Ferro Mischmetal tends to oxidize if they are stored for a longer time. The formed oxides are mostly available in form of powder. Powder and swarf of Mischmetal have pyrophoric properties and spontaneous ignition is possible. Put small portions of about 100 g in 1 l saltwater (5 - 15 %) in a metallic vessel and place it outside buildings. Wait till the reaction process (Hydrogen development) is finished, which may take a few days. The remaining sludge can be disposed riskless. In case of doubt contact manufacturer or supplier.

Disposal must be made according to official regulations.

Waste disposal key: 51310 (ÖNORM S 2100)

**European waste catalogue** 06 03 16

**Uncleaned packagings: Recommendation:** 

Packaging that cannot be cleansed are to be disposed of in the same manner as

the product.

Disposal must be made according to official regulations.

## 14. Transport Information

**UN-Number** 

DOT, ADR, ADN, IMDG, IATA Void

**UN proper shipping name** DOT, ADR, ADN, IMDG, IATA

Void

Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA

Class Void

**Packing group** 

DOT, AĎŘ, IMDG, IATA Void

**Environmental hazards:** Not applicable Special precautions for user Not applicable.

Transport in bulk according to Annex II

of MARPOL73/78 and the IBC Code Not applicable.

Version#: 01

**Transport/Additional information:** Not dangerous according to the above specifications.

**IATA** No dangerous good according to "IATA Dangerous Goods

Regulation (DGR) 55th Edition 2014"

UN "Model Regulation": -

**Lighter Flints** 

8/10 Issue date: 5-May-2015 **SDS Uniweld** 

## 15. Regulatory Information

**REACH-Registration number:** Cerium: 01-2119480148-35-0000

Lanthanum: 01-2119971281-39-0000 Iron: 01-2119462838-24-0360

Safety, health and environmental regulations/legislation specific for the substance or mixture

Sara

Section 302

(extremely hazardous substances): None of the ingredients is listed.

Section 313

**(Specific toxic chemical listings):** None of the ingredients is listed.

**TSCA (Toxic Substances Control Act):** All ingredients are listed.

**Proposition 65** 

**Chemicals known to cause cancer:** None of the ingredients is listed.

Chemicals known to cause

**reproductive toxicity for females:** None of the ingredients is listed.

Chemicals known to cause

**reproductive toxicity for males:** None of the ingredients is listed.

Chemicals known to cause

**developmental toxicity:**None of the ingredients is listed.

**Cancerogenity categories** 

**EPA (Environmental Protection Agency)** None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

MAK (German Maximum Workplace Concentration)

**Vorkplace Concentration**) None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

Occupational Safety and Health)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

**& Health Administration**) None of the ingredients is listed.

Canadian substance listings: Canadian Domestic Substances

**List (DSL)** All ingredients are listed.

**Canadian Ingredient Disclosure list** 

(**limit 0.1**%) None of the ingredients is listed.

**Canadian Ingredient Disclosure list** 

(**limit 0.1%**) None of the ingredients is listed.

**Philippines Inventory of Chemicals** 

and Chemical Substances All ingredients are listed.

Chinese Chemical Inventory

**of Existing Chemical Substances**7440-45-1 Cerium
7439-89-6 Iron

7439-95-4 Magnesium

Australian Inventory of Chemical Substances

nemical Substances All ingredients are listed.

Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 9/10



**Korean Existing Chemical Inventory** 7440-45-1 Cerium KE-05379

7439-91-0 Lanthanum KE-21820 7439-89-6 Iron KE-21059

7439-95-4 Magnesium KE-22673

Standard for the Uniform Scheduling

of Drugs and Poisons

7439-91-0 Lanthanum S4

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16. Other Information** 

**Relevant phrases** H250 Catches fire spontaneously if exposed to air.

H260 In contact with water releases flammable gases which may ignite spontaneously.

**Department issuing SDS:** HSE Department

Chemical Management

Date of preparation / last revision 5

5-May-2015

**Abbreviations and acronyms:**RID: Règlement international concernant le transport des marchandises dangereuses

par chemin de fer (Regulations Concerning the International Transport of Dangerous

Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods

by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

**ELINCS: European List of Notified Chemical Substances** 

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

\* Data compared to the previous version altered.



Lighter Flints Version#: 01 Issue date: 5-May-2015 SDS Uniweld 10/10